

davide groppi

HANDBOOK 2024

INDEX

WIRELESS / SENZA FILO	11	SUSPENSION / SOSPENSIONE	139
35MM	13	CARTESIO	141
BUGIA	17	CATHODE	145
PoPuP	21	FOSBURY	153
POST PRANDIUM	25	LED IS MORE	157
QuiQuoQua	31	LOUIS XIV	164
TeTaTeT	35	MISS	169
TeTaTeT Flûte	41	MOON	177
VIS À VIS	45	NEURO	185
		OVO	189
		OVONELPIATTO	193
TABLE / TAVOLO	49	REFLEX S	197
ABA 45	51	SHANGHAI	201
ANIMA	55	SIMBIOSI	205
CALVINO	59	SOTTILE	211
FM	63	SOTTOSOPRA	217
MOON T	67	SPY	221
MORSETTO	71		
PALPEBRA	77	WALL / PARETE	225
PIGRECO	81	DOT P	227
		DUET	233
FLOOR / TERRA	85	EDISON'S NIGHTMARE	237
ABA 120	87	FILM	241
BANNER	91	FOIL	245
HASHI	95	FOLDER	249
MASAI	99	LINET	253
MISTER	105	MIRA	257
MOON F	109	MIRA MAGNETIC	261
MOVIE	113	MORSETTO P	265
ORIGINE	117	PIÙ	269
PABLO	121	RAIL	273
Q	125	REFLEX	277
SAMPEI	129	SHADE	281
SHOJI	135	SOL 1	285
		SOL 2	289
		SPOT	293
		TOAST	299
		UTOPIA	305

CEILING / SOFFITTO	309	TRACKS - PROFILES / BINARI - PROFILI	483
ASINTOTO	311	BINARIO TRIFASE	485
AURORA	317	COLIBRI	497
DOT PL 51	321	FRAMELESS	509
HAKO PL	325	LIGHTLINE 0808	515
MINI PL 51	329	LIGHTLINE 1010	518
NULLA PL	333	LIGHTLINE 1508	520
PUNTO PL	337	LIGHTLINE 2612	522
PUNTO 2 PL	341	LIGHTLINE 7454	524
SANMARTINO	345		
SPY PL	349	OUTDOOR / ESTERNO	527
TRICK TRACK	353	BELLADINOTTE	529
		BUBKA	533
RECESSED / INCASSO	357	BUBKA BOLLARD	537
BUCO 58	359	CHILLOUT	541
BUCO R	363	GRILLO	545
DOT R	369	HAZARD	549
MINI 51	375	IMU	555
MINI BIT 51	379	JULIET	559
MIRA R	383	LENTA	563
NULLA	387	NEURO OUTDOOR	567
PUNTO	395	NUIT	571
PURA	399	ORIGINE OUTDOOR	575
QUAD	403	OUT 44	579
		OUT 58	583
		OUT 100	587
SYSTEMS / SISTEMI	407	Q²	591
ENDLESS	409	SAMPEI 440 OUTDOOR	595
FLASH	427	SHOJI OUTDOOR	599
INFINITO	443	SPOT IP65	603
MAGIA	457		
OHM	469	BULBS / LAMPADINE	606
		DG111 LED MODULES / MODULI LED	607
		DRIVERS	608
		COMMON ACCESSORIES / ACCESSORI COMUNI	612
		SUSPENSION FIXING KIT / KIT DI FISSAGGIO PER SOSPENSIONE	614
		COMMERCIAL TERMS / CONDIZIONI COMMERCIALI	618

INDEX

CODE SYSTEM / SISTEMA DI CODIFICA

Our codification system consists of a fifteen-digit structure defined as follows:
Il nostro sistema di codifica prevede una struttura a quindici cifre così definita:

1	A	3	0	0	0	3	0	0		2	7		0	0
PRODUCT FAMILY FAMIGLIA PRODOTTO					FINISH FINITURA		INTERNAL USE ONLY		-	COLOUR TEMPERATURE TEMPERATURA COLORE		-	ELECTRIFICATION ELETTRIFICAZIONE	

Finish / Finitura

0	0	Standard
0	1	Polished Chrome / Cromo Lucido
0	3	Matt White / Bianco Opaco
0	4	Matt Black / Nero Opaco
0	8	Brushed Brass / Ottone Spazzolato
1	0	Stainless Steel / Inox
1	3	Black Brushed Stainless Steel / Inox Nero Spazzolato
1	4	Brushed Chrome / Cromo Spazzolato
1	5	Natural Brass / Ottone Naturale
1	8	Matt Gold / Oro Opaco
1	9	Polished Gold / Oro Lucido
2	6	Total Black / Nero Totale
2	7	Gravity Black
2	8	Polished Black Chrome/ Cromo Nero Lucido
2	9	Brushed Champagne / Champagne Spazzolato
3	2	Copper Oxide
3	4	Matt White - Black Bicolour / Bianco - Nero Opaco Bicolore
3	6	Brushed Black Chrome / Cromo Nero Spazzolato
3	8	Blasted Inox / Inox Pallinato
4	1	Stainless Brushed Brass / Ottone Inossidabile Spazzolato

Colour temperature / Temperatura di colore

0	0	Light source not included / Sorgente non inclusa
2	2	2200K
2	7	2700K
3	0	3000K
9	6	2700 / 6500K (Tunable White)
9	8	RGBW (Warm White)
9	9	RGB

Electrification / Elettrificazione

0	0	ON/OFF
0	1	DALI
0	2	TRIAC/IGBT
0	3	1-10 V
0	4	PUSH
0	5	DIM (DALI - PUSH - 1-10 V - TRIAC)
0	6	Dimmer on board
0	7	DALI - PUSH - 1-10 V
2	0	CLASS III
4	0	ENDLESS
4	1	ENDLESS CASAMBI

GUIDELINE TO PROPERLY READ THE CATALOGUE / GUIDA ALLA LETTURA DEL CATALOGO

General data on the product
Informazioni generali sul prodotto

Mounting - Lighting - Use - Material - Finish - Note



Versions specifications
Specifiche modello

Technical data - Certifications - Codes

Compulsory and optional accessories
Accessori obbligatori e accessori opzionali

Accessories finishes and specifications - Codes

Reference version
Modello di riferimento

MOON					Davide Groppi / 2005
Suspension / Diffuse / Indoor					
Material Japanese Paper - PE					
Finish .00 Standard					
Note					Shade with japanese paper texture luminaires - 304 Stainless steel suspension cables - White cable. Apparecchio con paralume con texture in carta giapponese - Rossone bianco - Cavo di sospensione in acciaio INOX 304 - Cavo bianco.
	MOON 60 Max 15W - E27 100-240V - 50/60Hz Bulb not included ON/OFF C € IP20	Standard - ON/OFF		1A2820000.00.00	
	MOON 60 DE Max 15W - E27 + Max 10W - GU10 100-240V - 50/60Hz Bulb not included ON/OFF C € IP20	Standard - ON/OFF		1A2830000.00.00	
	MOON 80 Max 15W - E27 100-240V - 50/60Hz Bulb not included ON/OFF C € IP20	Standard - ON/OFF		1A2840000.00.00	
2					

Davide Groppi / 2005					MOON
	MOON 120 Max 2x25W - E27 100-240V - 50/60Hz Bulb not included ON/OFF C € IP20	Standard - ON/OFF		1A2850000.00.00	
	MOON 200 Max 4x25W - E27 100-240V - 50/60Hz Bulb not included ON/OFF C € IP20	Standard - ON/OFF		1A2860000.00.00	
Optional accessories / Accessori opzionali					
Installation kit / Kit installazione					
	Sloped rose fixing kit / Kit fissaggio rosone inclinato Nickel plated - 1 Piece	MOON 60 / MOON 60 DE / MOON 80	1A2520000.00.00	Not included	
	Sloped ceiling fixing kit / Kit fissaggio soffitto inclinato Nickel plated - 1 Piece	MOON 120	1A2510000.00.00	Not included	
Bulbs / Lampadine					
	LED - GU10 - PAR16 / 220-240V - 5.5W - 25° - 3000K - 375lm - CRI 97 - Energy Efficiency G - Dimmable	MOON 60 DE	50330500	Not included	
3					

PICTOGRAPHY / SIMBOLOGIA



Class II appliance: appliance whose protection against electric shock is not only relevant to the main insulation, but also includes additional safety measures, such as dual insulation or reinforced insulation. These measures do not include ground devices as protection and do not depend on the installation conditions.



Class III appliance: appliance whose safety against electric shock is based on safe extra low voltage power supply. Compliance with legislation is guaranteed only if the appliance is powered by a SELV safety transformer/driver in compliance with legislation in force. The appliance must not be connected to ground conductors.



Degree of protection against access of foreign bodies, dust and water.



Appliance with this symbol can only use low pressure bulbs or bulbs with safety glass.



Do not use cold light lamps.



To prevent the risk of fire, maintain the minimum distance indicated from the bulb with lighting objects. This distance should be measured along the optical axis of the appliance to the closest lighting object.



Color Rendering Index: the degree of colour distortion under a given light source in comparison with a reference light source. The optimum colour rendition index is Ra = 100.



The luminous flux, measured in lumen, indicates the quantity of light perceived by the human eye emitted by a light source. In Davide Groppi lights with an integrated module, the delivered lumen flux is obtained from the photometric measurement. In lights with a lightbulb included, the luminous flux is indicated provided by the manufacturer of the lightbulb.



Luminaire designed to be powered by ENDLESS system at 48 V DC.



Luminaire integrated with Casambi, the Bluetooth Low Energy (BLE) technology for lighting control.



Luminaire with Extradark comfort system. The Extradark system associates an optical TIR PMMA lens to an element that geometrically shields the light beam viewing angle to obtain highly uniform lighting and full beam control. The polished black light shield is used to control the mirror reflection of the light, perfectly controlling the unified glare rating (UGR* < 19).

Apparecchio in classe II: apparecchio in cui la protezione contro le scariche elettriche non interessa solamente l'isolamento principale, bensì comprende misure di sicurezza supplementari, come il doppio isolamento o l'isolamento rinforzato. Tali misure non comprendono mezzi di messa a terra come protezione e non dipendono dalle condizioni di installazione.

Apparecchio in classe III: apparecchio in cui la sicurezza contro la scossa elettrica si basa sull'alimentazione a bassissima tensione di sicurezza. La conformità alla normativa è garantita solo se l'apparecchio è alimentato da un trasformatore/driver di sicurezza SELV conforme alla normativa in vigore. L'apparecchio non deve essere collegato a conduttori di messa a terra.

Livello di protezione contro l'accesso di corpi estranei, polvere e acqua.

Apparecchio che può utilizzare solamente lampadine a bassa pressione o con vetro di protezione.

Non utilizzare lampade a luce fredda.

Per prevenire il rischio di incendio, mantenere come minimo la distanza indicata dalla lampadina agli oggetti illuminati. Tale distanza va misurata lungo l'asse ottico dell'apparecchio all'oggetto illuminato più vicino.

Color Rendering Index: grado di alterazione dei colori sotto una data illuminazione in confronto ad una sorgente luminosa di riferimento. L'indice ottimale di resa cromatica Ra è pari a 100.

Il flusso luminoso, misurato in lumen, indica la quantità di luce percepita dall'occhio umano emessa da una sorgente luminosa. Nelle lampade Davide Groppi con modulo integrato è indicato il reale flusso luminoso ricavato dal rilievo fotometrico. Nelle lampade in cui è inclusa una lampadina è indicato il flusso luminoso fornito dal fabbricante della lampadina stessa.

Apparecchio predisposto per essere alimentato dal sistema ENDLESS a 48 V DC.

Apparecchio in cui è integrata la tecnologia Bluetooth Low Energy (BLE), per il controllo dell'illuminazione, Casambi.

Apparecchio dotato di Extradark comfort system. Il sistema Extradark è l'unione di un'ottica TIR in PMMA ottico a un elemento che scherma geometricamente l'angolo di visione del fascio luminoso ottenendo un'elevata uniformità di illuminamento e il pieno controllo dell'emissione. L'elemento ottico schermante, con finitura nero lucido, permette di controllare la riflessione speculare della luce e quindi di controllare in maniera perfetta l'indice di abbagliamento (UGR* < 19).

*Unified Glare Rating

WIRELESS / SENZA FILO

Those dear old slides. Nobody pays any attention to them anymore.
It's the smallest lamp in our collection.
It's an idea, a thought, a pendant, something you can wear.
The pulsating light and the images you choose to display on it
make 35MM unique and exceptional.

La vecchia, cara diapositiva. Purtroppo ormai in disuso.
È la più piccola lampada della nostra collezione.
È un'idea, un pensiero, un ciondolo, luce da indossare.
La luce pulsante e le immagini personalizzabili
rendono 35MM un progetto unico ed eccezionale.



35MM

Alessandra Dallagiovanna - Davide Groppi / 2009

Objects / Diffuse / Wireless

Material

Metal - Polycarbonate


Finish

.00 Standard

Note

Slowly flashing light luminaire - White frame - Black back side - Customizable images not included.


Apparecchio a luce a lenta intermittenza - Telaio bianco - Retro nero - Immagine personalizzabile non inclusa.



35MM
0,3W
ON/OFF
Batteries 2 x CR2032 included
CE  IP20

Standard - ON/OFF

|1A2640000.00.00 |





BUGIA

Davide Groppi / 2018

A lightweight and soft light.

A lamp designed to enjoy wonderful diffuse light but without an electrical cable.


Una luce morbida e leggera.

Una lampada pensata per godere di una meravigliosa luce diffusa
senza il vincolo del cavo elettrico.

BUGIA

Davide Groppi / 2018

Table / Diffuse / Wireless	
Material	Metal - Methacrylate
Finish	.18 Matt Gold
Note	
Matt white diffuser luminaire - Gold finish base - Battery life 9 hours.	
Apparecchio con diffusore bianco opaco - Base verniciata dorata - Autonomia batteria 9 ore.	



BUGIA
2W
3000K - 120lm
CRI >90
ON/OFF
USB cable included -
Power supply not included
CE IP20

Matt Gold - 3000K - ON/OFF

1A2351800.30.00

Optional accessories / Accessori opzionali

Electrical power supply / Alimentazione elettrica



Power supply / Alimentatore		Not included
Matt Black	Input 110-240V - 50/60Hz - Output 5V DC - 2A - 10W - IP20	1Z0000088



USB to USB-C cable / Cavo da USB a USB-C		Included
Matt Black	Lenght 1m	1Z0000132





PoPuP

Davide Groppi / 2016

Light*Music*Wireless

Created to give you both light and music any place, at any time.

PoPuP accompanies you during your unforgettable moments.

The sounds it produces are dynamic and of excellent quality.

Light and sound can also be enjoyed separately.

Listen to the light.

Light*Music*Wireless

Ideata per ottenere luce e musica in qualsiasi luogo ed in qualunque momento.


PoPuP permette di vivere un'esperienza musicale emozionante

grazie ad un suono ampio e dinamico.

Luce e suono sono utilizzabili separatamente.


Ascolta la luce.

Table / Direct / Wireless	
Material	Metal - Methacrylate
Finish	.03 Matt White
Note	
Luminaire and acoustic diffuser with magnetic fixing base - Battery life: 12 hours for light only and 30 hours for audio only at medium volume.	
Apparecchio e diffusore audio con base a fissaggio magnetico - Autonomia batteria: 12 ore solo luce e 30 ore solo audio a medio volume.	


	PoPuP	
	2W	
	3000K - 183lm	
	CRI >80	
	ON/OFF	
	5W Audio - 50-20000Hz -	
	Charger included	
	CE IP20	
	Matt White - 3000K - ON/OFF	
	1A2610300.30.00	

Optional accessories / Accessori opzionali

Chargers / Caricabatterie

	Charger / Caricabatterie		Included
	Matt Black	Input 110-240V - 50/60Hz - Output 10000mAh - 4,2-14V DC - 18W - IP20	1Z1530030

Other accessories / Altri accessori

	Rechargeable battery / Batteria ricaricabile		Not included
	Matt White	12V DC - NiMH 3700mAh	1A2620300.00.00





POST PRANDIUM

Davide Groppi / 2023


...During a meal with friends, a ladle is reused to scoop up the light
and serve it onto the table.
A project from many years ago, today in a new wireless version.
Archiproducts Design Award 2023

...Durante una cena tra amici, un mestolo è ri-utilizzato
per raccogliere la luce e servirla al tavolo.
Un progetto di molti anni fa, oggi rieditato in versione wireless.
Archiproducts Design Award 2023

POST PRANDIUM

Davide Groppi / 2023

Table / Direct / Wireless	
Material	Metal - Methacrylate
Finish	.01 Polished Chrome
Note	
Matt black base luminaire - Gold finish details - Battery life 9 hours.	
Apparecchio con base nero opaco - Dettagli verniciati dorati - Autonomia batteria 9 ore.	




POST PRANDIUM
2W
3000K - 171lm
CRI >90
ON/OFF
USB cable included -
Power supply not included
CE IP20

Polished Chrome - 3000K - ON/OFF

1A4550100.30.00

Optional accessories / Accessori opzionali

Electrical power supply / Alimentazione elettrica



Power supply / Alimentatore		Not included
Matt Black	Input 110-240V - 50/60Hz - Output 5V DC - 2A - 10W - IP20	1Z0000088



USB to USB-C cable / Cavo da USB a USB-C		Included
Matt Black	Lenght 1,5m	1Z0000070





POST PRANDIUM



QuiQuoQua

Davide Groppi / 2017

The light where you want it.

A unique suspension lamp with a rechargeable battery.

The light source is applied magnetically to a metal dish that hangs from the ceiling

using a very thin steel wire. The effect is delicately elegant.

QuiQuoQua takes light where it is needed, without the limitation of electric wires.

La luce dove vuoi.

Un'inedita lampada a sospensione a batteria ricaricabile.

La parte ottica è applicata magneticamente ad una parabola e sospesa
attraverso un sottilissimo cavo in acciaio. L'effetto è delicatamente elegante.

QuiQuoQua offre la possibilità di portare la luce
dove si desidera senza il vincolo del cavo elettrico.

QuiQuoQua

Davide Groppi / 2017

Suspension / Direct / Wireless

Material

Metal - Methacrylate


Finish

.03 Matt White

Note

Magnetic fixing black LED module luminaire - 304 Stainless steel suspension cable - Battery life 8 hours.

Apparecchio con modulo LED nero a fissaggio magnetico - Cavo di sospensione in acciaio INOX 304 - Autonomia batteria 8 ore.



QuiQuoQua

5W

3000K - 345lm

CRI >80

ON/OFF

Charger included


CE IP20

Matt White - 3000K - ON/OFF

1A2630300.30.00

Optional accessories / Accessori opzionali

Chargers / Caricabatterie




Charger / Caricabatterie

Included

Matt Black	Input 110-240V - 50/60Hz - Output 9V DC - 20W - IP20	1Z1120170
------------	---	-----------

LED modules / Moduli LED




Magnetic fixing LED module / Modulo LED a fissaggio magnetico

Not included

Matt Black	5W - 3000K - 345lm - CRI >80 - Rechargeable lithium battery 9V DC - Li-Ion 5800mAh - Battery life 8 hours	1A0570400.30.00
------------	---	-----------------

Installation kit / Kit installazione




Sloped ceiling fixing kit / Kit fissaggio soffitto inclinato

Not included

	Nickel plated - 1 Piece	1A0510000.00.00
--	-------------------------	-----------------






A timeless icon with an eye on the future.
Portable and rechargeable, the greatest expression of freedom.
With TeTaTeT, every table becomes a meeting place, a complete dining experience.
Its light caresses those it illuminates with pure emotion.
Equipped with Touch technology and a magnetic fixing base.
Mention of Honour XXIV Compasso d'Oro ADI Award, 2016

Un'icona senza tempo, con lo sguardo rivolto al futuro.
Portatile e ricaricabile, la massima espressione della libertà.
Grazie a TeTaTeT, ogni tavola diventa un luogo d'incontro, ogni cena un'emozione.
La sua luce accarezza i volti e amplifica le sensazioni.
Dotata di accensione touch, il fissaggio alla base è magnetico.
Menzione d'Onore XXIV Compasso d'Oro ADI, 2016

Table / Direct / Wireless			
Material	ABS - Metal - Methacrylate		
Finish	.03 Matt White	.04 Matt Black	.18 Matt Gold
Note	Magnetic fixing base luminaire - ON/OFF touch - Battery life 12 hours.		
Apparecchio con base a fissaggio magnetico - ON/OFF touch - Autonomia batteria 12 ore.			




TeTaTeT
2W
2700K - 165lm / 3000K - 178lm
CRI >90
ON/OFF
Charger included
CE IP20

Matt White - 2700K - ON/OFF	1A0310300.27.00
Matt White - 3000K - ON/OFF	1A0310300.30.00
Matt Black - 2700K - ON/OFF	1A0310400.27.00
Matt Black - 3000K - ON/OFF	1A0310400.30.00
Matt Gold - 2700K - ON/OFF	1A0311800.27.00
Matt Gold - 3000K - ON/OFF	1A0311800.30.00


Optional accessories / Accessori opzionali

Chargers / Caricabatterie



Charger / Caricabatterie		Included
Matt Black	Input 110-240V - 50/60Hz - Output 6V DC - 1A - 6W - IP20	1Z0000073

Other accessories / Altri accessori



Rechargeable battery / Batteria ricaricabile			Not included
Matt White	4,8V DC - NiMH 4300mAh	1A0430300.00.00	
Matt Black	4,8V DC - NiMH 4300mAh	1A0430400.00.00	
Matt Gold	4,8V DC - NiMH 4300mAh	1A0431800.00.00	




Table / Tavolino		Not included
Matt White	1A4020300.00.00	
Matt Black	1A4020400.00.00	







TeTaTeT Flûte

Davide Groppi / 2017


This is an evolution of our TeTaTeT lamp.
The lamp head is lightweight and appears to be floating in air.
The transparent column brings to mind the glasses
used in the classic "mise en place".
Magnetic fixing base.

L'evoluzione del nostro modello TeTaTeT.
La testa appare leggera e sospesa nel vuoto.
Lo stelo trasparente evoca i bicchieri utilizzati nelle classiche "mise en place".
Il fissaggio alla base è magnetico.

TeTaTeT Flûte

Davide Groppi / 2017

Table / Direct / Wireless	
Material	Metal - Methacrylate
Finish	.03 Matt White
Note	
Magnetic fixing base and stem luminaire - Transparent stem - Battery life 9 hours.	
Apparecchio con base e stelo a fissaggio magnetico - Stelo trasparente - Autonomia batteria 9 ore.	



TeTaTeT Flûte

2W
2700K - 167lm / 3000K - 180lm
CRI >90
ON/OFF
USB cable included -
Power supply not included


CE IP20

Matt White - 2700K - ON/OFF
Matt White - 3000K - ON/OFF

1A2360300.27.00
1A2360300.30.00

Optional accessories / Accessori opzionali

Electrical power supply / Alimentazione elettrica



Power supply / Alimentatore

Not included

Matt Black Input 110-240V - 50/60Hz -
Output 5V DC - 2A - 10W - IP20

1Z0000088



USB to USB-C cable / Cavo da USB a USB-C

Included

Matt Black Lenght 1,5m

1Z0000070

Other accessories / Altri accessori




Table / Tavolino

Not included

Matt White

1A4020300.00.00

Matt Black

1A4020400.00.00



VIS À VIS


Michele Groppi / 2023



Vis à Vis is a magic trick, between technique and illusion.
Once again, we decided to take away, seeking only the light.
Transparency is the main feature of this battery-powered lamp.
Archiproducts Design Award 2023

Vis à Vis è un gioco di prestigio, tra la tecnica e l'illusione.
Abbiamo pensato, ancora una volta, di togliere, cercando solo la luce.
La trasparenza è la caratteristica principale di questa lampada a batteria.
Archiproducts Design Award 2023

Table / Direct / Wireless	
Material	Metal - Methacrylate
Finish	.00 Standard
Note	Magnetic fixing head luminaire - Transparent stem - Removable transparent disc with reflective effect - Battery life 9 hours - Indoor only - Dry environment.
	Apparecchio con testa a fissaggio magnetico - Stelo trasparente - Disco trasparente removibile con effetto rifrangente - Autonomia batteria 9 ore - Lampada solo per interni - Ambiente asciutto.



VIS A VIS

2W

2700K - 110lm / 3000K - 113lm

CRI >90

ON/OFF

USB cable included -

Power supply not included

CE IP20

Standard - 2700K - ON/OFF

Standard - 3000K - ON/OFF

1A4530000.27.00

1A4530000.30.00

Optional accessories / Accessori opzionali

Electrical power supply / Alimentazione elettrica



Power supply / Alimentatore

Not included

Matt Black

Input 110-240V - 50/60Hz -
Output 5V DC - 2A - 10W - IP20

1Z0000088



USB to USB-C cable / Cavo da USB a USB-C

Included

Matt Black

Lenght 1m

1Z0000132

TABLE / TAVOLO

ABA 45

Omar Carraglia / 2007




Inspired by the shape of a traditional lampshade.
The bulb is not shielded but displayed, and it peeks out from the shade.
Floor version available.

Ispirata alla forma di un'abat-jour tradizionale.
La lampadina non è schermata, ma esibita, e fa capolino dal paralume.
Disponibile anche nella versione da terra.

ABA 45

Omar Carraglia / 2007

Table / Diffuse / Indoor	
Material	Metal - Methacrylate
Finish	.03 Matt White
Note	
White cable luminaire.	
Apparecchio con cavo bianco.	



ABA 45

Max 10W - E27

100-240V - 50/60Hz

Bulb not included

Dimmer on board

CE IP20 0.5 m

Matt White - Dimmer on board

1A2700300.00.06

Optional accessories / Accessori opzionali

Bulbs / Lampadine	
	LED - E27 - G125
	220-240V - 7W - 360° - 2700K - 806lm - CRI 80 - Energy Efficiency E - Dimmable
	1Y2080010
Not included	





ANIMA

Davide Groppi - Giorgio Rava / 2021

A slender, light, ephemeral and abstract sculpture, it is a weightless ideogram. It's the emotion of an indirect light with an aesthetic poised between Scandinavian and Japanese design, two apparently distant cultures but, actually, very close.

At the top, an open circle, almost a hook for fishermen of the soul.

Selection for ADI Design Index 2022

AZ Award 2022

Archiproducts Design Award 2021

Scultura filiforme, leggera, effimera, astratta, è un ideogramma senza peso. È l'emozione di una luce indiretta con un'estetica in bilico tra la Scandinavia e il Giappone, due culture apparentemente lontane, ma in realtà molto vicine tra loro.

In cima, un cerchio non chiuso, quasi un amo per pescatori d'anime.

Selezione per ADI Design Index 2022


Premio AZ Award 2022

Premio Archiproducts Design Award 2021

ANIMA

Davide Groppi - Giorgio Rava / 2021

Table-Floor / Indirect / Indoor	
Material	ABS - Carbon Fiber - Metal
Finish	.04 Matt Black
Note	Black cable luminaire - ON/OFF and touch dimmable.
Apparecchio con cavo nero - ON/OFF e dimmerazione touch.	




ANIMA
4W
5V DC
2700K - 575lm / 3000K - 589lm
CRI >80
Driver on the wall
Dimmer on board
USB cable included -
Power supply not included
CE IP20

Matt Black - 2700K - Dimmer on board	1A1090400.27.06
Matt Black - 3000K - Dimmer on board	1A1090400.30.06

Optional accessories / Accessori opzionali

Other accessories / Altri accessori



Power bank		Not included
	10000mAh/36Wh - Output 5V DC Battery life 10 hours	1A1990000.00.00

Electrical power supply / Alimentazione elettrica



Power supply / Alimentatore		Not included
Matt Black	Input 110-240V - 50/60Hz - Output 5V DC - 2A - 10W - IP20	1Z0000088



USB to USB-C cable / Cavo da USB a USB-C		Included
Matt Black	Lenght 1m	1Z0000132






CALVINO

Davide Groppi / 2018

Full and empty, shadow and light.
A circular mirror to be positioned as you please,
to both light and capture the surrounding space.
Born Series Award 2019

Pieni e vuoti, ombra e luce.
Uno specchio circolare può essere orientato a piacimento
per illuminare e nello stesso tempo cogliere lo spazio circostante.
Premio Born Series Award 2019


Table / Indirect / Indoor	
Material	Brass - Metal - Methacrylate - Mirror
Finish	.00 Standard
Note	
Adjustable luminaire - Blue back side mirror plate - Brass stem - Black base - Black cable.	
Apparecchio orientabile con disco a specchio con retro blu - Stelo in ottone - Base nera - Cavo nero.	



CALVINO	
18W	
24V DC	
2700K - 1275lm / 3000K - 1372lm	
CRI >90	
Driver included	
Driver on the wall	
Dimmer on board	
CE  IP20	
Standard - 2700K - Dimmer on board	1A2710000.27.06
Standard - 3000K - Dimmer on board	1A2710000.30.06


Optional accessories / Accessori opzionali

Electrical power supply / Alimentazione elettrica



Power supply / Alimentatore		Included
Matt Black	Input 110-240V - 50/60Hz - Output 24V DC - 18W - IP20	1Z0431020





An antenna of light.

Antennas are mysterious, absolute and intrinsically beautiful, because their essentialness expresses nothing more than their function. A performing, adjustable and extremely comfortable light.

Selection for ADI Design Index 2023
Archiproducts Design Award 2022

Un'antenna di luce.


Le antenne sono misteriose, assolute e intrinsecamente belle perché esprimono, con la loro essenzialità, null'altro che la loro funzione. Una luce prestante, orientabile ed estremamente confortevole.

Selection for ADI Design Index 2023
Archiproducts Design Award 2022

FM


Davide Groppi / 2022

Table / Direct / Indoor	
Material	Carbon Fiber - Metal
Finish	.04 Matt Black
Note	
Adjustable luminaire with black cable and Extradark comfort system.	
Apparecchio orientabile con cavo nero e dotato di Extradark comfort system.	



	FM 1,5W 5V DC 2700K - 154lm / 3000K - 179lm CRI >90 UGR <19 Driver on the wall Dimmer on board USB cable included - Power supply not included CE IP20	Matt Black - 2700K - Dimmer on board Matt Black - 3000K - Dimmer on board 1A2440400.27.06 1A2440400.30.06
---	---	---

Optional accessories / Accessori opzionali

Other accessories / Altri accessori

	Power bank 10000mAh/36Wh - Output 5V DC Battery life 10 hours	Not included
---	---	--------------

Electrical power supply / Alimentazione elettrica

	Power supply / Alimentatore Matt Black Input 110-240V - 50/60Hz - Output 5V DC - 2A - 10W - IP20	Not included
	USB to USB-C cable / Cavo da USB a USB-C Matt Black Lenght 1,5m	Included



MOON T

Davide Groppi / 2019




Moon was created from the dream of bringing the moon inside your own home.
The hand-made Japanese paper surface makes every lamp unique.
Suspension and floor versions available.

Moon nasce da un sogno, quello di portare la luna dentro casa.
La superficie di carta giapponese, fatta a mano, rende unico ogni pezzo.
Disponibile nella versione a sospensione e da terra.

MOON T

Davide Groppi / 2019

Table / Diffuse / Indoor	
Material	Japanese Paper - Metal - PE
Finish	.00 Standard
Note	
Shade with japanese paper texture - Gold finish base - White cable.	
Apparecchio con paralume con texture in carta giapponese - Base verniciata dorata - Cavo bianco.	



MOON T
Max 15W - E27
100-240V - 50/60Hz
Bulb not included
Dimmer on board
CE IP20

Standard - Dimmer on board	1A2690000.00.06
----------------------------	-----------------

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - E27 - A60		Not included
	220-240V - 11,2W - 360° - 2700K - 1521lm - CRI 90 - Energy Efficiency D - Dimmable	1Y0330790





A lamp that can be positioned, balanced and turned,
but overall it produces a beautiful light on the table.
The oversized workshop-style clamp allows the light source to be positioned far
from where the lamp is attached to the table, using three adjustable arms.
A table lamp, but at the same time a suspended light.

Una lampada che si inclina, si bilancia, si gira,
ma soprattutto che produce una bellissima luce sul tavolo.
L'utilizzo di un grande e sproporzionato morsetto da officina, ci ha permesso di portare la
fonte luminosa lontana dal punto di fissaggio attraverso tre bracci regolabili.
Una lampada da tavolo, ma nello stesso tempo a sospensione.

MORSETTO

Table / Direct / Indoor

Material

Metal


Finish

.04 Matt Black

Note

Adjustable luminaire with Extradark comfort system - Red lever clamp - Black cable.

Apparecchio orientabile con morsetto rosso e dotato di Extradark comfort system - Cavo nero.



MORSETTO

13W

24V DC

2700K - 765lm / 3000K - 823lm

CRI >90

UGR <19

Driver included

Dimmer on board

CE IP20

Matt Black - 2700K - Dimmer on board


Matt Black - 3000K - Dimmer on board

1A2520400.27.06

1A2520400.30.06

Optional accessories / Accessori opzionali

Electrical power supply / Alimentazione elettrica

		Power supply / Alimentatore	Included
Matt Black	Input 110-240V - 50/60Hz - Output 24V DC - 18W - IP20	1Z0431020	







PALPEBRA

Federico Delrosso / 2009

Reminiscent of waking up, that magical instant just before you open your eyes completely, when the light barely filters, making everything indistinct as you pass from sleeping to being awake.


A metal cone positioned diagonally on its base creates an asymmetrical light.

Ricorda il risveglio, quel breve magico attimo, prima di aprire totalmente gli occhi, in cui la luce filtra appena, rendendo tutto indistinto nel passaggio fra il sonno e la veglia. Un cono in metallo, posizionato in obliquo sulla base, genera una luce asimmetrica.

PALPEBRA

Federico Delrosso / 2009

Table / Diffuse / Indoor	
Material	Metal
Finish	.03 Matt White
Note	White cable luminaire.
	Apparecchio con cavo bianco.



PALPEBRA
Max 5W - E14
100-240V - 50/60Hz
Bulb not included
Dimmer on board
CE IP20

Matt White - Dimmer on board

1A2680300.00.06

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - E14 - P40

220-240V - 4,5W -
2700K - 470lm - CRI >80 -
Energy Efficiency F - Dimmable

1Y0041410

Not included






A rigorous project in its design.
A dialogue between two essential, concrete and tangible materials: wood and glass.
Part frosted and part transparent, it moves feely on the base,
functioning both as diffuser and convex lens.

Un progetto dalle linee rigorose.
Un dialogo tra due materiali primari, concreti e tangibili: il legno e il vetro.
Satinata e in parte trasparente, si muove liberamente sulla base,
diventando a volte diffusore, a volte lente convessa.

Table / Diffuse / Indoor	
Material	Glass - Oak wood
Finish	.00 Standard
Note	
Frosted glass sphere luminaire - Oak wood base - Black cable.	
Apparecchio con sfera in vetro satinato - Base in legno rovere - Cavo nero.	




PIGRECO
6,5W
24V DC
3000K - 450lm
CRI >90
Driver included
Driver on the wall
Dimmer on board
CE IP20

Standard - 3000K - Dimmer on board | 1A2600000.30.06 |

Optional accessories / Accessori opzionali

Electrical power supply / Alimentazione elettrica



Power supply / Alimentatore		Included
Matt Black	Input 110-240V - 50/60Hz - Output 24V DC - 18W - IP20	1Z0431020



FLOOR / TERRA



ABA 120

Omar Carraglia / 2007


Inspired by the shape of a traditional lampshade.
The bulb is not shielded but displayed, and it peeks out from the shade.
Table version available.

Ispirata alla forma di un'abat-jour tradizionale.
La lampadina non è schermata, ma esibita, e fa capolino dal paralume.
Disponibile anche nella versione da tavolo.

ABA 120

Omar Carraglia / 2007

Floor / Diffuse / Indoor	
Material	Metal - Methacrylate
Finish	.03 Matt White
Note	
White cable luminaire.	
Apparecchio con cavo bianco.	



ABA 120
Max 10W - E27
100-240V - 50/60Hz
Bulb not included
Dimmer on board
CE IP20 0.5 m


Matt White - Dimmer on board

1A2770300.00.06

Optional accessories / Accessori opzionali

	Bulbs / Lampadine		
		LED - E27 - G125	Not included
		220-240V - 7W - 360° - 2700K - 806lm - CRI 80 - Energy Efficiency E - Dimmable	1Y2080010





BANNER

Mauro Ferrari / 2004


A solution that is part fixed and part mobile.
The lamp is fixed to the wall, but is powered by a cable and normal electrical plug.
Banner is one of our many solutions for bringing light
where you need it, with the greatest freedom.

Una soluzione fissa ma anche mobile.
La lampada è fissata a parete, ma viene alimentata attraverso una cavo e una normale
spina elettrica. Banner è una delle nostre tante soluzioni per portare
la luce dove si desidera con la massima libertà.

Floor / Indirect / Indoor

Material Metal - Polycarbonate


Finish .03 Matt White



BANNER
90W
110-240V - 50/60Hz
2700K - 11083lm / 3000K - 11918lm
CRI >80
Driver included
Driver integrated
DALI
CE IP20

Matt White - 2700K - DALI
Matt White - 3000K - DALI

1A1840300.27.01
1A1840300.30.01



BANNER
90W
110-240V - 50/60Hz
2700K - 11083lm / 3000K - 11918lm
CRI >80
Driver included
Driver integrated
Dimmer on board
CE IP20

Matt White - 2700K - Dimmer on board
Matt White - 3000K - Dimmer on board

1A1840300.27.06
1A1840300.30.06



A floor lamp conceived to provide direct light in a simple and flexible manner. Its principle component is the pivot point between two "chopsticks" (Hashi) that serve as light sources which, positioned in different ways, create a strong, graphic effect in space. Particular care has been given to the proportions. The sticks always appear lightweight and balanced.

Lampada da terra pensata per fare luce d'accento con purezza e flessibilità. La componente fondamentale di progetto è lo snodo che, grazie alla sua energica tenacia, permette di posizionare le "bacchette" (Hashi) nello spazio in modo grafico e deciso. La particolare attenzione per le proporzioni rende il gesto molto libero, ma sempre equilibrato.

HASHI


Federico Delrosso / 2017

Floor / Direct / Indoor

Material Metal - Methacrylate
Finish .04 Matt Black .18 Matt Gold

Note Adjustable luminaire with black cable and Extradark comfort system.

Apparecchio orientabile con cavo nero e dotato di Extradark comfort system.



HASHI
15,5W
110-240V - 50/60Hz
2700K - 765lm / 3000K - 823lm
CRI >90
UGR <19
Driver included
Dimmer on board
CE IP20

Matt Black - 2700K - Dimmer on board
Matt Black - 3000K - Dimmer on board
Matt Gold - 2700K - Dimmer on board
Matt Gold - 3000K - Dimmer on board

1A2510400.27.06
1A2510400.30.06
1A2511800.27.06
1A2511800.30.06





A tribute to Alberto Giacometti and to his thin fellows...
A lamp for lighting pictures, powered by an ordinary electrical socket.
The lamp has an adjustable light and it can be oriented.
The lamp section is reduced to a minimum.



Un omaggio ad Alberto Giacometti e alle sue figure sottili...
Una lampada per illuminare i quadri prendendo corrente da una normale presa elettrica.
La lampada è regolabile in altezza ed il flusso luminoso orientabile.
La sezione del corpo illuminante è ridotta ai minimi termini.

MASAI

Maurizio Mancini / 2015


Floor-Suspension / Indirect / Indoor

Material	Brass - Methacrylate		
Finish	.03 Matt White	.04 Matt Black	.08 Brushed Brass
Note	White celing rose luminaire - 304 Stainless steel suspension cable - Transparent cable.		
	Apparecchio con rosone bianco - Cavo di sospensione in acciaio INOX 304 - Cavo trasparente.		


	MASAI 1 Power kit with plug model 15,5W 110-240V - 50/60Hz 2700K - 600lm / 3000K - 619lm CRI >90 Driver included Dimmer on board CE IP20	Matt White - 2700K - Dimmer on board Matt White - 3000K - Dimmer on board Matt Black - 2700K - Dimmer on board Matt Black - 3000K - Dimmer on board Brushed Brass - 2700K - Dimmer on board Brushed Brass - 3000K - Dimmer on board	1A2720300.27.06 1A2720300.30.06 1A2720400.27.06 1A2720400.30.06 1A2720800.27.06 1A2720800.30.06
	MASAI 2 Remote power supply model 13W 24V DC - 50/60Hz 2700K - 600lm / 3000K - 619lm CRI >90 Driver not included CE IP20	Matt White - 2700K Matt White - 3000K Matt Black - 2700K Matt Black - 3000K Brushed Brass - 2700K Brushed Brass - 3000K	1A2720300.27.20 1A2720300.30.20 1A2720400.27.20 1A2720400.30.20 1A2720800.27.20 1A2720800.30.20

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica




Driver LED				Not included
220-240V(100-127V)	24V/20W(15W)/IP20/PUSH	MASAI 2	1Z0240870.24	



Driver LED				Not included
220-240V(100-127V)	24V/16W(15W)/IP20/DALI	MASAI 2	1Z0241180.24	

Maurizio Mancini / 2015

MASAI

Compulsory accessories / Accessori obbligatori				
Electrical power supply / Alimentazione elettrica				
	Driver LED			Not included
	220-240V	24V/20W/IP20/TRIAC/IGBT	MASAI 2	1Z0240850.24

Optional accessories / Accessori opzionali

Installation kit / Kit installazione

Suspension fixing kit - See page 614 / Kit di fissaggio per sospensione - Vedi pagina 614



Sloped ceiling fixing kit / Kit fissaggio soffitto inclinato			Not included
Nickel plated - 1 Piece			1A0510000.00.00



Recessed fixing kit for 12.5 mm plasterboard / Kit di fissaggio ad incasso per cartongesso 12,5 mm			Not included
Matt White	For suspension cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm	1X0000300.03.00	
Matt Black	For suspension cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm	1X0000400.03.00	



Ceiling fixing kit / Kit di fissaggio a soffitto			Not included
Matt White	For suspension cables - 1 Piece	1X0010300.03.00	
Matt Black	For suspension cables - 1 Piece	1X0010400.03.00	



Wall back plate / Piastra parete			Not included
Matt White	For mounting on brick masonry walls	1X0050300.01.00	

Suspension kit / Kit sospensione



304 Stainless steel suspension cable / Cavo di sospensione in acciaio inox 304			Not included
Lenght 10m			1A1680000.00.00





MISTER

Omar Carraglia / 2013


Portable light.

A floor tool to grant a wonderful indirect light in the purest possible way.

Luce mobile.

Un elemento da terra per garantire nel modo più puro possibile
una meravigliosa luce indiretta.

Floor / Indirect / Indoor		
Material	Metal - Methacrylate	
Finish	.03 Matt White	.04 Matt Black
Note		
White finish luminaire with white cable and black finish luminaire with black cable.		
Apparecchio con cavo bianco per la finitura bianca e cavo nero per la finitura nera.		



MISTER
33W
110-240V - 50/60Hz
2700K - 2771lm / 3000K - 2884lm
CRI >90
Driver included
Dimmer on board
CE IP20

Matt White - 2700K - Dimmer on board
Matt White - 3000K - Dimmer on board
Matt Black - 2700K - Dimmer on board
Matt Black - 3000K - Dimmer on board

1A2750300.27.06
1A2750300.30.06
1A2750400.27.06
1A2750400.30.06





MOON F

Davide Groppi / 2023

Moon was created from the dream of bringing the moon inside your own home.
The hand-made Japanese paper surface makes every lamp unique.
Suspension and floor versions available.

Moon nasce da un sogno, quello di portare la luna dentro casa.
La superficie di carta giapponese, fatta a mano, rende unico ogni pezzo.
Disponibile nella versione a sospensione e da tavolo.

MOON F

Davide Groppi / 2023

Floor / Diffuse / Indoor

Material

Japanese Paper - PE


Finish

.00 Standard

Note

Shade with japanese paper texture luminaire.

Apparecchio con paralume con texture in carta giapponese.



MOON 80 F

Diameter 780 mm

Max 15W - E27

100-240V - 50/60Hz


Bulb not included

Dimmer on board

CE IP20

Standard - Dimmer on board

1A4880000.00.06



MOON 120 F

Diameter 1200 mm

Max 2x25W - E27

100-240V - 50/60Hz

Bulb not included

Dimmer on board

CE IP20

Standard - Dimmer on board

1A4890000.00.06

Optional accessories / Accessori opzionali

Bulbs / Lampadine

	LED - E27 - A60	Not included		
	220-240V - 11,2W - 360° - 2700K - 1521lm - CRI 90 - Energy Efficiency D - Dimmable	MOON 80 F	1Y0330790	
	LED - E27 - A150	Not included		
	220-240V - 21W - 200° - 2700K - 2452lm - CRI >80 - Energy Efficiency E - Dimmable	MOON 120 F	1Y0041470	

Davide Groppi / 2023

MOON F

Optional accessories / Accessori opzionali

Other accessories / Altri accessori

Wooden crate / Cassa in legno

Not included

Packaging for air and sea shipping

MOON 120 F

49860010


Moisture barrier bag / Sacco barriera

Not included

Packaging for air and sea shipping

MOON 120 F

49860020



MOVIE

Omar Carraglia / 2005


To “play” with the light.
A RGBW system lets you create all the light of the world.
To feel the light and to live it in all its spectrum.

Per giocare con i colori della luce.
Un sistema RGBW permette di creare tutta la luce del mondo.
Per sentire la luce e viverla in tutto il suo spettro.

MOVIE


Omar Carraglia / 2005

Floor / Indirect / Indoor		
Material	Metal - Polycarbonate	
Finish	.03 Matt White	.13 Black Brushed Stainless Steel
Note		
RGBW wireless control luminaire - Black cable.		
Apparecchio con RGBW wireless control - Cavo nero.		



MOVIE
80W
100-240V - 50/60Hz
2700K - 2832lm
CRI >90
Driver included
Driver integrated
Dimmer on board
RGBW wireless control
CE IP20

Matt White - RGBW - Dimmer on board	1A2740300.98.06
Black Brushed Stainless Steel - RGBW - Dimmer on board	1A2741300.98.06





ORIGINE

Davide Groppi - Giorgio Rava / 2020

From the Latin “origo”, start, birth, source. It appears like a bud emerging from the ground and soaring upwards towards the sky, a stem that becomes increasingly thinner. Mysterious and enigmatic, it combines the fascination of the unknown with the pleasure of a sophisticated and elegant ambient light. Origine sculpts and enhances every environment with its indirect light, which is intentionally non-invasive, graphic and fascinating.

Available in 3 different heights and in an outdoor version.


**AZ Award 2021 and People's Choice
Archiproducts Design Award 2020**

Dal latino “origo”, inizio, nascita, fonte. Evoca un germoglio che emerge dalla terra e si slancia verso il cielo, lo stelo che diventa sempre più sottile. Misteriosa ed enigmatica, unisce il fascino dell'incognito al piacere di una luce d'ambiente sofisticata ed elegante. Origine scolpisce e valorizza ogni ambiente con la sua luce indiretta, volutamente non invasiva, grafica e affascinante.

Disponibile in 3 altezze differenti e nella versione outdoor.

**Premio AZ Award 2021 e People's Choice
Premio Archiproducts Design Award 2020**


Floor / Indirect / Indoor	
Material	Fiberglass - Metal
Finish	.04 Matt Black
Note	Black cable luminaire.
	Apparecchio con cavo nero.



ORIGINE 290
Height 2700 mm
25W
24V DC
2700K - 1926lm / 3000K - 2075lm
CRI >80
Driver included
Dimmer on board
C E IP20

Matt Black - 2700K - Dimmer on board
Matt Black - 3000K - Dimmer on board


1A2300400.27.06
1A2300400.30.06



ORIGINE 390
Height 3700 mm
30W
24V DC
2700K - 2843lm / 3000K - 3063lm
CRI >80
Driver included
Dimmer on board
C E IP20

Matt Black - 2700K - Dimmer on board
Matt Black - 3000K - Dimmer on board

1A2310400.27.06
1A2310400.30.06



ORIGINE 490
Height 4700 mm
35W
24V DC
2700K - 3760lm / 3000K - 4051lm
CRI >80
Driver included
Dimmer on board
C E IP20

Matt Black - 2700K - Dimmer on board
Matt Black - 3000K - Dimmer on board

1A2320400.27.06
1A2320400.30.06





The light is elevated to a work of art and contemplation.
A luminous panel without a frame leans against the wall as if waiting to be hung.
The colour and brightness can be controlled from the remote control.

La luce è elevata a oggetto d'arte e di contemplazione.
Un pannello luminoso senza cornice è appoggiato alla parete
come se aspettasse di essere appeso.
È possibile scegliere il colore e l'intensità della luce agendo sul telecomando.

PABLO

Floor / Diffuse / Indoor

Material

Metal - Methacrylate


Finish

.00 Standard

Note

White panel luminaire - Transparent cable.

Apparecchio con pannello bianco - Cavo trasparente.



PABLO

66W

220-240V - 50/60Hz

Driver included

Dimmer on board


RGB wireless control

CE IP20

Standard - RGB - Dimmer on board

1A2730000.99.06






A piece of architecture to be used in space.
A concrete cube that allows you to understand volumes and architecture
in an unusual and unprecedented way.
Outdoor version available.

Un pezzo di architettura da utilizzare nello spazio.
Un cubo realizzato in cemento che permette di interpretare i volumi
e le architetture in modo inconsueto e inedito.
Disponibile nella versione outdoor.

Q

Alberto Zattin / 2000

Floor / Direct / Indoor	
Material	Cement - Metal
Finish	.00 Standard
Note	Cement luminaire - Orange cable.
	Apparecchio in cemento - Cavo arancione.



Q Max 10W - GU10 100-240V - 50/60Hz Bulb not included ON/OFF CE IP20	Standard - ON/OFF	1A2760000.00.00
--	-------------------	-----------------

Optional accessories / Accessori opzionali

Bulbs / Lampadine		LED - GU10 - PAR16	Not included
		220-240V - 4,9W - 120° - 3000K - 550lm - CRI 80 - Energy Efficiency E	1Y0330740





A special project, an authentic ready-made.
Obtained from a flexible fishing rod, it is a delicate and elegant sign,
which brings to mind the subtle branches of a willow tree
or bamboo canes floating on a light breeze.
Sampei is an unexpected gift, it is the magic of looking up, using light as a hook,
and being amazed by so much weightlessness.
The light is the fisherman's line, catching faces, gazes, people.
Available in 4 different heights and in an outdoor version.

XXIII Compasso d'Oro ADI Award 2014

Elle Deco International Design Award 2011

Un progetto speciale, un autentico ready-made.
Ricavata da una canna da pesca flessibile, è un segno delicato ed elegante,
che fa pensare a effimeri rami di salice, a canne di bambù mosse da un debole vento.
Sampei è un regalo inaspettato, è la magia di guardare in alto,
usando la luce come amo, e stupirsi di tanta leggerezza.
La luce è la lenza del pescatore, pronta per catturare volti, sguardi, persone.
Disponibile in 4 altezze differenti e nella versione outdoor.

XXIII Premio Compasso d'Oro ADI 2014

Premio Elle Deco International Design Award 2011

SAMPEI

Enzo Calabrese - Davide Groppi / 2011

Floor / Direct / Indoor

Material

Fiberglass - Metal

Finish

.03

Matt White

.04

Matt Black

Note

Adjustable luminaire - White finish luminaire with white cable and black finish luminaire with black cable.

Apparecchio orientabile con cavo bianco per la finitura bianca e cavo nero per la finitura nera.

	SAMPEI 230 Height 2150 mm 21W 220-240V - 50/60Hz 2700K - 1808lm / 3000K - 1890lm CRI >90 Driver included Dimmer on board CE IP20	Matt White - 2700K - Dimmer on board Matt White - 3000K - Dimmer on board Matt Black - 2700K - Dimmer on board Matt Black - 3000K - Dimmer on board 1A3730300.27.06 1A3730300.30.06 1A3730400.27.06 1A3730400.30.06
	SAMPEI 260 Height 2350 mm 21W 220-240V - 50/60Hz 2700K - 1808lm / 3000K - 1890lm CRI >90 Driver included Dimmer on board CE IP20	Matt White - 2700K - Dimmer on board Matt White - 3000K - Dimmer on board Matt Black - 2700K - Dimmer on board Matt Black - 3000K - Dimmer on board 1A3740300.27.06 1A3740300.30.06 1A3740400.27.06 1A3740400.30.06
	SAMPEI 290 Height 2600 mm 21W 220-240V - 50/60Hz 2700K - 1808lm / 3000K - 1890lm CRI >90 Driver included Dimmer on board CE IP20	Matt White - 2700K - Dimmer on board Matt White - 3000K - Dimmer on board Matt Black - 2700K - Dimmer on board Matt Black - 3000K - Dimmer on board 1A3750300.27.06 1A3750300.30.06 1A3750400.27.06 1A3750400.30.06

Enzo Calabrese - Davide Groppi / 2011

SAMPEI

SAMPEI 440

Height 3900 mm

21W

220-240V - 50/60Hz

2700K - 1832lm / 3000K - 1915lm

CRI >90

Driver included

Dimmer on board

CE IP20

Matt White - 2700K - Dimmer on board

Matt White - 3000K - Dimmer on board

Matt Black - 2700K - Dimmer on board

Matt Black - 3000K - Dimmer on board

1A3760300.27.06

1A3760300.30.06

1A3760400.27.06

1A3760400.30.06

Optional accessories / Accessori opzionali

Other accessories / Altri accessori

	Accessory holder + Soft filter + Honeycomb louvre / Porta accessori + Filtro soft + Frangiluce nido d'ape	Not included
Matt Black	1X0070400.04.00	
	Accessory holder + Elliptical filter / Porta accessori + Filtro ellittico	Not included
Matt Black	1X0070400.05.00	
	Blue filter / Filtro blu	Not included
Standard	1X0070000.06.00	
	Red filter / Filtro rosso	Not included
Standard	1X0070000.07.00	
	Yellow filter / Filtro giallo	Not included
Standard	1X0070000.08.00	



SHOJI


Davide Groppi - Paola Lenti / 2013



Exploiting the technique used by Paola Lenti for her beautiful works, we designed a nylon lampshade, strictly hand-stitched and hand-made. Outdoor version available.

Sfruttando la tecnica utilizzata da Paola Lenti per la realizzazione dei suoi meravigliosi oggetti, abbiamo pensato ad un paralume in nylon rigorosamente cucito e confezionato a mano. Disponibile nella versione outdoor.

Floor / Diffuse / Indoor	
Material	Metal - PBT - Polycarbonate
Finish	.00 Standard
Note	White shade luminaire - Black leg base - Black cable.
Apparecchio con paralume bianco - Supporti neri - Cavo nero.	



SHOJI
Max 18W - E27
100-240V - 50/60Hz
Bulb not included
Dimmer on board
CE IP20

Standard - Dimmer on board

1A2780000.00.06

Optional accessories / Accessori opzionali

	LED - E27 - A60	Not included
	220-240V - 11,2W - 360° - 2700K - 1521lm - CRI 90 - Energy Efficiency D - Dimmable	1Y0330790



SUSPENSION / SOSPENSIONE

CARTESIO

Davide Groppi / 2018



A thin, circular mirror is suspended to provide light,
combining both direct and indirect lighting.
A sophisticated clamping system is used to position the disc wherever you want,
without the need for wall or ceiling wires.

Uno specchio circolare sospeso e sottile per illuminare,
coniugando la luce diretta e quella indiretta.
Il sofisticato sistema di fissaggio permette di posizionare il disco dove si desidera
senza il vincolo della posizione dei cavi di alimentazione a soffitto o a parete.

CARTESIO

Suspension / Indirect-Direct / Indoor

Material

Metal - Methacrylate



Finish

.00 Standard

Note

Dual emission luminaire - Stainless steel plate with mirror finish - Red back side - White ceiling rose - 304 Stainless steel suspensioe cables - White cable.

Apparecchio a doppia emissione - Disco in acciaio INOX con finitura a specchio - Retro rosso - Rosone bianco - Cavo di sospensione in acciaio INOX 304 - Cavo bianco.

	CARTESIO Diameter 600 mm - Dual emission 18W 110-240V - 50/60Hz 3000K - Down 350lm - CRI >80 3000K - Up 1050lm - CRI >90 Driver included Driver integrated PUSH CE IP20	Standard - 3000K - PUSH	1A3190000.30.04
	CARTESIO 90 Diameter 900 mm - Dual emission 18W 110-240V - 50/60Hz 3000K - Down 350lm - CRI >80 3000K - Up 1050lm - CRI >90 Driver included Driver integrated PUSH CE IP20	Standard - 3000K - PUSH	1A0070000.30.04





CATHODE

Omar Carraglia / 2015


A scientific looking bulb made from mouth blown glass.
The shape brings to mind a light bulb that was never born. Think steampunk:
situations in which instruments were inspired by the rudiments of electricity.

The classic light bulb that has no future becomes
a wonderful device made of luminous diodes.
What would the past have looked like if the future had arrived first?
Luminaire designed to be powered by Endless system.

Un'ampolla di vetro soffiato a bocca dall'aspetto scientifico.
La forma evoca quella di una lampadina mai nata, atmosfere steampunk, situazioni in cui
le strumentazioni erano attivate dalle prime forme di elettricità.
La classica lampadina senza più futuro diventa un apparecchio a diodi luminosi.
Come sarebbe stato il passato se il futuro fosse arrivato prima?
Apparecchio predisposto per essere alimentato dal sistema Endless.


Suspension / Diffuse / Indoor

Material	Blown glass - Metal		
Finish	.03 Matt White	.08	Brushed Brass
Note	White finish luminaire with white ceiling rose and white cable - Brushed brass finish luminaire with black ceiling rose and black cable - CATHODE 2: installation on plasterboard with flat rose - Magnetic fixing - Single ceiling rose for multiple luminaires on request.		
	Apparecchio con rosone bianco e cavo bianco per la finitura bianca - Apparecchio con rosone nero e cavo nero per la finitura ottone spazzolato - CATHODE 2: installazione su cartongesso con rosone piano - Fissaggio magnetico - Rosone unico per più apparecchi su richiesta.		




CATHODE 1
Ceiling rose model
5,6W
100-240V - 50/60Hz
2700K - 264lm / 3000K - 284lm
CRI >90
Driver included
Driver integrated
ON/OFF
C E IP20

Matt White - 2700K - ON/OFF	1A2980300.27.00
Matt White - 3000K - ON/OFF	1A2980300.30.00
Brushed Brass - 2700K - ON/OFF	1A2980800.27.00
Brushed Brass - 3000K - ON/OFF	1A2980800.30.00



CATHODE 1
Ceiling rose model
5,6W
100-240V - 50/60Hz
2700K - 264lm / 3000K - 284lm
CRI >90
Driver included
Driver integrated
DALI
C E IP20

Matt White - 2700K - DALI	1A2980300.27.01
Matt White - 3000K - DALI	1A2980300.30.01
Brushed Brass - 2700K - DALI	1A2980800.27.01
Brushed Brass - 3000K - DALI	1A2980800.30.01



CATHODE 1
Ceiling rose model
5,6W
100-240V - 50/60Hz
2700K - 264lm / 3000K - 284lm
CRI >90
Driver included
Driver integrated
TRIAC/IGBT
C E IP20

Matt White - 2700K - TRIAC/IGBT	1A2980300.27.02
Matt White - 3000K - TRIAC/IGBT	1A2980300.30.02
Brushed Brass - 2700K - TRIAC/IGBT	1A2980800.27.02
Brushed Brass - 3000K - TRIAC/IGBT	1A2980800.30.02



CATHODE 1
Ceiling rose model
5,6W
100-240V - 50/60Hz
2700K - 264lm / 3000K - 284lm
CRI >90
Driver included
Driver integrated
1-10V
C E IP20

Matt White - 2700K - 1-10V	1A2980300.27.03
Matt White - 3000K - 1-10V	1A2980300.30.03
Brushed Brass - 2700K - 1-10V	1A2980800.27.03
Brushed Brass - 3000K - 1-10V	1A2980800.30.03



CATHODE 1
Ceiling rose model
5,6W
100-240V - 50/60Hz
2700K - 264lm / 3000K - 284lm
CRI >90
Driver included
Driver integrated
PUSH
C E IP20

Matt White - 2700K - PUSH	1A2980300.27.04
Matt White - 3000K - PUSH	1A2980300.30.04
Brushed Brass - 2700K - PUSH	1A2980800.27.04
Brushed Brass - 3000K - PUSH	1A2980800.30.04




CATHODE 2
Remote power supply model
4W
Max 350mA DC
2700K - 264lm / 3000K - 284lm
CRI >90
Driver not included
C E IP20


Matt White - 2700K	1A2990300.27.20
Matt White - 3000K	1A2990300.30.20
Brushed Brass - 2700K	1A2990800.27.20
Brushed Brass - 3000K	1A2990800.30.20

Compulsory accessories / Accessori obbligatori


Electrical power supply / Alimentazione elettrica



Driver LED				Not included
220-240V(100-127V)	350mA/18W(15W)/IP20/PUSH - 1-10V	CATHODE 2	1Z0240870.350	




Driver LED				Not included
220-240V(100-127V)	350mA/17W(15W)/IP20/DALI	CATHODE 2	1Z0241180.350	




Driver LED				Not included
220-240V	350mA/17W/IP20/TRIAC/IGBT	CATHODE 2	1Z0240850.350	

Optional accessories / Accessori opzionali

Suspension kit / Kit sospensione



Decentralization kit / Kit decentratore			Not included
	CATHODE 1	1A0360000.00.00	



Kit ceiling rose and decentralizer / Kit rosone e decentratore			Not included
Matt White	White cable 3 m included	CATHODE 1	1A0770300.00.00
Matt Black	Black cable 3 m included	CATHODE 1	1A0770400.00.00





CATHODE

FOSBURY


Davide Groppi / 2014



A lamp that interprets the classic theme of decentralization.
An acrobatic and apparently precarious presence, bringing light where you prefer it,
starting from a simple wall socket.
AZ Award 2016

Una lampada che interpreta il classico tema del decentramento.
Una presenza funambolica e apparentemente instabile per portare la luce
dove si desidera partendo da una semplice presa elettrica.
Premio AZ Award 2016

Floor-Suspension / Direct / Indoor	
Material	Metal
Finish	.04 Matt Black
Note	Dual emission luminaire with Extradark comfort system - Indirect blue light (up) - 304 Stainless steel suspension cable - Transparent light.
Apparecchio con doppia emissione e dotato di Extradark comfort system - Luce indiretta blu (up) - Cavo di sospensione in acciaio INOX 304 - Cavo trasparente.	



FOSBURY

23W

220-240V - 50/60Hz

2700K - Down 765lm - Up 59lm /

3000K - Down 823lm - Up 59lm

CRI >90

UGR <19

Driver included

Driver integrated

ON/OFF


CE IP20

Matt Black - 2700K - ON/OFF	1A2590400.27.00
Matt Black - 3000K - ON/OFF	1A2590400.30.00


Optional accessories / Accessori opzionali

Installation kit / Kit installazione


Suspension fixing kit - See page 614 / Kit di fissaggio per sospensione - Vedi pagina 614



Recessed fixing kit for 12.5 mm plasterboard / Kit di fissaggio ad incasso per cartongesso 12,5 mm		Not included
Matt White	For suspension cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm	1X0000300.03.00
Matt Black	For suspension cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm	1X0000400.03.00



Ceiling fixing kit / Kit di fissaggio a soffitto		Not included
Matt White	For suspension cables - 1 Piece	1X0010300.03.00
Matt Black	For suspension cables - 1 Piece	1X0010400.03.00




Wall back plate / Piastra parete		Not included
Matt White	For mounting on brick masonry walls	1X0050300.01.00



Sloped ceiling fixing kit / Kit fissaggio soffitto inclinato		Not included
	Nickel plated - 1 Piece	1A0510000.00.00





LED IS MORE

Davide Groppi / 2011

A tribute to Mies van der Rohe and his Less is More.
The project represents a light icon in a LED key,
with a peculiar attention to energy savings and the quality of light.

Un omaggio a Mies van der Rohe e al suo Less is More.
Il progetto rappresenta un'icona della luce, rivisitata in chiave LED,
con una particolare attenzione al risparmio energetico e alla qualità della luce stessa.

LED IS MORE

Davide Groppi / 2011

Suspension / Diffuse / Indoor

Material

Metal - Methacrylate


Finish

.03 Matt White

Note

White ceiling rose luminaire - White cable - Single ceiling rose for multiple luminaires on request.

Apparecchio con rosone bianco - Cavo bianco - Rosone unico per più apparecchi su richiesta.



LED IS MORE

5,6W

100-240V - 50/60Hz

3000K - 354lm

CRI >90

Driver included

Driver integrated

ON/OFF


CE IP20

Matt White - 3000K - ON/OFF

1A2790300.30.00

Optional accessories / Accessori opzionali


Suspension kit / Kit sospensione



Decentralization kit / Kit decentratore

Not included

1A0360000.00.00



Kit ceiling rose and decentralizer / Kit rosone e decentratore

Not included

Matt White

White cable 3 m included


1A0770300.00.00

Matt Black

Black cable 3 m included

1A0770400.00.00







LOUIS XIV

Davide Groppi / 2023

Louis XIV is the freakiest letter of our light alphabet.
It's a disobedient design that translates a certain rebellion
to common lamp models into light.
I wanted to investigate the idea of the chandelier:
in line with our poetics, Louis XIV is the only possible solution
for lightness and irony.
Dimmable suspension lamp with double emission.

Louis XIV è la lettera più "freak" del nostro alfabeto luminoso.
È un progetto disobbediente, che traduce in luce
una certa ribellione ai modelli comuni di fare lampade.
Volevo affrontare il tema del lampadario a gocce:
Louis XIV è l'unica soluzione possibile, secondo le nostre poetiche, tra leggerezza e ironia.
Lampada a sospensione dimmerabile a doppia emissione.

LOUIS XIV




Suspension / Indirect-Direct / Indoor

Material

Glass - Metal

Finish

.19 Polished Gold

	LOUIS XIV 1 Ceiling rose model 30W 110-240V - 50/60Hz 2700K - Up 1650lm - Down 410lm / 3000K - Up 1650lm - Down 410lm CRI >90 Driver included Driver integrated TRIAC/IGBT CE IP20	Polished Gold - 2700K - TRIAC/IGBT Polished Gold - 3000K - TRIAC/IGBT	1A4361900.27.02 1A4361900.30.02
	LOUIS XIV 1 Ceiling rose model 30W 110-240V - 50/60Hz 2700K - Up 1650lm - Down 410lm / 3000K - Up 1650lm - Down 410lm CRI >90 Driver included Driver integrated DALI - PUSH - 1-10V CE IP20	Polished Gold - 2700K - DALI - PUSH - 1-10V Polished Gold - 3000K - DALI - PUSH - 1-10V	1A4361900.27.07 1A4361900.30.07
	LOUIS XIV 2 Remote power supply model 30W Max 500mA DC 2700K - Up 1650lm - Down 410lm / 3000K - Up 1650lm - Down 410lm CRI >90 Driver not included 2 Drivers required CE IP20	Polished Gold - 2700K Polished Gold - 3000K	1A4361900.27.20 1A4361900.30.20

LOUIS XIV

Suspension fixing kit - See page 614 / Kit di fissaggio per sospensione - Vedi pagina 614



Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Recessed fixing kit for 12.5 mm plasterboard / Kit di fissaggio ad incasso per cartongesso 12,5 mm			Not included
Matt White	For electrical cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm	LOUIS XIV 2	1X0000300.05.00
Matt Black	For electrical cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm	LOUIS XIV 2	1X0000400.05.00

Electrical power supply / Alimentazione elettrica




Driver LED				Not included
220-240V(110-127V)	500mA/25W(13,5W)/IP20/DALI - PUSH - 1-10V	LOUIS XIV 2	1Z0241270.500	
Driver LED				Not included
220-240V	500mA/36,4W/IP20/TRIAC/IGBT	LOUIS XIV 2	1Z2270010.500	



LOUIS XIV





MISS

Omar Carraglia / 2006

So slim and essential...

The fundamental concept of this project is minimalism.

A small tube that lights the table with wonder.

A real dual project: sign and light.

Luminaire designed to be powered by Endless system.

Così esile ed essenziale...

L'essenzialità è la componente fondamentale di progetto.

Un piccolo tubo in metallo per fare una meravigliosa luce sul tavolo.

Un vero progetto duale: segno e luce.

Apparecchio predisposto per essere alimentato dal sistema Endless.

Suspension / Direct / Indoor

Material	Metal			
Finish	.03 Matt White	.04 Matt Black	.08 Brushed Brass	.26 Total Black
Note	White and black finish luminaire with white ceiling rose and white cable - Brushed brass and total black finish luminaire with black ceiling rose and black cable - MISS 2: flat rose - Magneting fixing - Installation on plasterboard - Single ceiling rose for multiple luminaires on request.			
	Apparecchio con rosone bianco e cavo bianco per la finitura bianca e nera - Apparecchio con rosone nero e cavo nero per la finitura ottone spazzolato e nero totale - MISS 2: rosone piano - Fissaggio magnetico - Installazione su cartongesso - Rosone unico per più apparecchi su richiesta.			



MISS 1
5,6W
100-240V - 50/60Hz
2700K - 290lm / 3000K - 310lm
CRI >90
Driver included
Driver integrated
ON/OFF
C E IP20

Matt White - 2700K - ON/OFF	1A2960300.27.00
Matt White - 3000K - ON/OFF	1A2960300.30.00
Matt Black - 2700K - ON/OFF	1A2960400.27.00
Matt Black - 3000K - ON/OFF	1A2960400.30.00
Brushed Brass - 2700K - ON/OFF	1A2960800.27.00
Brushed Brass - 3000K - ON/OFF	1A2960800.30.00
Total Black - 2700K - ON/OFF	1A2962600.27.00
Total Black - 3000K - ON/OFF	1A2962600.30.00



MISS 1
5,6W
100-240V - 50/60Hz
2700K - 290lm / 3000K - 310lm
CRI >90
Driver included
Driver integrated
DALI
C E IP20

Matt White - 2700K - DALI	1A2960300.27.01
Matt White - 3000K - DALI	1A2960300.30.01
Matt Black - 2700K - DALI	1A2960400.27.01
Matt Black - 3000K - DALI	1A2960400.30.01
Brushed Brass - 2700K - DALI	1A2960800.27.01
Brushed Brass - 3000K - DALI	1A2960800.30.01
Total Black - 2700K - DALI	1A2962600.27.01
Total Black - 3000K - DALI	1A2962600.30.01



MISS 1
5,6W
100-240V - 50/60Hz
2700K - 290lm / 3000K - 310lm
CRI >90
Driver included
Driver integrated
TRIAC/IGBT
C E IP20

Matt White - 2700K - TRIAC/IGBT	1A2960300.27.02
Matt White - 3000K - TRIAC/IGBT	1A2960300.30.02
Matt Black - 2700K - TRIAC/IGBT	1A2960400.27.02
Matt Black - 3000K - TRIAC/IGBT	1A2960400.30.02
Brushed Brass - 2700K - TRIAC/IGBT	1A2960800.27.02
Brushed Brass - 3000K - TRIAC/IGBT	1A2960800.30.02
Total Black - 2700K - TRIAC/IGBT	1A2962600.27.02
Total Black - 3000K - TRIAC/IGBT	1A2962600.30.02



MISS 1
5,6W
100-240V - 50/60Hz
2700K - 290lm / 3000K - 310lm
CRI >90
Driver included
Driver integrated
1-10V
C E IP20

Matt White - 2700K - 1-10V	1A2960300.27.03
Matt White - 3000K - 1-10V	1A2960300.30.03
Matt Black - 2700K - 1-10V	1A2960400.27.03
Matt Black - 3000K - 1-10V	1A2960400.30.03
Brushed Brass - 2700K - 1-10V	1A2960800.27.03
Brushed Brass - 3000K - 1-10V	1A2960800.30.03
Total Black - 2700K - 1-10V	1A2962600.27.03
Total Black - 3000K - 1-10V	1A2962600.30.03



MISS 1
5,6W
100-240V - 50/60Hz
2700K - 290lm / 3000K - 310lm
CRI >90
Driver included
Driver integrated
PUSH
C E IP20

Matt White - 2700K - PUSH	1A2960300.27.04
Matt White - 3000K - PUSH	1A2960300.30.04
Matt Black - 2700K - PUSH	1A2960400.27.04
Matt Black - 3000K - PUSH	1A2960400.30.04
Brushed Brass - 2700K - PUSH	1A2960800.27.04
Brushed Brass - 3000K - PUSH	1A2960800.30.04
Total Black - 2700K - PUSH	1A2962600.27.04
Total Black - 3000K - PUSH	1A2962600.30.04




MISS 2
4W
Max 350mA DC
2700K - 290lm / 3000K - 310lm
CRI >90
Driver not included
C E IP20


Matt White - 2700K	1A2970300.27.20
Matt White - 3000K	1A2970300.30.20
Matt Black - 2700K	1A2970400.27.20
Matt Black - 3000K	1A2970400.30.20
Brushed Brass - 2700K	1A2970800.27.20
Brushed Brass - 3000K	1A2970800.30.20
Total Black - 2700K	1A2972600.27.20
Total Black - 3000K	1A2972600.30.20

Compulsory accessories / Accessori obbligatori


Electrical power supply / Alimentazione elettrica



Driver LED				Not included
220-240V(100-127V)	350mA/18W(15W)/IP20/PUSH - 1-10V	MISS 2	1Z0240870.350	




Driver LED				Not included
220-240V(100-127V)	350mA/17W(15W)/IP20/DALI	MISS 2	1Z0241180.350	




Driver LED				Not included
220-240V	350mA/17W/IP20/TRIAC/IGBT	MISS 2	1Z0240850.350	

Optional accessories / Accessori opzionali

Suspension kit / Kit sospensione



Decentralization kit / Kit decentratore			Not included
	MISS 1	1A0360000.00.00	



Kit ceiling rose and decentralizer / Kit rosone e decentratore				Not included
Matt White	White cable 3 m included	MISS 1	1A0770300.00.00	
Matt Black	Black cable 3 m included	MISS 1	1A0770400.00.00	





MOON

Davide Groppi / 2005



Moon was created from the dream of bringing the moon inside your own home.
The hand-made Japanese paper surface makes every lamp unique.
Table and floor version available.

Moon nasce da un sogno, quello di portare la luna dentro casa.
La superficie di carta giapponese, fatta a mano, rende unico ogni pezzo.
Disponibile anche nella versione da tavolo e terra.

MOON

Davide Groppi / 2005

Suspension / Diffuse / Indoor

Material

Japanese Paper - PE


Finish

.00 Standard

Note

Shade with japanese paper texture luminaire - 304 Stainless steel suspension cables - White cable - MOON 60 DE: dual emission with separated switch - Transparent cable.


Apparecchio con paralume con texture in carta giapponese - Rosone bianco - Cavo di sospensione in acciaio INOX 304 - Cavo bianco - MOON 60 DE: doppia emissione con accensione separata - Cavo trasparente.



MOON 60
Diameter 600 mm
Max 15W - E27
100-240V - 50/60Hz
Bulb not included
ON/OFF
C E IP20

Standard - ON/OFF


| 1A2820000.00.00 |



MOON 60 DE
Diameter 600 mm - Dual emission
Max 15W - E27 + Max 10W - GU10
100-240V - 50/60Hz
Bulb not included
ON/OFF
Dual emission with separated switch
C E IP20

Standard - ON/OFF

| 1A2830000.00.00 |



MOON 80
Diameter 780 mm
Max 15W - E27
100-240V - 50/60Hz
Bulb not included
ON/OFF
C E IP20

Standard - ON/OFF

| 1A2840000.00.00 |

Davide Groppi / 2005

MOON

MOON 120
Diameter 1200 mm
Max 2x25W - E27
100-240V - 50/60Hz
Bulb not included
ON/OFF
C E IP20

Standard - ON/OFF

| 1A2850000.00.00 |

MOON 200
Diameter 2000 mm
Max 4x25W - E27
100-240V - 50/60Hz
Bulb not included
ON/OFF
C E IP20

Standard - ON/OFF

| 1A2860000.00.00 |

Optional accessories / Accessori opzionali

Bulbs / Lampadine

LED - GU10 - PAR16			Not included
220-240V - 5,5W - 25° - 3000K - 375lm - CRI 97 - Energy Efficiency G - Dimmable	MOON 60 DE	1Y0330500	

LED - E27 - A60			Not included
220-240V - 11,2W - 360° - 2700K - 1521lm - CRI 90 - Energy Efficiency D - Dimmable	MOON 60 / MOON 60 DE / MOON 80 / MOON 200	1Y0330790	

LED - E27 - A150			Not included
220-240V - 21W - 200° - 2700K - 2452lm - CRI >80 - Energy Efficiency E - Dimmable	MOON 120	1Y0041470	

179

Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Sloped rose fixing kit / Kit fissaggio rosone inclinato			Not included
Nickel plated - 1 Piece	MOON 60 / MOON 60 DE / MOON 80	1A0520000.00.00	



Sloped ceiling fixing kit / Kit fissaggio soffitto inclinato			Not included
Nickel plated - 1 Piece	MOON 120	1A0510000.00.00	

Other accessories / Altri accessori

Wooden crate / Cassa in legno			Not included
Packaging for air and sea shipping	MOON 120	49860010	

Wooden crate / Cassa in legno			Not included
Packaging for air and sea shipping	MOON 200	48780020	

Moisture barrier bag / Sacco barriera			Not included
Packaging for air and sea shipping	MOON 120	49860020	

Moisture barrier bag / Sacco barriera			Not included
Packaging for air and sea shipping	MOON 200	48780030	

Suspension kit / Kit sospensione



Decentralization kit / Kit decentratore			Not included
	MOON 60 / MOON 60 DE / MOON 80 / MOON 120	1A0360000.00.00	





NEURO

Davide Groppi - Beppe Merlano / 2013

The idea is to bring light wherever you like, starting from a socket.

A simple project, almost a revival of the old electrical wiring.

A plug, a cable, some isolators, a socket and a LED.

Outdoor version available.

Design Plus Award 2014

È l'idea di portare la luce dove si desidera, partendo da una presa elettrica.

Un progetto semplice, quasi la rivisitazione dei vecchi impianti elettrici.

Una spina, un cavo, degli isolatori, un portalampada e una lampadina a LED.

Disponibile nella versione outdoor.

Premio Design Plus 2014



NEURO

Davide Groppi - Beppe Merlano / 2013

Suspension / Direct / Indoor

Material

Metal

Finish

.03

Matt White


.04

Matt Black

Note

White finish luminaire with white cable and black finish luminaire with black cable (10 m) - 5 Clamps included.

Apparecchio con cavo bianco per la finitura bianca e cavo nero per la finitura nera (10 m) - 5 Bloccacavo inclusi.



NEURO Max 15W - E27 100-240V - 50/60Hz Bulb not included ON/OFF CE IP20		
	Matt White - ON/OFF	1A0160300.00.00
	Matt Black - ON/OFF	1A0160400.00.00

Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Wall and ceiling rose / Rosone parete e soffitto		Not included
Matt White		1A3440300.00.00
Matt Black		1A3440400.00.00




Clamp / Bloccacavo		Included
Matt White	1 Piece	1A3270300.00.00
Matt Black	1 Piece	1A3270400.00.00

Bulbs / Lampadine



LED - E27 - PAR30s		Not included
	220-240V - 9,5W - 25° - 3000K - 760lm - CRI 80 - Energy Efficiency F - Dimmable	1Y0330730






OVO

Massimiliano Alajmo - Raffaele Alajmo / 2010

The light in the plate is the most beautiful light.
Light as an ingredient, used courteously but at the same time decisively.

La luce nel piatto è la luce più bella.
Una luce intesa come ingrediente della cucina, usata con garbo,
ma nello stesso tempo con decisione.

Suspension / Direct / Indoor	
Material	Metal
Finish	.03 Matt White
Note	
White ceiling rose luminaire - White cable.	
Apparecchio con rosone bianco - Cavo bianco.	



OVO
Max 20W - GU4 - 12V
230-240V - 50/60Hz
Bulb not included
ON/OFF
CE IP20 0.5m

Matt White - ON/OFF	1A2890300.00.00
---------------------	-----------------

Optional accessories / Accessori opzionali

	LED - GU4 - MR11	Not included
	12V - 20W - 24° - 2700K - 200lm - CRI 80 - Energy Efficiency G	1Y0330450





OVONELPIATTO

Massimiliano Alajmo - Raffaele Alajmo / 2010

The light in the plate is the most beautiful light.
Light as an ingredient, used courteously but at the same time decisively.

La luce nel piatto è la luce più bella.
Una luce intesa come ingrediente della cucina, usata con garbo,
ma nello stesso tempo con decisione.

OVONELPIATTO


Massimiliano Alajmo - Raffaele Alajmo / 2010

Suspension / Direct / Indoor

Material Metal
Finish .03 Matt White

Note White ceiling rose luminaire - White cable.

Apparecchio con rosone bianco - Cavo bianco.



OVONELPIATTO
Max 20W - GU4 - 12V
230-240V - 50/60Hz
Bulb not included
ON/OFF
CE IP20 0.5m

Matt White - ON/OFF

1A2880300.00.00

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - GU4 - MR11

12V - 20W - 24° -
2700K - 200lm - CRI 80 -
Energy Efficiency G

1Y0330450

Not included





REFLEX S

Michele Groppi / 2023

A powerful LED and a subtle mirror.


A magic and almost invisible lighting solution, which provides an indirect light that multiplies spaces and gives the eye unprecedented perspectives, unexpected depths, illusions of light.

Un LED potente, uno specchio sottile.

Un apparecchio magico e quasi invisibile per una luce che moltiplica gli spazi e regala allo sguardo prospettive inedite, profondità impreviste, illusioni di luce.

Suspension / Indirect / Indoor

Material	Metal - Mirror
Finish	.04 Matt Black




REFLEX S 1

Ceiling rose model
54W
110-240V - 50/60Hz
2700K - 5787lm / 3000K - 6156lm
CRI >90
Driver included
Driver integrated
DALI - PUSH - 1-10V
CE IP20

Matt Black - 2700K - DALI - PUSH - 1-10V
Matt Black - 3000K - DALI - PUSH - 1-10V

1A4790400.27.07
1A4790400.30.07



REFLEX S 2


Remote power supply model
49W
Max 500mA DC
2700K - 5787lm / 3000K - 6156lm
CRI >90
Driver not included
CE IP20

Matt Black - 2700K
Matt Black - 3000K

1A4790400.27.20
1A4790400.30.20

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica



Driver LED	Not included		
220-240V(100-127V)	1000mA/60W(40W)/IP20/DALI	REFLEX S 2	1Z0241140.1000

Optional accessories / Accessori opzionali

Installation kit / Kit installazione


Suspension fixing kit - See page 614 / Kit di fissaggio per sospensione - Vedi pagina 614




Recessed fixing kit for 12.5 mm plasterboard / Kit di fissaggio ad incasso per cartongesso 12,5 mm		Not included
Matt White	For suspension cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm	1X0000300.01.00
Matt Black	For suspension cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm	1X0000400.01.00
Matt White	For electrical cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm	1X0000300.04.00
Matt Black	For electrical cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm	1X0000400.04.00



Ceiling fixing kit / Kit di fissaggio a soffitto		Not included
Matt White	For suspension cables - 1 Piece	1X0010300.01.00
Matt Black	For suspension cables - 1 Piece	1X0010400.01.00
Matt White	For electrical cables - 1 Piece	1X0010300.04.00
Matt Black	For electrical cables - 1 Piece	1X0010400.04.00



Wall back plate / Piastra parete		Not included
Matt White	For mounting on brick masonry walls	1X0050300.01.00



SHANGHAI

Davide Groppi / 2013

The smallest possible shape.
A suspended luminous segment. Beautiful by itself or in composition.
Suitable for working area or kitchen.

La forma minima possibile.
Un segmento luminoso sospeso. Bellissima da sola o in composizione.
Per i luoghi di lavoro o per la cucina.

SHANGHAI

Suspension / Direct / Indoor

Material

Metal - Methacrylate

Finish


.03 Matt White

.08 Brushed Brass

Note

White ceiling rose luminaire - 304 Stainless steel suspension cables - Transparent coaxial cable.


Apparecchio con rosone bianco - Cavo di sospensione in acciaio INOX 304 - Cavo coassiale trasparente.



SHANGHAI 1
Power kit with plug model
15,5W
110-240V - 50/60Hz
2700K - 592lm / 3000K - 619lm
CRI >90
Driver included
Driver integrated
PUSH
CE IP20

Matt White - 2700K - PUSH
Matt White - 3000K - PUSH
Brushed Brass - 2700K - PUSH
Brushed Brass - 3000K - PUSH

1A3260300.27.04
1A3260300.30.04
1A3260800.27.04
1A3260800.30.04



SHANGHAI 2
Remote power supply model
13W
24V DC
2700K - 592lm / 3000K - 619lm
CRI >90
Driver not included
CE IP20

Matt White - 2700K
Matt White - 3000K
Brushed Brass - 2700K
Brushed Brass - 3000K

1A3260300.27.20
1A3260300.30.20
1A3260800.27.20
1A3260800.30.20

Daide Groppi / 2013

SHANGHAI

Electrical power supply / Alimentazione elettrica

Driver LED

220-240V(100-127V) 24V/20W(15W)/IP20/PUSH

SHANGHAI 2

1Z0240870.24

Not included

Driver LED

220-240V(100-127V) 24V/16W(15W)/IP20/DALI

SHANGHAI 2

1Z0241180.24

Not included




Driver LED

220-240V 24V/20W/IP20/TRIAC/IGBT

SHANGHAI 2

1Z0240850.24

Not included



Optional accessories / Accessori opzionali

Installation kit / Kit installazione


Suspension fixing kit - See page 614 / Kit di fissaggio per sospensione - Vedi pagina 614



Recessed fixing kit for 12.5 mm plasterboard / Kit di fissaggio ad incasso per cartongesso 12,5 mm		Not included
Matt White	For suspension cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm	1X0000300.01.00
Matt Black	For suspension cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm	1X0000400.01.00




Ceiling fixing kit / Kit di fissaggio a soffitto		Not included
Matt White	For suspension cables - 1 Piece	1X0010300.01.00
Matt Black	For suspension cables - 1 Piece	1X0010400.01.00



Wall back plate / Piastra parete		Not included
Matt White	For mounting on brick masonry walls	1X0050300.01.00

Suspension kit / Kit sospensione



Sloped ceiling fixing hook / Gancio per soffitto inclinato		Not included
Chrome plated - 1 Piece		1A0530000.00.00




SIMBIOSI

Davide Groppi / 2015

A de-structured chandelier that can be re-assembled as you like.
A conjuring trick that gives you the possibility of connecting the diodes in series
using very weak electric currents with wires that are practically invisible.
The very thin wire that connects the light sources and brings them alive, one in
relation to the other, is the principal component of this project.


Un lampadario destrutturato e componibile a piacere.
Un piccolo gioco di prestigio sfruttando la possibilità di collegare i diodi in serie utilizzando
correnti elettriche molto basse e quindi cavi quasi invisibili.
Il filo, sottilissimo, che unisce i corpi e li fa vivere l'uno in funzione dell'altro, è la
caratteristica principale di questo progetto.

Suspension / Direct / Indoor		
Material	Metal	
Finish	.03 Matt White .26 Total Black	
Note	White finish luminaire with white ceiling rose and red wires - Black finish luminaire with black ceiling rose and anthracite gray wires - 304 Stainless steel suspension cables.	
	Apparecchio con rosone bianco e cavi rossi per la finitura bianca e rosone nero e cavi grigio antracite per la finitura nera - Cavo di sospensione in acciaio INOX 304.	




SIMBIOSI
15W
110-240V - 50/60Hz
2700K - 931lm / 3000K - 960lm
CRI >90
Driver included
Driver integrated
DALI
C E IP20


Matt White - 2700K - DALI	1A2870300.27.01
Matt White - 3000K - DALI	1A2870300.30.01
Total Black - 2700K - DALI	1A2872600.27.01
Total Black - 3000K - DALI	1A2872600.30.01




SIMBIOSI
15W
110-240V - 50/60Hz
2700K - 931lm / 3000K - 960lm
CRI >90
Driver included
Driver integrated
PUSH
C E IP20

Matt White - 2700K - PUSH	1A2870300.27.04
Matt White - 3000K - PUSH	1A2870300.30.04
Total Black - 2700K - PUSH	1A2872600.27.04
Total Black - 3000K - PUSH	1A2872600.30.04

Optional accessories / Accessori opzionali		
Installation kit / Kit installazione		Suspension fixing kit - See page 614 / Kit di fissaggio per sospensione - Vedi pagina 614
		Recessed fixing kit for 12.5 mm plasterboard / Kit di fissaggio ad incasso per cartongesso 12,5 mm
Not included		
Matt White	For suspension cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm	1X0000300.01.00
Matt Black	For suspension cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm	1X0000400.01.00
		Ceiling fixing kit / Kit di fissaggio a soffitto
Not included		
Matt White	For suspension cables - 1 Piece	1X0010300.01.00
Matt Black	For suspension cables - 1 Piece	1X0010400.01.00
		Wall back plate / Piastra parete
Not included		
Matt White	For mounting on brick masonry walls	1X0050300.01.00
		Sloped ceiling fixing hook / Gancio per soffitto inclinato
Not included		
Chrome plated - 1 Piece		1A0530000.00.00





SOTTILE

Davide Groppi / 2023

A blade of light just 7 millimetres thick, the expression of that purest and most essential part of our thought. The surprise of an extremely thin, yet at the same time very bright, lamp.


Una lama di luce spessa solo 7 millimetri, espressione di una parte del nostro pensiero, quello più puro ed essenziale. La sorpresa di una lampada estremamente sottile ma al contempo molto luminosa.

Suspension / Direct / Indoor

Material	Metal		
Finish	.29 Brushed Champagne	.36	Brushed Black Chrome

Note Dimmable suspension lamp for direct light.

Apparecchio a sospensione dimmerabile a luce diretta.




SOTTILE 1

Ceiling rose model
22W
220-240V - 50/60Hz
2700K - 1692lm / 3000K - 1855lm
CRI >90
Driver included
Driver integrated
DALI - PUSH - 1-10V - TRIAC

CE IP20

Brushed Champagne - 2700K - DALI - PUSH - 1-10V - TRIAC	1A4232900.27.05
Brushed Champagne - 3000K - DALI - PUSH - 1-10V - TRIAC	1A4232900.30.05
Brushed Black Chrome - 2700K - DALI - PUSH - 1-10V - TRIAC	1A4233600.27.05
Brushed Black Chrome - 3000K - DALI - PUSH - 1-10V - TRIAC	1A4233600.30.05




SOTTILE 1 DE

Ceiling rose model - Dual emission
44W
120-240V - 50/60Hz
2700K - Up 1692lm - Down 1692lm /
3000K - Up 1855lm - Down 1855lm
CRI >90
Driver included
Driver integrated
DALI - PUSH - 1-10V - TRIAC

CE IP20

Brushed Champagne - 2700K - DALI - PUSH - 1-10V - TRIAC	1A4642900.27.05
Brushed Champagne - 3000K - DALI - PUSH - 1-10V - TRIAC	1A4642900.30.05
Brushed Black Chrome - 2700K - DALI - PUSH - 1-10V - TRIAC	1A4643600.27.05
Brushed Black Chrome - 3000K - DALI - PUSH - 1-10V - TRIAC	1A4643600.30.05




SOTTILE 2

Remote power supply model
19W
24V DC
2700K - 1692lm / 3000K - 1855lm
CRI >90
Driver not included

CE IP20

Brushed Champagne - 2700K	1A4232900.27.20
Brushed Champagne - 3000K	1A4232900.30.20
Brushed Black Chrome - 2700K	1A4233600.27.20
Brushed Black Chrome - 3000K	1A4233600.30.20



SOTTILE 2 DE

Remote power supply model -
Double output
38W
24V DC
2700K - Up 1692lm - Down 1692lm /
3000K - Up 1855lm - Down 1855lm
CRI >90
Driver not included

CE IP20

Brushed Champagne - 2700K	1A4642900.27.20
Brushed Champagne - 3000K	1A4642900.30.20
Brushed Black Chrome - 2700K	1A4643600.27.20
Brushed Black Chrome - 3000K	1A4643600.30.20

Optional accessories / Accessori opzionali

Installation kit / Kit installazione

Suspension fixing kit - See page 614 / Kit di fissaggio per sospensione - Vedi pagina 614



Recessed fixing kit for 12.5 mm plasterboard / Kit di fissaggio ad incasso per cartongesso 12,5 mm

Not included

Matt White	For suspension cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm	1X0000300.01.00
Matt Black	For suspension cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm	1X0000400.01.00
Matt White	For electrical cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm	1X0000300.04.00
Matt Black	For electrical cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm	1X0000400.04.00




Ceiling fixing kit / Kit di fissaggio a soffitto

Not included

Matt White	For suspension cables - 1 Piece	1X0010300.01.00
Matt Black	For suspension cables - 1 Piece	1X0010400.01.00
Matt White	For electrical cables - 1 Piece	1X0010300.04.00
Matt Black	For electrical cables - 1 Piece	1X0010400.04.00


Electrical power supply / Alimentazione elettrica



Driver LED

Not included

100-240V	24V/50W/IP20/ON/OFF	SOTTILE 2 / SOTTILE 2 DE	1Z1120490
----------	---------------------	--------------------------	-----------




Controller

Not included


Matt Black	DALI - PUSH - 0/1-10V - TRIAC - IP20	1Z2170010
------------	--------------------------------------	-----------

Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Wall back plate / Piastra parete		Not included
Matt White	For mounting on brick masonry walls	1X0050300.01.00





SOTTOSOPRA

Davide Groppi / 2023

The purity of the suspended cone encases a small light machine that produces direct, indirect and diffused light at the same time.

Sottosopra: pure, elegant, wonderfully efficient.

La purezza del cono sospeso racchiude una piccola macchina di luce che produce contemporaneamente luce diretta, indiretta e diffusa.

Sottosopra: pura, elegante, meravigliosamente efficiente.

SOTTOSOPRA

Davide Groppi / 2023

Suspension / Indirect-Direct / Indoor

Material

Metal


Finish

.03 Matt White

Note


Dimmable suspension lamp with double emission.

Apparecchio a sospensione dimmerabile a doppia emissione.




SOTTOSOPRA 1
Ceiling rose model
30W
100-240V - 50/60Hz
2700K - Down 228lm - Up 1827lm /
3000K - Down 245lm - Up 1876lm
CRI >90 / >80
Driver included
TRIAC/IGBT
CE IP20

Matt White - 2700K - TRIAC/IGBT	1A4540300.27.02
Matt White - 3000K - TRIAC/IGBT	1A4540300.30.02



SOTTOSOPRA 1
Ceiling rose model
30W
100-240V - 50/60Hz
2700K - Down 228lm - Up 1827lm /
3000K - Down 245lm - Up 1876lm
CRI >90 / >80
Driver included
DALI - PUSH - 1-10V
CE IP20

Matt White - 2700K - DALI - PUSH - 1-10V	1A4540300.27.07
Matt White - 3000K - DALI - PUSH - 1-10V	1A4540300.30.07



SOTTOSOPRA 2
Remote power supply model
30W
Max 500mA DC
2700K - Down 228lm - Up 1827lm /
3000K - Down 245lm - Up 1876lm
CRI >90 / >80
Driver not included
2 Drivers required
CE IP20

Matt White - 2700K	1A4540300.27.20
Matt White - 3000K	1A4540300.30.20

Davide Groppi / 2023

SOTTOSOPRA

Optional accessories / Accessori opzionali

Installation kit / Kit installazione

Suspension fixing kit - See page 614 / Kit di fissaggio per sospensione - Vedi pagina 614

Recessed fixing kit for 12.5 mm plasterboard / Kit di fissaggio ad incasso per cartongesso 12,5 mm

Not included


Matt White	For electrical cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm	SOTTOSOPRA 2	1X0000300.05.00
Matt Black	For electrical cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm	SOTTOSOPRA 2	1X0000400.05.00

Electrical power supply / Alimentazione elettrica

Driver LED			Not included
220-240V(110-127V)	500mA/25W(13,5W)/IP20/DALI - PUSH - 1-10V	SOTTOSOPRA 2	1Z0241270.500

Driver LED			Not included
220-240V	500mA/36,4W/IP20/TRIAC/IGBT	SOTTOSOPRA 2	1Z2270010.500

219





A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

Suspension / Direct / Indoor	
Material	Metal - Polycarbonate
Finish	.03 Matt White
Note	White ceiling rose luminaire with Extradark comfort system - 304 Stainless steel suspension cables - SPY: white cables - SPY DE: dual emission and separate switch - Transparent cable.
	Apparecchio con rosone bianco e dotato di Extradark comfort system - Cavo di sospensione in acciaio INOX 304 - SPY: cavo bianco - SPY DE: doppia emissione con accensione separata - Cavo trasparente.

	SPY 39W 110-240V - 50/60Hz 3000K - 4292lm CRI >80 UGR <19 Driver included Driver integrated DALI C E IP20 	Matt White - 3000K - DALI	1A2910300.30.01
	SPY DE Dual emission 77W 110-240V - 50/60Hz 3000K - Down 4292lm - Up 4360lm CRI >80 UGR <19 Driver included Driver integrated DALI C E IP20 	Matt White - 3000K - DALI	1A2940300.30.01

Optional accessories / Accessori opzionali	
Installation kit / Kit installazione	
Suspension fixing kit - See page 614 / Kit di fissaggio per sospensione - Vedi pagina 614	
	
Recessed fixing kit for 12.5 mm plasterboard / Kit di fissaggio ad incasso per cartongesso 12,5 mm	
Not included	
Matt White	For suspension cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm
1X0000300.03.00	
Matt Black	For suspension cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm
1X0000400.03.00	
Ceiling fixing kit / Kit di fissaggio a soffitto	
Not included	
Matt White	For suspension cables - 1 Piece
1X0010300.03.00	
Matt Black	For suspension cables - 1 Piece
1X0010400.03.00	
Wall back plate / Piastra parete	
Not included	
Matt White	For mounting on brick masonry walls
1X0050300.01.00	
Sloped ceiling fixing kit / Kit fissaggio soffitto inclinato	
Not included	
Nickel plated - 1 Piece	
1A0510000.00.00	

WALL / PARETE



DOT P

Omar Carraglia - Davide Groppi / 2015


A tool to light.

A luminaire designed for use with state-of-the-art LED modules to offer superior performance and a wide range of light beams.

Elemento di luce.


Un apparecchio progettato per utilizzare moduli a LED in grado di fornire prestazioni superiori ed un'ampia gamma di fasci luminosi.

Wall / Direct / Indoor		
Material	Metal	
Finish	.03 Matt White	.04 Matt Black
Note	Adjustable luminaire.	
	Apparecchio orientabile.	




DOT P
13W
100-240V - 50/60Hz
2700K / 3000K
CRI 97
Driver included
Driver integrated
DALI
C E IP20

Matt White - 2700K - DALI	1A2340300.27.01
Matt White - 3000K - DALI	1A2340300.30.01
Matt Black - 2700K - DALI	1A2340400.27.01
Matt Black - 3000K - DALI	1A2340400.30.01




DOT P
13W
100-240V - 50/60Hz
2700K / 3000K
CRI 97
Driver included
Driver integrated
PUSH
C E IP20

Matt White - 2700K - PUSH	1A2340300.27.04
Matt White - 3000K - PUSH	1A2340300.30.04
Matt Black - 2700K - PUSH	1A2340400.27.04
Matt Black - 3000K - PUSH	1A2340400.30.04




DOT P 51
Max 10W - GU10
100-240V - 50/60Hz
Bulb not included
ON/OFF
C E IP20

Matt White - ON/OFF	1A2490300.00.00
Matt Black - ON/OFF	1A2490400.00.00



DOT P DE
Dual emission
29W
220-240V - 50/60Hz
2700K / 3000K
CRI 97
Driver included
Driver integrated
DALI
C E IP20

Matt White - 2700K - DALI	1A4900300.27.01
Matt White - 3000K - DALI	1A4900300.30.01
Matt Black - 2700K - DALI	1A4900400.27.01
Matt Black - 3000K - DALI	1A4900400.30.01



DOT P DE 51
Dual emission
Max 2x10W - GU10
100-240V - 50/60Hz
Bulb not included
ON/OFF
C E IP20

Matt White - ON/OFF	1A3810300.00.00
Matt Black - ON/OFF	1A3810400.00.00

Compulsory accessories / Accessori obbligatori

Other accessories / Altri accessori



Lens / Lente		Not included	
Beam - 14°	2700K - CRI 97 - 983lm	DOT P	1A3090000.00.00
	2700K - CRI 97 - 1966lm	DOT P DE	
	3000K - CRI 97 - 1038lm	DOT P	
	3000K - CRI 97 - 2076lm	DOT P DE	
Beam - 24°	2700K - CRI 97 - 943lm	DOT P	1A3100000.00.00
	2700K - CRI 97 - 1886lm	DOT P DE	
	3000K - CRI 97 - 996lm	DOT P	
	3000K - CRI 97 - 1992lm	DOT P DE	
Beam - 36°	2700K - CRI 97 - 955lm	DOT P	1A3110000.00.00
	2700K - CRI 97 - 1910lm	DOT P DE	
	3000K - CRI 97 - 1005lm	DOT P	
	3000K - CRI 97 - 2010lm	DOT P DE	
Beam - 50°	2700K - CRI 97 - 965lm	DOT P	1A3120000.00.00
	2700K - CRI 97 - 1930lm	DOT P DE	
	3000K - CRI 97 - 1016lm	DOT P	
	3000K - CRI 97 - 2032lm	DOT P DE	

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - GU10 - PAR16		Not included	
	220-240V - 5,5W - 25° - 3000K - 375lm - CRI 97 - Energy Efficiency G - Dimmable	DOT P 51	1Y0330500




LED SORAA - GU10 - MR16		Not included	
	230V - 7,5W - 10° - 2700K - 390lm - CRI 95 - Energy Efficiency G - Dimmable	DOT P 51 / DOT P DE 51	1Y1580210




LED SORAA - GU10 - MR16		Not included	
	230V - 7,5W - 10° - 3000K - 410lm - CRI 95 - Energy Efficiency G - Dimmable	DOT P 51 / DOT P DE 51	1Y1580010

Optional accessories / Accessori opzionali


Other accessories / Altri accessori




Accessory holder + Honeycomb louvre / Porta accessori + Frangiluce nido d'ape		Not included	
		DOT P / DOT P DE	1X0080400.01.00




Elliptical filter / Filtro ellittico		Not included	
Standard		DOT P / DOT P DE	1X0080000.02.00



Blue filter / Filtro blu		Not included	
Standard		DOT P / DOT P DE	1X0080000.03.00




Red filter / Filtro rosso		Not included	
Standard		DOT P / DOT P DE	1X0080000.04.00




Yellow filter / Filtro giallo		Not included	
Standard		DOT P / DOT P DE	1X0080000.05.00


Other accessories / Altri accessori



Darklight		Not included	
MR16		DOT P 51 / DOT P DE 51	51580040



25° beam filter / Filtro fascio 25°		Not included	
MR16		DOT P 51 / DOT P DE 51	51580020



36° beam filter / Filtro fascio 36°		Not included	
MR16		DOT P 51 / DOT P DE 51	51580030



It is pure form.

A tool to light, simple container for the light source.

Light is incorporated into the space, becoming an architectural element.

È forma pura.

Elemento di luce semplice contenitore della fonte luminosa.


La luce si integra con lo spazio diventando elemento architettonico.

DUET

/ 2014

Wall / Diffuse / Indoor

Material	Glass - Metal		
Finish	.03 Matt White	.04	Matt Black




DUET

23W
220-240V - 50/60Hz
2700K - 1293lm / 3000K - 1352lm
CRI >90
TRIAC/IGBT
CE IP20

Matt White - 2700K - TRIAC/IGBT
Matt White - 3000K - TRIAC/IGBT
Matt Black - 2700K - TRIAC/IGBT
Matt Black - 3000K - TRIAC/IGBT

1A3300300.27.02
1A3300300.30.02
1A3300400.27.02
1A3300400.30.02





EDISON'S NIGHTMARE

Harry Thaler / 2014

A gestural project, full of irony and nostalgia.

Therefore, among a thousand stories, prohibitions, absurd technical rules,
we have reached the end. The end of the incandescent bulb.

Edison's Nightmare is a salute to Edison's light bulb*, a dream that changed the way
we live forever, stealing time to read and write from sleep.

It is a classic light bulb, nailed to the wall. Like a work of art.

** From 01 September 2012, incandescent bulbs cannot be sold in the EU.*

Un progetto gestuale, carico di ironia e nostalgia.

E così, tra mille vicende, divieti, assurde norme tecniche, siamo arrivati alla fine.

Alla fine della lampadina a incandescenza.

Edison's Nightmare è un saluto alla lampadina di Edison*, ad un sogno che ha cambiato
per sempre il modo di vivere, sottraendo al sonno ore da dedicare a lettura e scrittura.


Si tratta di una classica lampadina inchiodata al muro. Come un'opera d'arte.

** Dal 1 Settembre 2012 non è più possibile, nella Comunità Europea, vendere lampadine ad
incandescenza.*

EDISON'S NIGHTMARE

Harry Thaler / 2014

Wall / Diffuse / Indoor	
Material	Blown glass - Metal
Finish	.00 Standard
Note	
Coaxial cable luminaire - Transparent cable - Halogen bulb included.	
Apparecchio orientabile con cavo coassiale - Cavo trasparente - Lampadina alogena inclusa.	



EDISON'S NIGHTMARE

Max 10W - G4 12V
100-240V - 50/60Hz
Bulb included
Driver included
Dimmer on board

CE IP20

Standard - Dimmer on board

1A3380000.00.06





A luminous short film.

Telling a story in light, a series of old 35MM slides are lit from behind, pulsating and shown at random.

The photographs can be assembled and replaced as you like.

The choice of the message to be communicated is completely personal: it can be an image, a logo, a sentence, anything you want to represent, at any time. The light message is punctuated by a blinking LED, offering reading in movement.

Un cortometraggio luminoso.

Per raccontare una storia con la luce, retroilluminando in modo pulsante e casuale le vecchie diapositive da 35MM.

Le fotografie possono essere montate e sostituite a piacimento.

La scelta del messaggio da comunicare è del tutto personale: può essere un'immagine, un logo, una frase, tutto ciò che al momento si vuole rappresentare.


Il messaggio luminoso, ritmato attraverso la diversa intermittenza dei LED, permette una lettura in movimento.

Objects-Wall / Diffuse / Indoor

Material Metal - Polycarbonate
Finish .00 Standard

Note Slowly flashing lights luminaire - White luminous module - Black fixing structure - Customizable images not included - Modules connector included.

Apparecchio a luce a lenta intermittenza - Modulo luminoso bianco - Barra per fissaggio nero opaco - Immagini personalizzabili non incluse - Connettore moduli incluso.




FILM
3W
5V DC
Driver not included
Driver on the wall
ON/OFF
CE IP20

Standard - ON/OFF

1A3410000.00.00

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica



Power supply with plug / Kit di alimentazione con spina		Not included
100-240V	5V/15W/IP20/ON/OFF	1Z1470180






FOIL

967 DESIGN / 2011

An architectural lamp for wall and ceiling installation.
Although it's there, you can't see the thickness.
A luminaire that amazes with skill, so you only notice its two-dimensional effect.

Lampada architettuale, da installare sia a parete che a soffitto.
Lo spessore c'è, ma non si vede. Apparecchio efficace e stupendo
nel momento in cui si coglie solo l'aspetto bidimensionale.

Wall / Indirect / Indoor			
Material	Metal		
Finish	.03 Matt White	.04	Matt Black



FOIL LED

24,5W
220-230V - 50/60Hz
2700K - 1681lm / 3000K - 1808lm
CRI >90
TRIAC/IGBT
CE IP20

Matt White - 2700K - TRIAC/IGBT
Matt White - 3000K - TRIAC/IGBT
Matt Black - 2700K - TRIAC/IGBT
Matt Black - 3000K - TRIAC/IGBT

1A3150300.27.02
1A3150300.30.02
1A3150400.27.02
1A3150400.30.02




An indirect wall light project.
The light source remains invisible while the light comes out soft
from the metal diffuser, creating a delicate atmosphere.

Un lavoro sulla luce indiretta da parete.
La sorgente rimane invisibile mentre la luce esce morbida dal diffusore metallico,
creando un'atmosfera delicata.

FOLDER

967 DESIGN / 2013

Wall / Indirect / Indoor
Material Metal
Finish .03 Matt White



FOLDER
20W
110-240V - 50/60Hz
2700K - 397lm / 3000K - 415lm
CRI >80
Driver included
Driver integrated
DALI
CE IP20

Matt White - 2700K - DALI
Matt White - 3000K - DALI

1A3350300.27.01
1A3350300.30.01





A tool to light.

The luminaire is pure form, a simple container for the light source.

Single-emission lamp with light directed downwards.

Light is incorporated into the space, becoming an architectural element.


Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.

Lampada monoemissione con luce direzionata verso il basso.

La luce si integra con lo spazio diventando elemento architettonico.

Wall / Diffuse / Indoor			
Material	Metal - Methacrylate		
Finish	.03 Matt White	.04	Matt Black



LINET
11,5W
220-240V - 50/60Hz
2700K - 626lm / 3000K - 655lm
CRI >90
TRIAC/IGBT
CE IP20

Matt White - 2700K - TRIAC/IGBT
Matt White - 3000K - TRIAC/IGBT
Matt Black - 2700K - TRIAC/IGBT
Matt Black - 3000K - TRIAC/IGBT

1A3310300.27.02
1A3310300.30.02
1A3310400.27.02
1A3310400.30.02




MIRA

Omar Carraglia / 2012

Lamp with a simple and essential shape.
For interiors and adjustable.

Lampada dalla forma semplice ed essenziale.
Per interni e orientabile.


Wall / Direct / Indoor		
Material	Metal	
Finish	.03 Matt White	.04 Matt Black
Note		
Adjustable luminaire.		
Apparecchio orientabile.		



MIRA
8W
110-240V - 50/60Hz
2700K - 327lm / 3000K - 352lm
CRI >90
Driver included
Driver integrated
ON/OFF
C E IP20

Matt White - 2700K - ON/OFF
Matt White - 3000K - ON/OFF
Matt Black - 2700K - ON/OFF
Matt Black - 3000K - ON/OFF


1A2280300.27.00
1A2280300.30.00
1A2280400.27.00
1A2280400.30.00



MIRA
8W
110-240V - 50/60Hz
2700K - 327lm / 3000K - 352lm
CRI >90
Driver included
Driver integrated
DALI
C E IP20

Matt White - 2700K - DALI
Matt White - 3000K - DALI
Matt Black - 2700K - DALI
Matt Black - 3000K - DALI

1A2280300.27.01
1A2280300.30.01
1A2280400.27.01
1A2280400.30.01



MIRA
8W
110-240V - 50/60Hz
2700K - 327lm / 3000K - 352lm
CRI >90
Driver included
Driver integrated
PUSH
C E IP20

Matt White - 2700K - PUSH
Matt White - 3000K - PUSH
Matt Black - 2700K - PUSH
Matt Black - 3000K - PUSH

1A2280300.27.04
1A2280300.30.04
1A2280400.27.04
1A2280400.30.04





MIRA MAGNETIC

Omar Carraglia / 2015


Lamp with a simple and essential shape.
For interiors and adjustable, it is designed with a magnetic application system
to be even more versatile and functional.

Lampada dalla forma semplice ed essenziale.
Per interni e orientabile, è concepita con sistema di applicazione magnetico
per essere ancora più versatile e funzionale.

MIRA MAGNETIC

Omar Carraglia / 2015

Wall / Direct / Indoor		
Material	Metal	
Finish	.03 Matt White	.04 Matt Black
Note	Adjustable luminaire with magnetic fixing base - White finish luminaire with white cable and black finish luminaire with black cable (3 m).	
	Apparecchio orientabile con base a fissaggio magnetico - Cavo bianco per la finitura bianca e cavo nero (3 m) per la finitura nera.	



MIRA MAGNETIC

5,6W
Max 500mA DC
2700K - 327lm / 3000K - 352lm
CRI >90
Driver not included


CE IP20

Matt White - 2700K
Matt White - 3000K
Matt Black - 2700K
Matt Black - 3000K


1A3680300.27.20
1A3680300.30.20
1A3680400.27.20
1A3680400.30.20

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica



Driver LED		Not included
220-240V(100-127V)	500mA/20W(15W)/IP20/PUSH - 1-10V	1Z0240870.500



Power supply kit with plug / Kit alimentazione con spina		Not included
Matt White	Input 100-240V - 50/60Hz - Output 350mA - 15W - IP20 - Dimmer on board	1A3180300.00.06
Matt Black	Input 100-240V - 50/60Hz - Output 350mA - 15W - IP20 - Dimmer on board	1A3180400.00.06





MORSETTO P

Davide Groppi / 2019

A lamp that can be positioned, balanced and turned,
but overall it produces a beautiful light on the table.

It's the wall version of the Morsetto lamp.
Three adjustable arms allow the light source to be positioned
far from where the lamp is attached.

Una lampada che si inclina, si bilancia, si gira,
ma soprattutto che produce una bellissima luce sul tavolo.

È la versione da parete della lampada Morsetto.
Tre bracci regolabili permettono di portare la fonte luminosa
lontana dal punto di fissaggio.

MORSETTO P

Davide Groppi / 2019

Wall / Direct / Indoor

Material

Metal


Finish

.04 Matt Black

Note

Adjustable luminaire with Extradark comfort system - Black cable.

Apparecchio orientabile con cavo nero, dotato di Extradark comfort system.



MORSETTO P

13W

24V DC

2700K - 765lm / 3000K - 823lm

CRI >90

UGR <19

Driver included

Dimmer on board

CE IP20

Matt Black - 2700K - Dimmer on board


Matt Black - 3000K - Dimmer on board

1A2570400.27.06

1A2570400.30.06

Optional accessories / Accessori opzionali

Electrical power supply / Alimentazione elettrica



Power supply / Alimentatore

Included

Matt Black	Input 110-240V - 50/60Hz - Output 24V DC - 18W - IP20	1Z0431020
------------	--	-----------





PIÙ

Davide Groppi / 2007

A tool to light.


Pure form, a simple container for the light source.

Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Forma pura, semplice contenitore della fonte luminosa.

La luce si integra con lo spazio diventando elemento architettonico.




PIÙ
Max 120W - R7s
100-240V - 50/60Hz
Bulb not included
ON/OFF
CE IP20

Matt White - ON/OFF

1A3370300.00.00






A ready-made project to design the space with a sense of irony and weightlessness.
The tracks of an electric train can be used to draw a heart,
but also to conduct electricity.
Rail is the boundary between usefulness and show, between art and design.


Un ready-made per firmare lo spazio con ironia e leggerezza.
I binari di un trenino elettrico sono lo strumento per disegnare un cuore,
ma anche per condurre la corrente elettrica.
Rail è sul confine tra utilità e rappresentazione, design e arte.

Wall / Direct / Indoor	
Material	ABS - Metal
Finish	.00 Standard
Note	Black rails luminaire - Black cable.
Apparecchio con binari neri - Cavo nero.	



RAIL
22W
24V DC
3000K - 2000lm
CRI >90
Driver included
Dimmer on board
CE IP20

Standard - 3000K - Dimmer on board | 1A3400000.30.06 |





REFLEX

Michele Groppi / 2022

A powerful LED and a subtle mirror.

A magic and almost invisible lighting solution, which provides an indirect light that multiplies spaces and gives the eye unprecedented perspectives, unexpected depths, illusions of light.

Luminaire designed to be powered by the Endless system.

Un LED potente, uno specchio sottile.

Un apparecchio magico e quasi invisibile per una luce che moltiplica gli spazi e regala allo sguardo prospettive inedite, profondità imprevedute, illusioni di luce. Apparecchio predisposto per essere alimentato dal sistema Endless.

REFLEX

Michele Groppi / 2022

Wall / Indirect / Indoor

Material

Metal - Mirror


Finish

.04 Matt Black

Note

Luminaire with mirror top and black back side.

Apparecchio con piano a specchio e retro nero.



REFLEX

23W

48V DC

2700K - 2158lm / 3000K - 2320lm

CRI >90

Driver not included

CE IP20 ENEC

Matt Black - 2700K


Matt Black - 3000K

1A0850400.27.20

1A0850400.30.20

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica




Driver LED

100-240V

48V/60W/IP20/1-10V

1Z1120600

Not included



Driver LED

220-240V

48V/60W/IP20/DALI

1Z0830820

Not included





Reflections of light.

The pure and essential form of a thin mirror wich provides indirect light.

Riflessioni di luce.

La forma pura ed essenziale di uno specchio sottile a luce indiretta.

SHADE

Federico Delrosso / 2013


Wall / Indirect / Indoor

Material	Metal - Mirror
Finish	.00 Standard

Note

Mirror top luminaire.

Apparecchio con piano a specchio.




SHADE
23W
220-240V - 50/60Hz
2700K - 1293lm / 3000K - 1352lm
CRI >90
Driver included
Driver integrated
TRIAC/IGBT
CE IP20

Standard - 2700K - TRIAC/IGBT
Standard - 3000K - TRIAC/IGBT

1A3360000.27.02
1A3360000.30.02





SOL 1

Omar Carraglia - Davide Groppi / 2003


A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

Wall / Indirect / Indoor			
Material	Metal		
Finish	.03 Matt White	.04 Matt Black	

	SOL 1		
	12,5W		
	220-230V - 50/60Hz		
	2700K - 836lm / 3000K - 899lm		
	CRI >90		
		TRIAC/IGBT	
		CE IP20	
		Matt White - 2700K - TRIAC/IGBT	1A3130300.27.02
		Matt White - 3000K - TRIAC/IGBT	1A3130300.30.02
		Matt Black - 2700K - TRIAC/IGBT	1A3130400.27.02
		Matt Black - 3000K - TRIAC/IGBT	1A3130400.30.02





SOL 2

/ 2008


A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

Wall / Indirect / Indoor			
Material	Metal		
Finish	.03 Matt White	.04	Matt Black



SOL 2
24,5W
220-230V - 50/60Hz
2700K - 1681lm / 3000K - 1808lm
CRI >90
TRIAC/IGBT
CE IP20

Matt White - 2700K - TRIAC/IGBT
Matt White - 3000K - TRIAC/IGBT
Matt Black - 2700K - TRIAC/IGBT
Matt Black - 3000K - TRIAC/IGBT

1A3140300.27.02
1A3140300.30.02
1A3140400.27.02
1A3140400.30.02






A luminaire designed for use with state-of-the-art LED modules to offer superior performance and a wide range of light beams.
Luminaire designed to be powered by Endless system.

Un apparecchio illuminante progettato per utilizzare moduli a LED in grado di fornire prestazioni superiori ed un'ampia gamma di fasci luminosi.
Apparecchio predisposto per essere alimentato dal sistema Endless.


Wall-Ceiling / Direct / Indoor		
Material	Metal	
Finish	.03 Matt White	.04 Matt Black
Note	Adjustable luminaire.	
	Apparecchio orientabile.	



SPOT
Max 21W
220-240V - 50/60Hz
Driver included
Driver integrated
DALI
LED Module not included
CE IP20

Matt White - DALI
Matt Black - DALI

1A1080300.00.01
1A1080400.00.01




SPOT
Max 21W
220-240V - 50/60Hz
Driver included
Driver integrated
PUSH
LED Module not included
CE IP20

Matt White - PUSH
Matt Black - PUSH


1A1080300.00.04
1A1080400.00.04

Optional accessories / Accessori opzionali


LED modules / Moduli LED



DG111 LED Module / Modulo LED DG111	Not included
16,7W - 15° - 500mA DC - 2700K - 1648lm - CRI 90 - Energy Efficiency F - Dimmable	1A4700000.27.20
16,7W - 15° - 500mA DC - 3000K - 1682lm - CRI 90 - Energy Efficiency F - Dimmable	1A4700000.30.20




DG111 LED Module / Modulo LED DG111	Not included
16,7W - 22° - 500mA DC - 2700K - 1859lm - CRI 90 - Energy Efficiency F - Dimmable	1A3890000.27.20
16,7W - 22° - 500mA DC - 3000K - 1945lm - CRI 90 - Energy Efficiency F - Dimmable	1A3890000.30.20




DG111 LED Module / Modulo LED DG111	Not included
16,7W - 36° - 500mA DC - 2700K - 1808lm - CRI 90 - Energy Efficiency F - Dimmable	1A3900000.27.20
16,7W - 36° - 500mA DC - 3000K - 1890lm - CRI 90 - Energy Efficiency F - Dimmable	1A3900000.30.20


Other accessories / Altri accessori



Horizontal directional fins / Alette direzionali	Not included
Matt Black	1X0070400.01.00



Cylindrical screen / Schermo cilindrico	Not included
Matt Black	1X0070400.02.00



Cone 45° / Cono 45°	Not included
Matt Black	1X0070400.03.00

Optional accessories / Accessori opzionali

Other accessories / Altri accessori



Accessory holder + Soft filter + Honeycomb louvre / Porta accessori + Filtro soft + Frangiluce nido d'ape	Not included
Matt Black	1X0070400.04.00



Accessory holder + Elliptical filter / Porta accessori + Filtro ellittico	Not included
Matt Black	1X0070400.05.00



Blue filter / Filtro blu	Not included
Standard	1X0070000.06.00



Red filter / Filtro rosso	Not included
Standard	1X0070000.07.00



Yellow filter / Filtro giallo	Not included
Standard	1X0070000.08.00



TOAST

Davide Groppi - Alberto Zattin / 2001




The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

TOAST

Davide Groppi - Alberto Zattin / 2001

Wall / Diffuse / Indoor				
Material	Glass - Metal			
Finish	.01 Polished Chrome	.03 Matt White	.04 Matt Black	.08 Brushed Brass
	.14 Brushed Chrome			
Note	Bulb not included with specifications: ø 25 mm x 78 mm.			
	Lampadina non inclusa con specifiche ø 25 mm x 78 mm.			





TOAST

12W
100-240V - 50/60Hz
2700K - 743lm / 3000K - 743lm
CRI >90
Driver included
Driver integrated
ON/OFF
CE IP20

Polished Chrome - 2700K - ON/OFF	1A3280100.27.00
Polished Chrome - 3000K - ON/OFF	1A3280100.30.00
Matt White - 2700K - ON/OFF	1A3280300.27.00
Matt White - 3000K - ON/OFF	1A3280300.30.00
Matt Black - 2700K - ON/OFF	1A3280400.27.00
Matt Black - 3000K - ON/OFF	1A3280400.30.00
Brushed Brass - 2700K - ON/OFF	1A3280800.27.00
Brushed Brass - 3000K - ON/OFF	1A3280800.30.00
Brushed Chrome - 2700K - ON/OFF	1A3281400.27.00
Brushed Chrome - 3000K - ON/OFF	1A3281400.30.00







Utopia is a project on the limit state of light, the research for the minimum dimension necessary for pure and essential lighting. It represents full flexibility, in both its design and its light control.

The light strip reaches into space, bending, breaking and drawing abstract, mysterious patterns.

Utopia è un progetto sullo stato limite della luce, alla ricerca della dimensione minima necessaria per illuminare in modo puro ed essenziale.

Rappresenta la massima flessibilità, sia nel disegno della linea che nella gestione della luce. Il nastro luminoso si tende nello spazio, piegandosi, interrompendosi, disegnando grafi astratti e misteriosi.

UTOPIA


Davide Groppi / 2023

Wall / Indirect / Indoor

Material	Metal
Finish	.00 Standard

Note Dimmable wall luminaire.

Apparecchio da parete dimmerabile.




UTOPIA 6

Length 6000 mm
79W
24V DC
2700K - 6079lm / 3000K - 6322lm
CRI >90
Driver not included



Standard - 2700K
Standard - 3000K

1A4250000.27.20
1A4250000.30.20



UTOPIA 12

Length 12000 mm
125W
24V DC
2700K - 10133lm / 3000K - 10538lm
CRI >90
Driver not included




Standard - 2700K
Standard - 3000K

1A4600000.27.20
1A4600000.30.20

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica




Driver LED				Not included
100-240V	24V/96W/IP67/1-10V	UTOPIA 6	1Z1120540	

Davide Groppi / 2023


UTOPIA

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica



Driver LED				Not included
100-240V	24V/150W/IP67/1-10V	UTOPIA 12	1Z1120500	




Controller	Not included
Matt Black DALI - PUSH - 0/1-10V- TRIAC - IP20	1Z2170010

Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Accessory 1 / Accessorio 1	Not included
Polished Chrome	1A4480100.00.00



Accessory 2 / Accessorio 2		Not included
Polished Chrome	1A4490100.00.00	



Strip LED - 6 m			Not included
Input 24V DC - 79W - IP20 - 2700K - 6079lm - CRI >90	UTOPIA 6	1A4940000.27.00	



Strip LED - 12 m				Not included
Input 24V DC - 125W - IP20 - 2700K - 10133lm - CRI >90	UTOPIA 12		1A4950000.27.00	



Strip LED - 6 m			Not included
Input 24V DC - 79W - IP20 - 3000K - 6322lm - CRI >90	UTOPIA 6	1A4940000.30.00	



Strip LED - 12 m			Not included
Input 24V DC - 125W - IP20 - 3000K - 10538lm - CRI >90	UTOPIA 12	1A4950000.30.00	

CEILING / SOFFITTO



Abstraction, purity, graphic sign.
The projected reduction of Infinito.
The disc appears enigmatic, the symbolic presence of the absence of light.

Astrazione, purezza, segno grafico.
La riduzione puntuale di Infinito.
Il disco appare enigmatico, presenza simbolica dell'assenza della luce.

ASINTOTO

Davide Groppi / 2023

Ceiling / Indirect / Indoor

Material

Metal - Methacrylate


Finish

.27 Gravity Black

Note

Luminaire with black cable (1 m).

Apparecchio con cavo nero (1 m).



ASINTOTO

18W

Max 500mA DC

2700K - 1435lm / 3000K - 1478lm

CRI >80

Driver not included

CE IP20

Gravity Black - 2700K


Gravity Black - 3000K

1A4072700.27.20

1A4072700.30.20

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica




Driver LED

220-240V(100-127V) 500mA/20W(15W)/IP20/DALI

1Z0241180.500

Not included




Driver LED

220-240V(100-127V) 500mA/20W(15W)/IP20/PUSH - 1-10V

1Z0240870.500

Not included



Driver LED

220-240V 500mA/20W/IP20/TRIAC/IGBT

1Z0240850.500


Not included

Davide Groppi / 2023

ASINTOTO

Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Circular plasterboard panel 12,5 mm / Botola circolare per cartongesso 12,5 mm

Standard Cut-out 400 x 400 mm - Minimum space for mounting Ø 115 mm

1A4520000.00.00

Not included



Recessed fixing kit for 12.5 mm plasterboard / Kit di fissaggio ad incasso per cartongesso 12,5 mm

Matt White For elettrcal cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm

1X0000300.04.00

Not included

Matt Black For elettrcal cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm

1X0000400.04.00



Ceiling fixing kit / Kit di fissaggio a soffitto


Matt White For elettrcal cables - 1 Piece

1X0010300.04.00

Not included

Matt Black For elettrcal cables - 1 Piece

1X0010400.04.00



Wall back plate / Piastra parete

Matt White For mounting on brick masonry walls

1X0050300.01.00

Not included

Other accessories / Altri accessori





Magnetic weight / Peso magnetico

For sloped installation

1A4710000.00.00

Not included






A white disc, the perfect representation of diffused light.
It can be mounted on the wall or ceiling, with modular brightness.

Un disco bianco, rappresentazione perfetta della luce diffusa.
È applicabile a soffitto o a parete ed è modulabile in tutte le intensità.

AURORA

Davide Groppi / 2023

Ceiling-Wall / Diffuse / Indoor				
Material	Metal - PMMA			
Finish	.03 Matt White	.04 Matt Black	.32 Copper Oxide	
Note	White wall and ceiling mount luminaire.			
	Apparecchio con attacco a parete e soffitto bianco.			



AURORA

28W
110-240V - 50/60Hz
3000K - 2700lm
CRI 80
Driver included
Driver integrated
DALI - PUSH - 1-10V

CE IP20

Matt White - 3000K - DALI - PUSH - 1-10V
Matt Black - 3000K - DALI - PUSH - 1-10V
Copper Oxide - 3000K - DALI - PUSH - 1-10V

1A4010300.30.07
1A4010400.30.07
1A4013200.30.07



DOT PL 51

Omar Carraglia - Davide Groppi / 2015




A tool to light.

A luminaire designed for use with state-of-the-art LED bulbs to offer superior performance and a wide range of light beams.

Elemento di luce.

Un apparecchio illuminante progettato per utilizzare lampadine a LED in grado di fornire prestazioni superiori ed un'ampia gamma di fasci luminosi.



DOT PL 51

Max 10W - GU10

100-240V - 50/60Hz

Bulb not included

ON/OFF

CE IP20




Matt White - ON/OFF

1A3800300.00.00

Optional accessories / Accessori opzionali

Bulbs / Lampadine

	LED SORAA - GU10 - MR16	Not included
	230V - 7,5W - 10° - 2700K - 390lm - CRI 95 - Energy Efficiency G - Dimmable	1Y1580210
	LED SORAA - GU10 - MR16	Not included
	230V - 7,5W - 10° - 3000K - 410lm - CRI 95 - Energy Efficiency G - Dimmable	1Y1580010
	LED - GU10 - PAR16	Not included
	220-240V - 5,5W - 25° - 3000K - 375lm - CRI 97 - Energy Efficiency G - Dimmable	1Y0330500

	Darklight	Not included	
	MR16	LED SORAA - GU10	51580040
	36° beam filter / Filtro fascio 36°	Not included	
	MR16	LED SORAA - GU10	51580030
	25° beam filter / Filtro fascio 25°	Not included	
	MR16	LED SORAA - GU10	51580020

HAKO PL

Alberto Zattin / 2000





A tool to light.


The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

	HAKO PL Max 60W - R7s 100-240V - 50/60Hz Bulb not included ON/OFF CE IP20 0,5 m	Matt White - ON/OFF 1A3460300.00.00
	HAKO PL LED 12,5W 220-230V - 50/60Hz 2700K - 593lm / 3000K - 638lm CRI >90 TRIAC/IGBT CE IP20	Matt White - 2700K - TRIAC/IGBT Matt White - 3000K - TRIAC/IGBT 1A3160300.27.02 1A3160300.30.02






The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

Ceiling / Direct / Indoor		
Material	Metal	
Finish	.03 Matt White .34 Matt White/Black Bicolor	
Note	Adjustable luminaire.	
	Apparecchio orientabile.	



MINI PL 51

Max 10W - GU10

100-240V - 50/60Hz

Bulb not included

ON/OFF

CE IP20

Matt White - ON/OFF

Matt White/Black Bicolor - ON/OFF

1A3450300.00.00

1A3453400.00.00

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - GU10 - PAR16	Not included
220-240V - 5,5W - 25° - 3000K - 375lm - CRI 97 - Energy Efficiency G - Dimmable	1Y0330500




LED SORAA - GU10 - MR16	Not included
230V - 7,5W - 10° - 3000K - 410lm - CRI 95 - Energy Efficiency G - Dimmable	1Y1580010




LED SORAA - GU10 - MR16	Not included
230V - 7,5W - 10° - 2700K - 390lm - CRI 95 - Energy Efficiency G - Dimmable	1Y1580210

Optional accessories / Accessori opzionali


Other accessories / Altri accessori



Darklight	Not included	
MR16	LED SORAA - GU10	51580040



25° beam filter / Filtro fascio 25°	Not included	
MR16	LED SORAA - GU10	51580020



36° beam filter / Filtro fascio 36°	Not included	
MR16	LED SORAA - GU10	51580030




NULLA PL

Davide Groppi / 2014

The marvellous Nulla project, also available in a surface mounted version.

Il meraviglioso progetto Nulla utilizzabile anche in versione non incassata.



NULLA PL
8,5W
100-240V - 50/60Hz
2700K - 460lm / 3000K - 495lm
CRI >90
Driver included
Driver integrated
ON/OFF
CE IP20

Matt White - 2700K - ON/OFF
Matt White - 3000K - ON/OFF

1A2500300.27.00
1A2500300.30.00





A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

Ceiling / Direct / Indoor		
Material	Metal	
Finish	.03 Matt White .34 Matt White/Black Bicolor	
Note	Adjustable luminaire.	
	Apparecchio orientabile.	



PUNTO PL

Max 21W

100-240V - 50/60Hz

Driver included

Driver integrated

PUSH

LED Module not included

CE IP20

Matt White - PUSH


1A1110300.00.04

Matt White/Black Bicolor - PUSH


1A1113400.00.04

Optional accessories / Accessori opzionali


LED modules / Moduli LED



DG111 LED Module / Modulo LED DG111		Not included
16,7W - 15° - 500mA DC - 2700K - 1648lm - CRI 90 - Energy Efficiency F - Dimmable	1A4700000.27.20	
16,7W - 15° - 500mA DC - 3000K - 1682lm - CRI 90 - Energy Efficiency F - Dimmable	1A4700000.30.20	



DG111 LED Module / Modulo LED DG111		Not included
16,7W - 22° - 500mA DC - 2700K - 1859lm - CRI 90 - Energy Efficiency F - Dimmable	1A3890000.27.20	
16,7W - 22° - 500mA DC - 3000K - 1945lm - CRI 90 - Energy Efficiency F - Dimmable	1A3890000.30.20	



DG111 LED Module / Modulo LED DG111		Not included
16,7W - 36° - 500mA DC - 2700K - 1808lm - CRI 90 - Energy Efficiency F - Dimmable	1A3900000.27.20	
16,7W - 36° - 500mA DC - 3000K - 1890lm - CRI 90 - Energy Efficiency F - Dimmable	1A3900000.30.20	

Optional accessories / Accessori opzionali

Other accessories / Altri accessori



Accessory holder + Soft filter + Honeycomb louvre / Porta accessori + Filtro soft + Frangiluce nido d'ape	Not included
Matt Black	1X0070400.04.00



Accessory holder + Elliptical filter / Porta accessori + Filtro ellittico	Not included
Matt Black	1X0070400.05.00



Blue filter / Filtro blu	Not included
Standard	1X0070000.06.00



Red filter / Filtro rosso	Not included
Standard	1X0070000.07.00



Yellow filter / Filtro giallo	Not included
Standard	1X0070000.08.00




A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.


Ceiling / Direct / Indoor		
Material	Metal	
Finish	.03 Matt White .34 Matt White/Black Bicolor	
Note	Adjustable luminaire.	
	Apparecchio orientabile.	




PUNTO 2 PL		
Max 2x21W		
100-240V - 50/60Hz		
Driver included	Matt White - PUSH	1A1120300.00.04
Driver integrated	Matt White/Black Bicolor - PUSH	1A1123400.00.04
PUSH		
LED Modules not included		
C E IP20		

Optional accessories / Accessori opzionali


LED modules / Moduli LED



DG111 LED Module / Modulo LED DG111		Not included
16,7W - 15° - 500mA DC - 2700K - 1648lm - CRI 90 - Energy Efficiency F - Dimmable	1A4700000.27.20	
16,7W - 15° - 500mA DC - 3000K - 1682lm - CRI 90 - Energy Efficiency F - Dimmable	1A4700000.30.20	



DG111 LED Module / Modulo LED DG111		Not included
16,7W - 22° - 500mA DC - 2700K - 1859lm - CRI 90 - Energy Efficiency F - Dimmable	1A3890000.27.20	
16,7W - 22° - 500mA DC - 3000K - 1945lm - CRI 90 - Energy Efficiency F - Dimmable	1A3890000.30.20	



DG111 LED Module / Modulo LED DG111		Not included
16,7W - 36° - 500mA DC - 2700K - 1808lm - CRI 90 - Energy Efficiency F - Dimmable	1A3900000.27.20	
16,7W - 36° - 500mA DC - 3000K - 1890lm - CRI 90 - Energy Efficiency F - Dimmable	1A3900000.30.20	

Optional accessories / Accessori opzionali

Other accessories / Altri accessori



Accessory holder + Soft filter + Honeycomb louvre / Porta accessori + Filtro soft + Frangiluce nido d'ape		Not included
Matt Black	1X0070400.04.00	



Accessory holder + Elliptical filter / Porta accessori + Filtro ellittico		Not included
Matt Black	1X0070400.05.00	



Blue filter / Filtro blu		Not included
Standard	1X0070000.06.00	



Red filter / Filtro rosso		Not included
Standard	1X0070000.07.00	



Yellow filter / Filtro giallo		Not included
Standard	1X0070000.08.00	



SANMARTINO

Omar Carraglia - Davide Groppi / 2014

Where did the chandelier go?

A work about absence. About something missing. As if by removing the chandelier, its memory stays, but with a modern and sensual light.

Dov'è finito il lampadario?

Un progetto sull'assenza, su qualcosa che manca. Come se togliendo il lampadario, rimanga la sua memoria, ma con una luce moderna e sensuale.

SANMARTINO

Omar Carraglia - Davide Groppi / 2014

Ceiling / Direct / Indoor
Material Metal
Finish .03 Matt White .15 Natural Brass



SANMARTINO

8,5W
100-240V - 50/60Hz
3000K - 375lm
CRI >90
Driver included
Driver integrated
ON/OFF
CE IP20

Matt White - 3000K - ON/OFF
Natural Brass - 3000K - ON/OFF

1A3420300.30.00
1A3421500.30.00






A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

Ceiling / Direct / Indoor	
Material	Metal - Polycarbonate
Finish	.03 Matt White
Note	Luminaire with Extradark comfort system.
Apparecchio dotato di Extradark comfort system.	




SPY PL
39W
110-240V - 50/60Hz
3000K - 4292lm
CRI >80
UGR <19
Driver included
Driver integrated
DALI
CE IP20

Matt White - 3000K - DALI

1A2930300.30.01





TRICK TRACK

/ 2016

A simple, graphic solution.
Bringing accent lighting with an external wiring system.

Una soluzione semplice e grafica.
Per portare luce d'accento con un sistema fuori traccia.


TRICK TRACK

/ 2016

TRICK TRACK

/ 2016

Wall-Ceiling / Direct / Indoor			
Material	Metal		
Finish	.03 Matt White	.04	Matt Black
Note	Adjustable luminaire - White finish luminaire with white cable and black finish luminaire with black cable (2 m) - Maximum 20 connectable luminaires.		
	Apparecchio orientabile con cavo bianco per la finitura bianca e cavo nero per la finitura nera (2 m) - Collegabili max 20 apparecchi.		

	TRICK TRACK		
	Max 10W - GU10		
	100-240V - 50/60Hz		
	Bulb not included		
	ON/OFF		
	CE IP20		
		Matt White - ON/OFF	1A3430300.00.00
		Matt Black - ON/OFF	1A3430400.00.00

Optional accessories / Accessori opzionali

Installation kit / Kit installazione




	Wall and ceiling rose / Rosone parete e soffitto	Not included
	Matt White	1A3440300.00.00
	Matt Black	1A3440400.00.00

Bulbs / Lampadine

	LED SORAA - GU10 - MR16	Not included
	230V - 7,5W - 10° - 2700K - 390lm - CRI 95 - Energy Efficiency G - Dimmable	1Y1580210
	LED SORAA - GU10 - MR16	Not included
	230V - 7,5W - 10° - 3000K - 410lm - CRI 95 - Energy Efficiency G - Dimmable	1Y1580010
	LED - GU10 - PAR16	Not included
	220-240V - 5,5W - 25° - 3000K - 375lm - CRI 97 - Energy Efficiency G - Dimmable	1Y0330500

Optional accessories / Accessori opzionali

Other accessories / Altri accessori

	Darklight	Not included
	MR16	LED SORAA - GU10 51580040
	36° beam filter / Filtro fascio 36°	Not included
	MR16	LED SORAA - GU10 51580030
	25° beam filter / Filtro fascio 25°	Not included
	MR16	LED SORAA - GU10 51580020

RECESSED / INCASSO



A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.


Outdoor-Recessed / Direct / Indoor		
Material	Glass - Metal	
Finish	.03 Matt White	.04 Matt Black
Note	For installation: plasterboard cut-out ø 50 mm - Minimum space for mounting 150 mm.	
<i>Per installazione: dimensioni taglio cartongesso ø 50 mm - Spazio minimo per incasso 150 mm.</i>		



BUCO 58 - 40°		
7W		
24V DC	Matt White - 2700K	1A1490300.27.20
2700K - 495lm / 3000K - 546lm	Matt White - 3000K	1A1490300.30.20
Beam 40°	Matt Black - 2700K	1A1490400.27.20
CRI >90	Matt Black - 3000K	1A1490400.30.20
Driver not included		
CE IP67		

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica



Driver LED		Not included
110-240V	24V/25W/IP67/ON/OFF	1Z1120620

Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Installation box / Cassaforma installazione		Not included
Cut-out Ø 53 mm - Minimum space for mounting 150 mm		1A1500000.00.00



Driver connector IP68 / Connettore driver IP68		Not included
1 Piece		1A1660000.00.00





BUCO R

/ 2006

A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.


Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

Recessed / Direct / Indoor	
Material	Metal
Finish	.03 Matt White
Note	Adjustable luminaire - For installation: plasterboard cut-out ø 90 mm - Minimum space for mounting 85 mm.
	Apparecchio orientabile - Per installazione: dimensioni taglio cartongesso ø 90 mm - Spazio minimo per incasso 85 mm.

	BUCO R Max 35W - GU5,3 - 12V 12V Bulb not included Driver not included Driver remote ON/OFF CE IP20 1.0 m	Matt White - ON/OFF	1A3720300.00.00
---	---	---------------------	-----------------

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica

	Electronic Transformer 12V / Trasformatore elettronico 12V 230-240V 12V/50W/IP20/TRIAC/IGBT 1Z0240440	Not included
---	---	--------------

Optional accessories / Accessori opzionali

Bulbs / Lampadine

	LED - GU5,3 - MR16 12V - 6,7W - 36° - 3000K - 440lm - CRI 97 - Energy Efficiency G - Dimmable 1Y0330530	Not included
---	---	--------------







DOT R

Omar Carraglia - Davide Groppi / 2015

A tool to light.

A luminaire designed for use with state-of-the-art LED modules to offer superior performance and a wide range of light beams.


Elemento di luce.

Un apparecchio illuminante progettato per utilizzare moduli a LED in grado di fornire prestazioni superiori ed un'ampia gamma di fasci luminosi.

DOT R

Omar Carraglia - Davide Groppi / 2015


Recessed / Direct / Indoor		
Material	Metal	
Finish	.03 Matt White	.04 Matt Black
Note	Adjustable luminaire - For installation: plasterboard cut-out 40 x 40 mm - Minimum space for mounting 85 mm.	
	Apparecchio orientabile - Per installazione: dimensioni taglio cartongesso 40 x 40 mm - Spazio minimo per incasso 85 mm.	



DOT R
13W
Max 350mA DC
2700K / 3000K
CRI 97
Driver not included
CE IP20

Matt White - 2700K
Matt White - 3000K
Matt Black - 2700K
Matt Black - 3000K

1A4770300.27.20
1A4770300.30.20
1A4770400.27.20
1A4770400.30.20



DOT R 51
Max 10W - GU10
100-240V - 50/60Hz
Bulb not included
ON/OFF
CE IP20

Matt White - ON/OFF
Matt Black - ON/OFF


1A3700300.00.00
1A3700400.00.00

Omar Carraglia - Davide Groppi / 2015


DOT R

Compulsory accessories / Accessori obbligatori			
Other accessories / Altri accessori			
	Lens / Lente		Not included
	Beam - 14°	2700K - CRI 97 - 983lm 3000K - CRI 97 - 1038lm	DOT R 1A3090000.00.00
	Beam - 24°	2700K - CRI 97 - 943lm 3000K - CRI 97 - 996lm	DOT R 1A3100000.00.00
	Beam - 36°	2700K - CRI 97 - 955lm 3000K - CRI 97 - 1005lm	DOT R 1A3110000.00.00
	Beam - 50°	2700K - CRI 97 - 965lm 3000K - CRI 97 - 1016lm	DOT R 1A3120000.00.00


Electrical power supply / Alimentazione elettrica



Driver LED		Not included	
220-240V(100-127V)	350mA/18W(15W)/IP20/PUSH - 1-10V	DOT R	1Z0240870.350



Driver LED		Not included	
220-240V(100-127V)	350mA/17W(15W)/IP20/DALI	DOT R	1Z0241180.350



Driver LED		Not included	
220-240V	350mA/17W/IP20/TRIAC/IGBT	DOT R	1Z0240850.350

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - GU10 - PAR16		Not included	
	220-240V - 5,5W - 25° - 3000K - 375lm - CRI 97 - Energy Efficiency G - Dimmable	DOT R 51	1Y0330500




LED SORAA - GU10 - MR16		Not included	
	230V - 7,5W - 10° - 3000K - 410lm - CRI 95 - Energy Efficiency G - Dimmable	DOT R 51	1Y1580010




LED SORAA - GU10 - MR16		Not included	
	230V - 7,5W - 10° - 2700K - 390lm - CRI 95 - Energy Efficiency G - Dimmable	DOT R 51	1Y1580210

Optional accessories / Accessori opzionali


Other accessories / Altri accessori




Accessory holder + Honeycomb louvre / Porta accessori + Frangiluce nido d'ape		Not included
	DOT R	1X0080400.01.00




Elliptical filter / Filtro ellittico		Not included
Standard	DOT R	1X0080000.02.00




Blue filter / Filtro blu		Not included
Standard	DOT R	1X0080000.03.00




Red filter / Filtro rosso		Not included
Standard	DOT R	1X0080000.04.00




Yellow filter / Filtro giallo		Not included
Standard	DOT R	1X0080000.05.00



Darklight		Not included
MR16	DOT R 51	51580040



25° beam filter / Filtro fascio 25°		Not included
MR16	DOT R 51	51580020



36° beam filter / Filtro fascio 36°		Not included
MR16	DOT R 51	51580030





A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

Recessed-Ceiling / Direct / Indoor			
Material	Metal		
Finish	.03 Matt White	.04	Matt Black
Note	Adjustable luminaire.		
	Apparecchio orientabile.		

	MINI 51		
	Max 10W - GU10		
	100-240V - 50/60Hz		
	Bulb not included		
	ON/OFF		
	     1.0 m		
	Matt White - ON/OFF	1A0660300.00.00	
	Matt Black - ON/OFF	1A0660400.00.00	

Compulsory accessories / Accessori obbligatori

Installation kit / Kit installazione

	Plasterboard frame 12,5 mm / Cornice per cartongesso 12,5 mm		Not included
	Matt White	Cut-out 104 x 104 mm - Minimum space for mounting 130 mm	1A3500300.00.00
	Matt Black	Cut-out 104 x 104 mm - Minimum space for mounting 130 mm	1A3500400.00.00




Optional accessories / Accessori opzionali


Bulbs / Lampadine

	LED - GU10 - PAR16		Not included
		220-240V - 5,5W - 25° - 3000K - 375lm - CRI 97 - Energy Efficiency G - Dimmable	1Y0330500
	LED SORAA - GU10 - MR16		Not included
		230V - 7,5W - 10° - 2700K - 390lm - CRI 95 - Energy Efficiency G - Dimmable	1Y1580210
	LED SORAA - GU10 - MR16		Not included
		230V - 7,5W - 10° - 3000K - 410lm - CRI 95 - Energy Efficiency G - Dimmable	1Y1580010

Optional accessories / Accessori opzionali

Other accessories / Altri accessori

	Darklight		Not included
	MR16	LED SORAA - GU10	51580040
	25° beam filter / Filtro fascio 25°		Not included
	MR16	LED SORAA - GU10	51580020
	36° beam filter / Filtro fascio 36°		Not included
	MR16	LED SORAA - GU10	51580030



A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

Recessed-Ceiling / Direct / Indoor		
Material	Metal	
Finish	.03 Matt White .34 Matt White/Black Bicolor	
Note	Adjustable luminaire - For installation: plasterboard cut-out 115 x 105 mm - Minimum space for mounting 130 mm.	
	Apparecchio orientabile - Per installazione: dimensione taglio cartongesso 115 x 105 mm - Spazio minimo per incasso 130 mm.	



MINI BIT 51

Max 10W - GU10

100-240V - 50/60Hz

Bulb not included

ON/OFF

CE IP20 1.0 m

Matt White - ON/OFF

1A0670300.00.00

Matt White/Black Bicolor - ON/OFF

1A0673400.00.00

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - GU10 - PAR16	Not included
220-240V - 5,5W - 25° - 3000K - 375lm - CRI 97 - Energy Efficiency G - Dimmable	1Y0330500




LED SORAA - GU10 - MR16	Not included
230V - 7,5W - 10° - 3000K - 410lm - CRI 95 - Energy Efficiency G - Dimmable	1Y1580010




LED SORAA - GU10 - MR16	Not included
230V - 7,5W - 10° - 2700K - 390lm - CRI 95 - Energy Efficiency G - Dimmable	1Y1580210

Optional accessories / Accessori opzionali


Other accessories / Altri accessori



Darklight	Not included	
MR16	LED SORAA - GU10	51580040



25° beam filter / Filtro fascio 25°	Not included	
MR16	LED SORAA - GU10	51580020



36° beam filter / Filtro fascio 36°	Not included	
MR16	LED SORAA - GU10	51580030

MIRA R

Omar Carraglia / 2015



A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

MIRA R

Omar Carraglia / 2015

Recessed / Direct / Indoor

Material

Metal

Finish

.03

Matt White


.04

Matt Black

Note

Adjustable luminaire - For installation: plasterboard cut-out 40 x 40 mm - Minimum space for mounting 85 mm.

Apparecchio orientabile - Per installazione: dimensioni taglio cartongesso 40 x 40 mm - Spazio minimo per incasso 85 mm.



MIRA R

5,6W

Max 500mA DC

2700K - 327lm / 3000K - 352lm

CRI >90

Driver not included

CE IP20

Matt White - 2700K

Matt White - 3000K

Matt Black - 2700K

Matt Black - 3000K

1A3690300.27.20


1A3690300.30.20

1A3690400.27.20

1A3690400.30.20

Compulsory accessories / Accessori obbligatori


Electrical power supply / Alimentazione elettrica



Driver LED

Not included


220-240V(100-127V)	500mA/20W(15W)/IP20/PUSH - 1-10V	1Z0240870.500
--------------------	----------------------------------	---------------



Driver LED

Not included

220-240V(100-127V)	500mA/20W(15W)/IP20/DALI	1Z0241180.500
--------------------	--------------------------	---------------



Driver LED

Not included

220-240V	500mA/20W/IP20/TRIAC/IGBT	1Z0240850.500
----------	---------------------------	---------------

384

385



NULLA

Davide Groppi / 2010

An extreme expression of subtraction, uniting optics and electronics as an answer to the ultimate challenge: the absence of structural support and the essence of light.

Nulla is a project that represents both the beginning and end of our work on light. It's the beginning, in the sense that we have always been looking for absolute light, one coming from a distance, almost without a source. It's the end in that every time we look at Nulla, we feel as though we can't get it better than that.

Nulla generates light and propagates mystery. Nulla is the most generous of our lamps. Its sole objective is to hide and give all the attention to whatever it is lighting. What we see is only a tiny black hole, as if it were drawn on the ceiling.

A circle in the ceiling hiding a very bright LED and lens to project the light.

XXIII Compasso d'Oro ADI Award, 2014

Un lavoro estremo di sottrazione, che unisce elettronica e l'ottica verso la sfida finale: l'assenza del supporto e l'essenza della luce.

Nulla è un progetto che rappresenta l'inizio e la fine del nostro lavoro sulla luce. L'inizio perché da sempre cerchiamo la luce assoluta, quella che arriva da lontano, quasi senza fonte. La fine perché ogni volta che guardiamo Nulla ci sembra di non potere andare più avanti di così. Nulla genera luce e diffonde mistero. È la più generosa delle nostre lampade, quella che si nasconde al solo scopo di regalare la scena al soggetto illuminato. Ciò che appare è solo un minuscolo buco nero, quasi disegnato.

Un foro nel soffitto, un LED potentissimo e una lente che generano la luce.




Premio XXIII Premio Compasso d'Oro ADI, 2014

Recessed / Direct / Indoor			
Material	Metal		
Finish	.00 Standard		
Note	Luminaire with Extradark comfort system - NULLA and NULLA 18: visible hole ø 18 mm - NULLA 25: visible hole ø 25 mm - NULLA 18 and NULLA 25: luminaire removable for maintenance.		
	Apparecchio dotato di Extradark comfort system - NULLA e NULLA 18: foro visibile ø 18 mm - NULLA 25: foro visibile ø 25 mm - NULLA 18 e NULLA 25: apparecchio estraibile per manutenzione.		





NULLA 25 - BEAM 23°	
9W	
24V DC	
2700K - 304lm / 3000K - 327lm	Standard - 2700K
Beam 23°	Standard - 3000K
CRI >90	
UGR <19	

1A4080000.27.20
1A4080000.30.20




	NULLA - BEAM 23° 14W 24V DC 2700K - 425lm / 3000K - 458lm Beam 23° CRI >90 UGR <19 Driver not included C E IP20/IP65	Standard - 2700K Standard - 3000K	1A4100000.27.20 1A4100000.30.20
	NULLA - BEAM 32° 14W 24V DC 2700K - 538lm / 3000K - 579lm Beam 32° CRI >90 UGR <19 Driver not included C E IP20/IP65	Standard - 2700K Standard - 3000K	1A2110000.27.20 1A2110000.30.20
	NULLA 18 - BEAM 20° 4,5W 24V DC 2700K - 174lm / 3000K - 186lm Beam 20° CRI >90 UGR <19 Driver not included C E IP20	Standard - 2700K Standard - 3000K	1A2010000.27.20 1A2010000.30.20

Compulsory accessories / Accessori obbligatori

Installation kit / Kit installazione






	Plasterboard flange 12,5 mm / Flangia per cartongesso 12,5 mm			Not included
	Matt Black	Cut-out Ø 21 mm - Minimum space for mounting 100 mm - IP65	NULLA	1A2200400.00.00
	Plasterboard flange 12,5 mm / Flangia per cartongesso 12,5 mm			Not included
	Matt Black	Cut-out Ø 22 mm - Minimum space for mounting 190 mm	NULLA 18	1A2210400.00.00
	Plasterboard flange 12,5 mm / Flangia per cartongesso 12,5 mm			Not included
	Matt Black	Cut-out Ø 35 mm - Minimum space for mounting 190 mm	NULLA 25	1A2170400.00.00
	Plasterboard flange 12,5 mm / Flangia per cartongesso 12,5 mm			Not included
	Matt Black	Cut-out Ø 35 mm - Minimum space for mounting 190 mm - IP65	NULLA 25	1A3980400.00.00
	Plasterboard flange (bottom) 12,5 mm / Flangia (da sotto) per cartongesso 12,5 mm			Not included
	Matt Black		NULLA 25	1A4960400.00.00

Electrical power supply / Alimentazione elettrica

	Driver LED			Not included
	220-240V	24V/20W/IP20/TRIAC/IGBT	NULLA / NULLA 18 / NULLA 25	1Z0240850.24
	Driver LED			Not included
	220-240V(100-127V)	24V/16W(15W)/IP20/DALI	NULLA / NULLA 18 / NULLA 25	1Z0241180.24
	Driver LED			Not included
	220-240V(100-127V)	24V/20W(15W)/IP20/PUSH	NULLA / NULLA 18 / NULLA 25	1Z0240870.24

Optional accessories / Accessori opzionali

Installation kit / Kit installazione

	Trapdoor for plasterboard 12,5 mm / Botola per cartongesso 12,5 mm			Not included
	Standard	Cut-out 200 x 200 mm	NULLA	1A3780000.00.00
	Trapdoor for plasterboard 12,5 mm / Botola per cartongesso 12,5 mm			Not included
	Standard	Cut-out 400 x 400 mm	NULLA	1A3790000.00.00
	Masonry Box / Cassaforma per laterizio			Not included
		Dimensions 189 x 445 mm	NULLA 18	1A2390000.00.00
	Concrete box / Cassaforma per cemento armato			Not included
		Dimensions 189 x 445 mm	NULLA 18	1A2240000.00.00
	Masonry Box / Cassaforma per laterizio			Not included
		Dimensions 189 x 445 mm	NULLA 25	1A2380000.00.00
	Concrete box / Cassaforma per cemento armato			Not included
		Dimensions 189 x 445 mm	NULLA 25	1A2230000.00.00





A tool to light.

The luminaire is pure form, a simple container for the light source. Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa. La luce si integra con lo spazio diventando elemento architettonico.

Recessed / Direct / Indoor		
Material	Metal	
Finish	.03 Matt White .04 Matt Black	
Note	Adjustable luminaire.	
	Apparecchio orientabile.	

	PUNTO		
	Max 21W		
	Max 500mA DC		
	Driver included		
	Driver remote		
	PUSH		
	LED Module not included		
 	IP20		
			</

Compulsory accessories / Accessori obbligatori

Installation kit / Kit installazione

	Plasterboard frame 12,5 mm / Cornice per cartongesso 12,5 mm		Not included
	Matt White	Cut-out 133 x 148 mm - Minimum space for mounting 180 mm	1A3510300.00.00
	Matt Black	Cut-out 133 x 148 mm - Minimum space for mounting 180 mm	1A3510400.00.00

Optional accessories / Accessori opzionali

LED modules / Moduli LED

	DG111 LED Module / Modulo LED DG111		Not included
	16,7W - 15° - 500mA DC - 2700K - 1648lm - CRI 90 - Energy Efficiency F - Dimmable	1A4700000.27.20	
	16,7W - 15° - 500mA DC - 3000K - 1682lm - CRI 90 - Energy Efficiency F - Dimmable	1A4700000.30.20	
	DG111 LED Module / Modulo LED DG111		Not included
	16,7W - 22° - 500mA DC - 2700K - 1859lm - CRI 90 - Energy Efficiency F - Dimmable	1A3890000.27.20	
	16,7W - 22° - 500mA DC - 3000K - 1945lm - CRI 90 - Energy Efficiency F - Dimmable	1A3890000.30.20	

Optional accessories / Accessori opzionali

LED modules / Moduli LED

	DG111 LED Module / Modulo LED DG111		Not included
	16,7W - 36° - 500mA DC - 2700K - 1808lm - CRI 90 - Energy Efficiency F - Dimmable	1A3900000.27.20	
	16,7W - 36° - 500mA DC - 3000K - 1890lm - CRI 90 - Energy Efficiency F - Dimmable	1A3900000.30.20	

Other accessories / Altri accessori

	Accessory holder + Soft filter + Honeycomb louvre / Porta accessori + Filtro soft + Frangiluce nido d'ape		Not included
	Matt Black	1X0070400.04.00	
	Accessory holder + Elliptical filter / Porta accessori + Filtro ellittico		Not included
	Matt Black	1X0070400.05.00	
	Blue filter / Filtro blu		Not included
	Standard	1X0070000.06.00	
	Red filter / Filtro rosso		Not included
	Standard	1X0070000.07.00	
	Yellow filter / Filtro giallo		Not included
	Standard	1X0070000.08.00	



A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

Recessed / Diffuse / Indoor

MaterialMetal

Finish.03 Matt White

NoteFor installation: plasterboard cut-out 161 x 138 mm - Minimum space for mounting 70 mm.

Per installazione: dimensioni taglio cartongesso 161 x 138 mm - Spazio minimo per incasso 70 mm.



PURA


6W
110-240V - 50/60Hz
3000K - 445lm
CRI >80
Driver included
Driver integrated
ON/OFF
CE IP20

Matt White - 3000K - ON/OFF

1A3520300.30.00

Compulsory accessories / Accessori obbligatori

Installation kit / Kit installazione




Installation box / Cassaforma installazione

Not included

Plasterboard cut-out 161 x 138 mm -
Minimum space for mounting 70 mm

1A3530000.00.00





A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.


Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

Recessed / Diffuse / Indoor	
Material	Metal
Finish	.03 Matt White
Note	For installation: plasterboard cut-out 40 x 60 mm - Minimum space for mounting 65 mm.
Per installazione: dimensioni taglio cartongesso 40 x 60 mm - Spazio minimo per incasso 65 mm.	

	QUAD	
	2W	
	Max 500mA DC	
	2700K - 128lm / 3000K - 133lm	
	CRI >90	
Driver not included		
CE IP44		
Matt White - 2700K		1A1510300.27.20
Matt White - 3000K		1A1510300.30.20

Compulsory accessories / Accessori obbligatori


Electrical power supply / Alimentazione elettrica



Driver LED		Not included
220-240V(110-127V)	500mA/24W(15W)/IP68/ON/OFF	1Z0241170

Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Installation box / Cassaforma installazione		Not included
Plasterboard cut-out 40 x 60 mm - Minimum space for mounting 65 mm		1A1520000.00.00



SYSTEMS / SISTEMI



ENDLESS

Davide Groppi / 2018

Absolute freedom, absolute spatiality, absolute creativity.
An adhesive tape that conducts electricity can be placed anywhere on walls and ceilings to power our lighting projects.

Endless is the system created and patented by our Team in order to transport electric energy in a digital and graphic manner.

It's the idea of considering walls and ceilings like electronic circuits, where luminaires can be done fixed freely and easily. This system comes with various accessories to provide and manage the flow of electricity.

Libertà assoluta, spazialità assoluta, creatività assoluta.


Un nastro conduttore e adesivo che può essere disposto a piacimento su pareti e soffitti per alimentare i nostri modelli.

Endless è il sistema ideato e brevettato dal nostro Team per portare "differenza di potenziale" dove si desidera in modo grafico e digitale.


È l'idea di considerare le pareti e i soffitti come circuiti elettronici per posizionare gli apparecchi illuminanti con la massima libertà. Il sistema è dotato di vari accessori di alimentazione e derivazione.

ENDLESS


Remote power supply kit
for Endless ON/OFF
system




Wall and ceiling rose kit
for Endless ON/OFF
system




Power supply kit with plug
for Endless ON/OFF
system




Remote power supply kit
for Endless dimmable
system




Wall and ceiling rose kit
for Endless dimmable
system



Power supply kit with plug
for Endless dimmable
system



Systems / Diffuse-Direct-Indirect / Indoor				
Material	Metal			
Finish	.03 Matt White	.04 Matt Black	.08 Brushed Brass	.26 Total Black
Note	Conductive strip that can be applied to walls, ceilings and windows - Possibility of connecting multiple devices simultaneously - Maximum absorption 4A.			
	Nastro conduttore applicabile a pareti, soffitti e vetrate - Possibilità di collegare più apparecchi contemporaneamente - Assorbimento max 4A.			




MIRA ENDLESS

7,5W
48V DC
2700K - 327lm / 3000K - 352lm
CRI >90
Driver not included
ENDLESS

Matt White - 2700K - ENDLESS
Matt White - 3000K - ENDLESS
Matt Black - 2700K - ENDLESS
Matt Black - 3000K - ENDLESS

1A2280300.27.40
1A2280300.30.40
1A2280400.27.40
1A2280400.30.40




MIRA ENDLESS CASAMBI

8,5W
48V DC
2700K - 327lm / 3000K - 352lm
CRI >90
Driver not included
ENDLESS - CASAMBI

Matt White - 2700K - ENDLESS - CASAMBI
Matt White - 3000K - ENDLESS - CASAMBI
Matt Black - 2700K - ENDLESS - CASAMBI
Matt Black - 3000K - ENDLESS - CASAMBI

1A2280300.27.41
1A2280300.30.41
1A2280400.27.41
1A2280400.30.41




DOT P ENDLESS

13W
48V DC
2700K / 3000K
CRI 97
Driver not included
ENDLESS

Matt White - 2700K - ENDLESS
Matt White - 3000K - ENDLESS
Matt Black - 2700K - ENDLESS
Matt Black - 3000K - ENDLESS

1A2340300.27.40
1A2340300.30.40
1A2340400.27.40
1A2340400.30.40




DOT P ENDLESS CASAMBI

15,5W
48V DC
2700K / 3000K
Driver not included
ENDLESS - CASAMBI

Matt White - 2700K - ENDLESS - CASAMBI
Matt White - 3000K - ENDLESS - CASAMBI
Matt Black - 2700K - ENDLESS - CASAMBI
Matt Black - 3000K - ENDLESS - CASAMBI

1A2340300.27.41
1A2340300.30.41
1A2340400.27.41
1A2340400.30.41




SPOT ENDLESS

Max 13W
48V DC
Driver not included
ENDLESS
LED Module not included

Matt White - ENDLESS
Matt Black - ENDLESS

1A1080300.00.40
1A1080400.00.40




SPOT ENDLESS CASAMBI

Max 15,5W
48V DC
Driver not included
ENDLESS - CASAMBI
LED Module not included

Matt White - ENDLESS - CASAMBI
Matt Black - ENDLESS - CASAMBI

1A1080300.00.41
1A1080400.00.41



REFLEX

23W
48V DC
2700K - 2158lm / 3000K - 2320lm
CRI >90
Driver not included

Matt Black - 2700K
Matt Black - 3000K


1A0850400.27.20
1A0850400.30.20



MISS ENDLESS

6,3W
48V DC
2700K - 290lm / 3000K - 310lm
CRI >90
Driver not included
ENDLESS

Matt White - 2700K - ENDLESS	1A2960300.27.40
Matt White - 3000K - ENDLESS	1A2960300.30.40
Matt Black - 2700K - ENDLESS	1A2960400.27.40
Matt Black - 3000K - ENDLESS	1A2960400.30.40
Brushed Brass - 2700K - ENDLESS	1A2960800.27.40
Brushed Brass - 3000K - ENDLESS	1A2960800.30.40
Total Black - 2700K - ENDLESS	1A2962600.27.40
Total Black - 3000K - ENDLESS	1A2962600.30.40




CATHODE ENDLESS

6,3W
48V DC
2700K - 264lm / 3000K - 284lm
CRI >90
Driver not included
ENDLESS

Matt White - 2700K - ENDLESS	1A2980300.27.40
Matt White - 3000K - ENDLESS	1A2980300.30.40
Brushed Brass - 2700K - ENDLESS	1A2980800.27.40
Brushed Brass - 3000K - ENDLESS	1A2980800.30.40

Compulsory accessories / Accessori obbligatori

Installation kit / Kit installazione



Strip Endless - 5m		Not included
Matt White	Output 48V - Max 150W - Max 4A	1A3470300.00.00
Matt Black	Output 48V - Max 150W - Max 4A	1A3470400.00.00

Strip Endless - 10m		Not included
Matt White	Output 48V - Max 150W - Max 4A	1A0050300.00.00
Matt Black	Output 48V - Max 150W - Max 4A	1A0050400.00.00

Fixing rough walls kit / Kit fissaggio pareti ruvide		Not included
Lenght 2,5m		1A0370000.00.00

Terminal box / Box morsetti		Not included
Matt White	2 Terminals included	1A3480300.00.00
Matt Black	2 Terminals included	1A3480400.00.00

Power base / Base alimentazione		Not included
Matt White		1A0030300.00.00
Matt Black		1A0030400.00.00

Terminals / Morsetti		Not included
2 Pieces		1A3490000.00.00

Compulsory accessories / Accessori obbligatori

LED modules / Moduli LED



DG111 LED Module / Modulo LED DG111			Not included
	11,7W - 15° - 350mA DC - 2700K - 1336lm - CRI 90 - Energy Efficiency F - Dimmable	SPOT ENDLESS	1A4700000.27.20
	11,7W - 15° - 350mA DC - 3000K - 1364lm - CRI 90 - Energy Efficiency F - Dimmable		1A4700000.30.20



DG111 LED Module / Modulo LED DG111			Not included
	11,7W - 22° - 350mA DC - 2700K - 1266lm - CRI 90 - Energy Efficiency F - Dimmable	SPOT ENDLESS	1A3900000.27.20
	11,7W - 22° - 350mA DC - 3000K - 1323lm - CRI 90 - Energy Efficiency F - Dimmable		1A3900000.30.20



DG111 LED Module / Modulo LED DG111			Not included
	11,7W - 36° - 350mA DC - 3000K - 1578lm - CRI 90 - Energy Efficiency F - Dimmable	SPOT ENDLESS	1A3890000.30.20
	11,7W - 36° - 350mA DC - 2700K - 1508lm - CRI 90 - Energy Efficiency F - Dimmable		1A3890000.27.20


Other accessories / Altri accessori




Lens / Lente			Not included
Beam - 14°	2700K - CRI 97 - 983lm	DOT P ENDLESS	1A3090000.00.00
	3000K - CRI 97 - 1038lm		
Beam - 24°	2700K - CRI 97 - 943lm	DOT P ENDLESS	1A3100000.00.00
	3000K - CRI 97 - 996lm		
Beam - 36°	2700K - CRI 97 - 955lm	DOT P ENDLESS	1A3110000.00.00
	3000K - CRI 97 - 1005lm		
Beam - 50°	2700K - CRI 97 - 965lm	DOT P ENDLESS	1A3120000.00.00
	3000K - CRI 97 - 1016lm		

Compulsory accessories / Accessori obbligatori


Electrical power supply for ENDLESS ON/OFF system and CASAMBI / Alimentazione elettrica per sistema ENDLESS ON/OFF e CASAMBI




Power supply kit with plug / Kit alimentazione con spina			Not included
Matt White	Input 100-240V - 50/60Hz - Output 48V - 60W - IP20 - ON/OFF		1A1330300.00.00
Matt Black	Input 100-240V - 50/60Hz - Output 48V - 60W - IP20 - ON/OFF		1A1330400.00.00



Wall/ceiling power supply kit / Kit alimentazione parete/soffitto/remoto			Not included
Matt White	Input 100-240V - 50/60Hz - Output 48V - 60W - IP20 - ON/OFF		1A2450300.00.00
Matt Black	Input 100-240V - 50/60Hz - Output 48V - 60W - IP20 - ON/OFF		1A2450400.00.00




Power supply kit with plug / Kit alimentazione con spina			Not included
Matt White	Input 100-240V - 50/60Hz - Output 48V - 150W - IP20 - ON/OFF		1A0260300.00.00
Matt Black	Input 100-240V - 50/60Hz - Output 48V - 150W - IP20 - ON/OFF		1A0260400.00.00




Wall/ceiling power supply kit / Kit alimentazione parete/soffitto/remoto			Not included
Matt White	Input 100-240V - 50/60Hz - Output 48V - 150W - IP20 - ON/OFF		1A1020300.00.00
Matt Black	Input 100-240V - 50/60Hz - Output 48V - 150W - IP20 - ON/OFF		1A1020400.00.00

Electrical power supply for ENDLESS dimmable system / Alimentazione elettrica per sistema ENDLESS dimmerabile




Power supply kit with plug / Kit alimentazione con spina			Not included
Matt White	Input 100-240V - 50/60Hz - Output 48V - 60W - IP20 - Dimmer on board		1A1340300.00.06
Matt Black	Input 100-240V - 50/60Hz - Output 48V - 60W - IP20 - Dimmer on board		1A1340400.00.06




Wall/ceiling power supply kit / Kit alimentazione parete/soffitto			Not included
Matt White	Input 100-240V - 50/60Hz - Output 48V - 60W - IP20 - DALI - PUSH - 1-10V		1A4090300.00.07
Matt Black	Input 100-240V - 50/60Hz - Output 48V - 60W - IP20 - DALI - PUSH - 1-10V		1A4090400.00.07

Compulsory accessories / Accessori obbligatori

Electrical power supply for ENDLESS dimmable system / Alimentazione elettrica per sistema ENDLESS dimmerabile




Power supply kit with plug / Kit alimentazione con spina			Not included
Matt White	Input 100-240V - 50/60Hz - Output 48V - 150W - IP20 - Dimmer on board	1A1800300.00.06	
Matt Black	Input 100-240V - 50/60Hz - Output 48V - 150W - IP20 - Dimmer on board	1A1800400.00.06	




Wall/ceiling power supply kit / Kit alimentazione parete/soffitto			Not included
Matt White	Input 100-240V - 50/60Hz - Output 48V - 150W - IP20 - DALI - PUSH - 1-10V	1A1810300.00.07	
Matt Black	Input 100-240V - 50/60Hz - Output 48V - 150W - IP20 - DALI - PUSH - 1-10V	1A1810400.00.07	


Electrical power supply for ENDLESS remote system / Alimentazione elettrica per sistema ENDLESS remoto



Driver LED			Not included
100-240V	48V/60W/IP67/ON/OFF	1Z1120640	




Driver LED			Not included
100-240V	48V/150W/IP67/1-10V	1Z1120250	




Controller			Not included
Matt Black	DALI - PUSH - 0/1-10V - TRIAC - IP20	1Z2170010	

Optional accessories / Accessori opzionali


Other accessories / Altri accessori



Horizontal directional fins / Alette direzionali			Not included
Matt Black	SPOT ENDLESS	1X0070400.01.00	



Cylindrical screen / Schermo cilindrico			Not included
Matt Black	SPOT ENDLESS	1X0070400.02.00	



Cone 45° / Cono 45°			Not included
Matt Black	SPOT ENDLESS	1X0070400.03.00	



Accessory holder + Soft filter + Honeycomb louvre / Porta accessori + Filtro soft + Frangiluce nido d'ape			Not included
Matt Black	SPOT ENDLESS	1X0070400.04.00	



Accessory holder + Elliptical filter / Porta accessori + Filtro ellittico			Not included
Matt Black	SPOT ENDLESS	1X0070400.05.00	



Blue filter / Filtro blu			Not included
Standard	SPOT ENDLESS	1X0070000.06.00	




Red filter / Filtro rosso			Not included
Standard	SPOT ENDLESS	1X0070000.07.00	




Yellow filter / Filtro giallo			Not included
Standard	SPOT ENDLESS	1X0070000.08.00	

Integrated products with ENDLESS system / Prodotti compatibili con il sistema ENDLESS - Absorption Max 3,125 A		Wattage	Ampere (A)
Power Kit:			
1A133XX00.00.00	Power supply kit with plug - 48V - Not dimmable	60	Max 1,25
1A245XX00.00.00	Wall ceiling rose kit - Remote - 48V - Not dimmable	60	Max 1,25
1A134XX00.00.06	Power supply kit with plug - 48v - Dimmable	60	Max 1,25
1A409XX00.00.07	Wall ceiling rose kit - 48V - DALI - PUSH - 1-10 V Dimmable	60	Max 1,25
1Z1120640	Remote driver - 48V - Not dimmable	60	Max 1,25
1A026XX00.00.00	Power supply kit with plug - 48V - Not dimmable	150	Max 3,125
1A102XX00.00.00	Wall ceiling rose kit - Remote - 48V - Not dimmable	150	Max 3,125
1A180XX00.00.06	Power supply kit with plug - 48V - Dimmable	150	Max 3,125
1A181XX00.00.07	Wall ceiling rose kit - 48V - DALI - PUSH - 1-10 V Dimmable	150	Max 3,125
1Z1120250	Remote driver - 48V - 1-10 V Dimmable	150	Max 3,125
Elements:			
1A2980300.27.40	CATHODE - Matt White - 2700K - ENDLESS	5,5	0,14
1A2980300.30.40	CATHODE - Matt White - 3000K - ENDLESS	5,5	0,14
1A2980800.27.40	CATHODE - Brushed Brass - 2700K - ENDLESS	5,5	0,14
1A2980800.30.40	CATHODE - Brushed Brass - 3000K - ENDLESS	5,5	0,14
1A2340300.27.40	DOT P - Matt White - 2700K - ENDLESS	13	0,34
1A2340300.30.40	DOT P - Matt White - 3000K - ENDLESS	13	0,34
1A2340400.27.40	DOT P - Matt Black - 2700K - ENDLESS	13	0,34
1A2340400.30.40	DOT P - Matt Black - 3000K - ENDLESS	13	0,34
1A2340300.27.41	DOT P - Matt White - 2700K - ENDLESS - CASAMBI	15,5	0,4
1A2340300.30.41	DOT P - Matt White - 3000K - ENDLESS - CASAMBI	15,5	0,4
1A2340400.27.41	DOT P - Matt Black - 2700K - ENDLESS - CASAMBI	15,5	0,4
1A2340400.30.41	DOT P - Matt Black - 3000K - ENDLESS - CASAMBI	15,5	0,4
1A2280300.27.40	MIRA - Matt White - 2700K - ENDLESS	6	0,16
1A2280300.30.40	MIRA - Matt White - 3000K - ENDLESS	6	0,16
1A2280400.27.40	MIRA - Matt Black - 2700K - ENDLESS	6	0,16
1A2280400.30.40	MIRA - Matt Black - 3000K - ENDLESS	6	0,16
1A2280300.27.41	MIRA - Matt White - 2700K - ENDLESS - CASAMBI	8,5	0,22
1A2280300.30.41	MIRA - Matt White - 3000K - ENDLESS - CASAMBI	8,5	0,22
1A2280400.27.41	MIRA - Matt Black - 2700K - ENDLESS - CASAMBI	8,5	0,22
1A2280400.30.41	MIRA - Matt Black - 3000K - ENDLESS - CASAMBI	8,5	0,22
1A2960300.27.40	MISS - Matt White - 2700K - ENDLESS	5,5	0,14
1A2960300.30.40	MISS - Matt White - 3000K - ENDLESS	5,5	0,14
1A2960400.27.40	MISS - Matt Black - 2700K - ENDLESS	5,5	0,14
1A2960400.30.40	MISS - Matt Black - 3000K - ENDLESS	5,5	0,14
1A2960800.27.40	MISS - Brushed Brass - 2700K - ENDLESS	5,5	0,14
1A2960800.30.40	MISS - Brushed Brass - 3000K - ENDLESS	5,5	0,14
1A2962600.27.40	MISS - Matt Total Black - 2700K - ENDLESS	5,5	0,14
1A2962600.30.40	MISS - Matt Total Black - 3000K - ENDLESS	5,5	0,14


Integrated products with ENDLESS system / Prodotti compatibili con il sistema ENDLESS - Absorption Max 3,125 A		Wattage	Ampere (A)
Elements:			
1A0850400.27.20	REFLEX - Matt Black - 2700K - ENDLESS	23	0,57
1A0850400.30.20	REFLEX - Matt Black - 3000K - ENDLESS	23	0,57
1A1080300.00.40	SPOT - Matt White - ENDLESS	13	0,34
1A1080400.00.40	SPOT - Matt Black - ENDLESS	13	0,34
1A1080300.00.41	SPOT - Matt White - ENDLESS - CASAMBI	15,5	0,4
1A1080400.00.41	SPOT - Matt Black - ENDLESS - CASAMBI	15,5	0,4




MISS ENDLESS - Installation with Endless and remote power supply kit




CATHODE ENDLESS - Installation with Endless and power supply kit with plug



REFLEX - Installation with Endless and power supply kit with plug



REFLEX - Installation with Endless and wall and ceiling rose kit



REFLEX - Installation with Endless and remote power supply kit



FLASH

Davide Groppi / 2017

It is our Infinito model turned around, with the light flowing downwards.
The 9 mm wide stainless steel strip can run perfectly up to 36 metres in length
(standard versions at 6 / 12 / 18 metres in length).

The ideal solution for direct illumination of spaces with very high ceilings.

Its name pays homage to the famous comic book superhero.

Who can run seven times the speed of light.

Flash in its versions of 6 and 12 meters can be integrated with our Endless system.

È la declinazione del nostro modello Infinito, ma con la luce diretta verso il basso.

Il nastro in acciaio inossidabile, largo 9 millimetri, può essere teso perfettamente fino a 36
metri di lunghezza (lampada standard 6 / 12 / 18 metri).


La soluzione ideale per l'illuminazione diretta di spazi con grande altezza.

Il nome è un omaggio al leggendario supereroe dei fumetti.


Famoso perché corre sette volte più veloce della luce...

Flash 6 e Flash 12 sono integrabili con il nostro sistema Endless.


How to order -
FLASH 6



How to order -
FLASH 12




How to order -
FLASH 18



Wall-Systems / Direct / Indoor


Material Metal
Finish .03 Matt White .04 Matt Black

Note LED module 6/12/18 m long available with double emission - LED module 5/10 m long with Tunable White technology available with double emission - Harmonic steel strip 10 mm wide - Can be cut every 96,6 mm - FLASH 6 and FLASH 12: luminaires designed to be powered by ENDLESS system.
Modulo LED lunghezza 6/12/18 m disponibile a doppia emissione - Modulo LED lunghezza 5/10 m con tecnologia Tunable White disponibile a doppia emissione - Nastro in acciaio armonico larghezza 10 mm - Sezionabile ogni 96,6 mm - FLASH 6 e FLASH 12: apparecchi predisposti per essere alimentati dal sistema ENDLESS.




FLASH 6
Length 6000 mm
57W
48V DC
2700K - 6576lm / 3000K - 6708lm
CRI >90
Driver not included
CE IP20 E

Matt White - 2700K	1A2130300.27.20
Matt White - 3000K	1A2130300.30.20
Matt Black - 2700K	1A2130400.27.20
Matt Black - 3000K	1A2130400.30.20



FLASH 12
Length 12000 mm
114W
48V DC
2700K - 13152lm / 3000K - 13416lm
CRI >90
Driver not included
CE IP20 E


Matt White - 2700K	1A2150300.27.20
Matt White - 3000K	1A2150300.30.20
Matt Black - 2700K	1A2150400.27.20
Matt Black - 3000K	1A2150400.30.20




FLASH 18
Length 18000 mm
171W
48V DC
2700K - 19728lm / 3000K - 20124lm
CRI >90
Driver not included
CE IP20

Matt White - 2700K	1A2900300.27.20
Matt White - 3000K	1A2900300.30.20
Matt Black - 2700K	1A2900400.27.20
Matt Black - 3000K	1A2900400.30.20



How to order -
FLASH 6 DE



How to order -
FLASH 12 DE




How to order -
FLASH 18 DE



FLASH 6 DE
Length 6000 mm -
Double output and double switch
114W
48V DC
2700K - Up 6576lm - Down 6576lm /
3000K - Up 6708lm - Down 6708lm
CRI >90
Driver not included
CE IP20

Matt White - 2700K
Matt White - 3000K
Matt Black - 2700K
Matt Black - 3000K


1A1290300.27.20
1A1290300.30.20
1A1290400.27.20
1A1290400.30.20



FLASH 12 DE
Length 12000 mm -
Double output and double switch
228W
48V DC
2700K - Up 13152lm - Down 13152lm /
3000K - Up 13416lm - Down 13416lm
CRI >90
Driver not included
CE IP20

Matt White - 2700K
Matt White - 3000K
Matt Black - 2700K
Matt Black - 3000K

1A1300300.27.20
1A1300300.30.20
1A1300400.27.20
1A1300400.30.20




FLASH 18 DE
Length 18000 mm -
Double output and double switch
342W
48V DC
2700K - Up 19728lm - Down 19728lm /
3000K - Up 20124lm - Down 20124lm
CRI >90
Driver not included
CE IP20


Matt White - 2700K
Matt White - 3000K
Matt Black - 2700K
Matt Black - 3000K

1A1310300.27.20
1A1310300.30.20
1A1310400.27.20
1A1310400.30.20


How to order -
FLASH 5 TW



How to order -
FLASH 10 TW




Note Tunable White describes the variable colour temperature controls from warm white to cool white light.
Tunable White è la regolazione variabile della temperatura di colore dalla tonalità calda a quella fredda.



FLASH 5 TW
Length 5000 mm - Tunable White
50W
24V DC
2700/6500K - 7650lm
CRI >90
Driver not included
CE IP20


Matt White - 2700/6500K	1A4820300.96.20
Matt Black - 2700/6500K	1A4820400.96.20




FLASH 10 TW
Length 10000 mm - Tunable White
100W
24V DC
2700/6500K - 15300lm
CRI >90
Driver not included
CE IP20

Matt White - 2700/6500K	1A4830300.96.20
Matt Black - 2700/6500K	1A4830400.96.20


How to order -
FLASH 5 DE TW



How to order -
FLASH 10 DE TW




Note Tunable White describes the variable colour temperature controls from warm white to cool white light.
Tunable White è la regolazione variabile della temperatura di colore dalla tonalità calda a quella fredda.



FLASH 5 DE TW
Length 5000 mm -
Double output - Tunable White
100W
24V DC
2700/6500K - 15300lm
CRI >90
Driver not included
CE IP20

Matt White - 2700/6500K	1A4840300.96.20
Matt Black - 2700/6500K	1A4840400.96.20



FLASH 10 DE TW
Length 10000 mm -
Double output - Tunable White
200W
24V DC
2700/6500K - 30600lm
CRI >90
Driver not included
CE IP20

Matt White - 2700/6500K	1A4850300.96.20
Matt Black - 2700/6500K	1A4850400.96.20


Compulsory accessories / Accessori obbligatori

Installation kit / Kit installazione




Spacer / Distanziale				Not included
Matt White	For power supply kit with plug	FLASH 6 / FLASH 12	1A4930300.00.00	
Matt Black	For power supply kit with plug	FLASH 6 / FLASH 12	1A4930400.00.00	


Electrical power supply / Alimentazione elettrica




Power supply kit with plug / Kit alimentazione con spina				Not included
Matt White	Input 100-240V - 50/60Hz - Output 48V - Max 57W - IP20	FLASH 6	1X0060300.01.06	
Matt Black	Input 100-240V - 50/60Hz - Output 48V - Max 57W - IP20	FLASH 6	1X0060400.01.06	




Power supply kit with plug / Kit alimentazione con spina				Not included
Matt White	Input 100-240V - 50/60Hz - Output 48V - Max 114W - IP20	FLASH 12	1X0060300.02.06	
Matt Black	Input 100-240V - 50/60Hz - Output 48V - Max 114W - IP20	FLASH 12	1X0060400.02.06	




Driver LED				Not included
100-240V	48V/80W/IP67/1-10V	FLASH 6 / FLASH 6 DE / FLASH 5 TW / FLASH 5 DE TW	1Z1120400	




Driver LED				Not included
100-240V	48V/150W/IP67/1-10V	FLASH 12 / FLASH 12 DE / FLASH 10 TW / FLASH 10 DE TW	1Z1120250	



Driver LED				Not included
100-240V	48V/240W/IP67/1-10V	FLASH 18 / FLASH 18 DE	1Z1120390	




Controller				Not included
Matt Black	DALI - PUSH - 0/1-10V - TRIAC - IP20	FLASH 6 / FLASH 12 / FLASH 18 / FLASH 6 DE / FLASH 12 DE / FLASH 18 DE	1Z2170010	




Controller Casambi - Tunable White				Not included
		FLASH 5 TW / FLASH 10 TW / FLASH 5 DE TW / FLASH 10 DE TW	1Z0830880	

Optional accessories / Accessori opzionali


Installation kit / Kit installazione




Ceiling connection kit / Kit attacco soffitto		Not included
Matt Black	1A0080400.00.00	



Kit wall connection vertical sloped 45° / Kit attacco parete per inclinazione verticale 45°		Not included
Matt Black	1A0120400.00.00	




Kit wall connection sloped right 75° / Kit attacco parete per inclinazione 75° destro		Not included
Matt Black	1A0340400.00.00	




Kit wall connection sloped left 75° / Kit attacco parete per inclinazione 75° sinistro		Not included
Matt Black	1A0350400.00.00	




Swallows / Rondini		Not included
Matt Black	1A0800400.00.00	




Remote power supply kit




Power supply kit with plug




1A0080400.00.00 - Ceiling connection kit




1A0080400.00.00 - Example of installation with ceiling connection kit



Example of installation with max rotation 30°



1A0120400.00.00 - Kit wall connection vertical sloped 45°



1A0340400.00.00 - 1A0350400.00.00 - Kit wall connection sloped 75°



INFINITO

Davide Groppi / 2016

A spatial concept, it is continuous light.

An ultra-thin strip of special stainless steel just 18 mm wide “cuts” the space to produce indirect light. Infinito can be adapted to various situations, stretched from wall to wall or ceiling to floor. It comes in strips up to 36 metres in length (standard versions at 6 / 12 / 18 metres in length). Infinito breaks down the luminaire, turning it into something else, leaving only a trace, a line and then not even that, just light.

This project pays homage to the art of Lucio Fontana and his spatial concepts. The graphic force of this system is surprising. It can be integrated into space, but at the same time it becomes part of that space. Infinito: essence and absence.

Infinito in its versions of 6 and 12 meters can be integrated with our Endless system.

Archiproducts Design Award 2017
People's Choice AZ Award 2017


È un concetto spaziale, è luce continua.

Un nastro sottilissimo, in un particolare acciaio inossidabile e di soli 18 millimetri di larghezza, taglia lo spazio e produce luce indiretta. È possibile adattare, tendere e orientare Infinito da parete a parete, da soffitto a pavimento, fino a 36 metri di lunghezza (lampada standard 6 / 12 / 18 metri). Infinito smaterializza l'oggetto lampada, trasformandolo in qualcos'altro, lasciandone solo una traccia, una riga e poi nemmeno più quella, solo la luce. È un omaggio all'arte di Lucio Fontana e ai suoi concetti spaziali. La forza grafica di questo sistema è sorprendente, per la sua capacità di essere integrato e nello stesso tempo presente nello spazio. Infinito, essenza e assenza.


Infinito 6 e Infinito 12 sono integrabili con il nostro sistema Endless.

Archiproducts Design Award 2017
People's Choice AZ Award 2017


How to order - INFINITO 6



How to order - INFINITO 12



How to order - INFINITO 18




Wall-Systems / Indirect / Indoor


Material	Metal
Finish	.03 Matt White .04 Matt Black

Note LED module 6/12/18 m long - LED module 5/10 m long with Tunable White technology - Harmonic steel strip 19 mm wide - Can be cut every 96,6 mm - INFINITO 6 and INFINITO 12: luminaires designed to be powered by ENDLESS system.


Modulo LED lunghezza 6/12/18 m - Modulo LED lunghezza 5/10 m con tecnologia Tunable White - Nastro in acciaio armonico larghezza 19 mm - Sezionabile ogni 96,6 mm - INFINITO 6 e INFINITO 12: apparecchi predisposti per essere alimentati dal sistema ENDLESS.



INFINITO 6 Length 6000 mm 57W 48V DC 2700K - 6576lm / 3000K - 6708lm CRI >90 Driver not included CE IP20 ENEC	Matt White - 2700K Matt White - 3000K Matt Black - 2700K Matt Black - 3000K	1A2250300.27.20 1A2250300.30.20 1A2250400.27.20 1A2250400.30.20
---	--	--




INFINITO 12 Length 12000 mm 114W 48V DC 2700K - 13152lm / 3000K - 13416lm CRI >90 Driver not included CE IP20 ENEC	Matt White - 2700K Matt White - 3000K Matt Black - 2700K Matt Black - 3000K	1A2260300.27.20 1A2260300.30.20 1A2260400.27.20 1A2260400.30.20
--	--	--




INFINITO 18 Length 18000 mm 171W 48V DC 2700K - 19728lm / 3000K - 20124lm CRI >90 Driver not included CE IP20 ENEC	Matt White - 2700K Matt White - 3000K Matt Black - 2700K Matt Black - 3000K	1A2270300.27.20 1A2270300.30.20 1A2270400.27.20 1A2270400.30.20
--	--	--


How to order -
INFINITO 5 TW



How to order -
INFINITO 10 TW




Note Tunable White describes the variable colour temperature controls from warm white to cool white light.
Tunable White è la regolazione variabile della temperatura di colore dalla tonalità calda a quella fredda.



INFINITO 5 TW
Length 5000 mm - Tunable White
50W
24V DC
2700/6500K - 7650lm
CRI >90
Driver not included
CE IP20

Matt White - 2700/6500K	1A4860300.96.20
Matt Black - 2700/6500K	1A4860400.96.20



INFINITO 10 TW
Length 10000 mm - Tunable White
100W
24V DC
2700/6500K - 15300lm
CRI >90
Driver not included
CE IP20

Matt White - 2700/6500K	1A4870300.96.20
Matt Black - 2700/6500K	1A4870400.96.20


Compulsory accessories / Accessori obbligatori

Installation kit / Kit installazione




Spacer / Distanziale				Not included
Matt White	For power supply kit with plug	INFINITO 6 / INFINITO 12	1A4930300.00.00	
Matt Black	For power supply kit with plug	INFINITO 6 / INFINITO 12	1A4930400.00.00	


Electrical power supply / Alimentazione elettrica




Power supply kit with plug / Kit alimentazione con spina				Not included
Matt White	Input 100-240V - 50/60Hz - Output 48V - Max 57W - IP20	INFINITO 6	1X0060300.01.06	
Matt Black	Input 100-240V - 50/60Hz - Output 48V - Max 57W - IP20	INFINITO 6	1X0060400.01.06	




Power supply kit with plug / Kit alimentazione con spina				Not included
Matt White	Input 100-240V - 50/60Hz - Output 48V - Max 114W - IP20	INFINITO 12	1X0060300.02.06	
Matt Black	Input 100-240V - 50/60Hz - Output 48V - Max 114W - IP20	INFINITO 12	1X0060400.02.06	




Driver LED				Not included
100-240V	48V/80W/IP67/1-10V	INFINITO 6 / INFINITO 5 TW	1Z1120400	




Driver LED				Not included
100-240V	48V/150W/IP67/1-10V	INFINITO 12 / INFINITO 10 TW	1Z1120250	



Driver LED				Not included
100-240V	48V/240W/IP67/1-10V	INFINITO 18	1Z1120390	




Controller				Not included
Matt Black	DALI - PUSH - 0/1-10V - TRIAC - IP20	INFINITO 6 / INFINITO 12 / INFINITO 18	1Z2170010	



Controller Casambi - Tunable White				Not included
		INFINITO 5 TW / INFINITO 10 TW	1Z0830880	

Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Ceiling connection kit / Kit attacco soffitto		Not included
Matt Black	1A0080400.00.00	



Kit wall connection vertical sloped 45° / Kit attacco parete per inclinazione verticale 45°		Not included
Matt Black	1A0120400.00.00	




Kit wall connection sloped right 75° / Kit attacco parete per inclinazione 75° destro		Not included
Matt Black	1A0340400.00.00	




Kit wall connection sloped left 75° / Kit attacco parete per inclinazione 75° sinistro		Not included
Matt Black	1A0350400.00.00	




Swallows / Rondini		Not included
Matt Black	1A0800400.00.00	




Remote power supply kit




Power supply kit with plug




1A0080400.00.00 - Ceiling connection kit




1A0080400.00.00 - Example of installation with ceiling connection kit




Example of installation with max rotation 30°



1A0120400.00.00 - Kit wall connection vertical sloped 45°



1A0340400.00.00 - 1A0350400.00.00 - Kit wall connection sloped 75°





MAGIA

Michele Groppi / 2023

Light and transparency are the true stars of this project. We have always liked to think heretically, evoking mystery, magic and seduction. Magia is the new modular suspension lighting system that can be adapted to suit the different heights of the rooms and can generate direct and indirect light with the 360° adjustable module. In this case, the lens is not used to focus, but to modify the vision and perception of the object. The effect of the convex lens conceals the part of the light beam and produces the lightest effect of suspension and inconsistency.


Archiproducts Design Award 2023

La luce e la trasparenza sono le vere protagoniste di questo progetto. Da sempre ci piace pensare in modo eretico, evocando mistero, magia e seduzione. Magia è il nuovo sistema d'illuminazione a sospensione componibile e adattabile a seconda delle diverse altezze degli ambienti che può generare luce diretta e indiretta con il modulo orientabile a 360°. In questo caso, la lente non è usata per focalizzare, ma per modificare la visione e la percezione dell'oggetto. L'effetto della lente convessa permette di celare la parte di emissione della luce e produrre un leggerissimo effetto di sospensione e inconsistenza.


Archiproducts Design Award 2023




Single installation with ceiling rose




Multiple installation with ceiling rose



Single installation with recessed fixing kit or ceiling fixing kit



Multiple installation with recessed fixing kit or ceiling fixing kit



MAGIA

Michele Groppi / 2023

Systems / Direct-Indirect / Indoor

Material

Finish


.19 Polished Gold

.28 Polished Black Chrome

Note

Adjustable modular system.

Sistema orientabile modulare.

	MAGIA - TUBE		
	19W	Polished Gold - 2700K	1A4721900.27.20
	24V DC	Polished Gold - 3000K	1A4721900.30.20
	2700K - 1272lm / 3000K - 1312lm	Polished Black Chrome - 2700K	1A4722800.27.20
	CRI >90	Polished Black Chrome - 3000K	1A4722800.30.20
Driver not included			

Compulsory accessories / Accessori obbligatori


Installation kit / Kit installazione		Suspension fixing kit - See page 614 / Kit di fissaggio per sospensione - Vedi pagina 614	
	Unipolar wire - 6m / Cavo unipolare - 6m		Not included
	1 Piece - Max 60V DC	Max 3 tubes	1A4730000.00.00
	Wire guide / Guidacavo		Not included
	Matt Black	1 Piece	1A3040400.00.00
	Recessed fixing kit for 12.5 mm plasterboard / Kit di fissaggio ad incasso per cartongesso 12,5 mm		Not included
	Matt White	For electrical cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm	1X0000300.02.00
	Matt Black	For electrical cables - 1 Piece - Plasterboard cut-out Ø 44 mm - Minimum space for mounting 70 mm	1X0000400.02.00
	Ceiling fixing kit / Kit di fissaggio a soffitto		Not included
	Matt White	For electrical cables - 1 Piece	1X0010300.02.00
	Matt Black	For electrical cables - 1 Piece	1X0010400.02.00

Michele Groppi / 2023


MAGIA

Compulsory accessories / Accessori obbligatori


Electrical power supply / Alimentazione elettrica




Ceiling rose / Rosone da soffitto		Not included	
Matt White	Input 220-240V - 50/60Hz - Output 24V - 21W - IP20 - DALI - PUSH - 1-10V - TRIAC	Max 1 tube	1A4780300.00.05




Ceiling rose / Rosone da soffitto		Not included	
Matt White	Input 120-240V - 50/60Hz - Output 24V - 60W - IP20 - DALI - PUSH - 1-10V - TRIAC	Max 3 tubes	1A4740300.00.05




Driver LED		Not included	
100-240V	24V/50W/IP20/ON/OFF	Max 1 tube	1Z1120490



Driver LED		Not included	
100-240V	24V/80W/IP20/ON/OFF	Max 3 tubes	1Z1120440




Driver LED		Not included	
100-240V	24V/150W/IP67/1-10V	Max 6 tubes	1Z1120500



Controller		Not included	
Matt Black	DALI - PUSH - 0/1-10V - TRIAC - IP20	1Z2170010	


Optional accessories / Accessori opzionali

Installation kit / Kit installazione




Wall back plate / Piastra parete		Not included	
Matt White	For mounting on brick masonry walls	1X0050300.01.00	


463




Example of single installation with ceiling rose




Example of multiple installation with ceiling rose




Example of single installation with recessed fixing kit




Example of multiple installation with recessed fixing kit




Example of single installation with ceiling fixing kit



Example of multiple installation with ceiling fixing kit



Example of multiple installation | **Max 3 tubes for cable**



Light runs on a wire. An almost imperceptible wire, suspended in space. Like a tightrope walker on a thin rope, the light reaches everywhere, weightless and wonderful. Ohm is an electro mechanic project that takes maximum advantage of the characteristics of luminous diodes. Its secret is a special unipolar wire stretched from wall to wall. Where the light comes from is discreetly hidden, giving all the attention to what it is illuminating.

It is possible to replace the light source even with the luminaire assembled. It can be powered with pur Endless system.

Selection for ADI Design Index 2020

La luce corre sul filo. Un filo quasi impercettibile, sospeso nello spazio. Come un funambolo su una corda sottilissima, la luce arriva ovunque, con leggerezza ed emozione.


Ohm è un progetto elettromeccanico, che sfrutta al massimo le caratteristiche dei diodi luminosi. Il segreto è uno speciale cavo unipolare tirato da parete a parete. La fonte quasi si nasconde, impalpabile e discreta, regalando la scena al soggetto illuminato.

È possibile sostituire l'ottica anche ad apparecchio montato.


Può essere alimentata con il nostro sistema Endless.

Selezione per ADI Design Index 2020


Remote driver version



Wall and ceiling rose version



Suspension version




Systems / Direct / Indoor

Material	Metal - PA
Finish	.04 Matt Black

Note Special single-pole cable running between two walls and ceiling - Max 4 Spot on unipolar wire.

Speciale cavo unipolare tirato da parete a parete o a soffitto - Max 4 Spot su cavo unipolare.



OHM SPOT

3,2W

Max 350mA DC

2700K / 3000K

CRI 95

Driver not included

CE  IP20

Matt Black - 2700K


Matt Black - 3000K

1A3000400.27.20

1A3000400.30.20

Compulsory accessories / Accessori obbligatori

Installation kit / Kit installazione



Tie rods / Tiranti

Not included

Matt White

2 Pieces

1A3020300.00.00



Unipolar wire - 12m / Cavo unipolare - 12m

Not included

Max 60V DC

1A3060000.00.00

Unipolar wire - 24m / Cavo unipolare - 24m

Not included

Max 60V DC

1A3070000.00.00

Unipolar wire - 48m / Cavo unipolare - 48m

Not included

Max 60V DC

1A3080000.00.00


Compulsory accessories / Accessori obbligatori

Other accessories / Altri accessori




Lens / Lente		Not included		
Beam - 12°	2700K - CRI 95 - 272lm	OHM SPOT	1A3090000.00.00	
	3000K - CRI 95 - 288lm			
Beam - 24°	2700K - CRI 95 - 271lm	OHM SPOT	1A3100000.00.00	
	3000K - CRI 95 - 286lm			
Beam - 39°	2700K - CRI 95 - 257lm	OHM SPOT	1A3110000.00.00	
	3000K - CRI 95 - 273lm			
Beam - 54°	2700K - CRI 95 - 254lm	OHM SPOT	1A3120000.00.00	
	3000K - CRI 95 - 270lm			

Electrical power supply / Alimentazione elettrica




Wall/ceiling rose power supply kit / Kit alimentazione rosone parete/soffitto			Not included	
Matt White	Input 100-240V - 50/60Hz - Output 350mA - 18,5W - IP20 - DALI - PUSH - 1-10V		1A3010300.00.07	



Driver LED		Not included		
220-240V(100-127V)	350mA/18W(18W)/IP20/DALI - PUSH - 1-10V		1Z0240530.350	

Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Wall back plate / Piastra parete		Not included		
Matt White	For mounting on brick masonry walls		1A3030300.00.00	




Wire guide / Guidacavo		Not included		
Matt Black	1 Piece		1A3040400.00.00	




Weight kit for suspension version / Kit pesi per versione a sospensione		Not included		
	4 Pieces		1A3050000.00.00	











Remote driver version






Remote driver layout example



Remote driver layout example








BINARIO TRIFASE

/ 2007


Pure line in space.
Our track holds the models Dot, Mira and Spot.

Linea pura nello spazio.
Il nostro binario accoglie i modelli Dot, Mira e Spot.

Power right connector and power left connector installation



Power intermediate connector installation




Tracks / Diffuse / Indoor

Material Metal
Finish .03 Matt White .04 Matt Black

Note Wall and ceiling track with white.


Binario a parete e soffitto in finitura bianca e nera.



MIRA BINARIO
8W
220-240V
2700K - 327lm / 3000K - 352lm
CRI >90
Driver not included
DALI
CE IP20

Matt White - 2700K - DALI
Matt White - 3000K - DALI
Matt Black - 2700K - DALI
Matt Black - 3000K - DALI

1A0490300.27.01
1A0490300.30.01
1A0490400.27.01
1A0490400.30.01



DOT BINARIO
13W
220-240V
2700K / 3000K
Driver not included
DALI
CE IP20

Matt White - 2700K - DALI
Matt White - 3000K - DALI
Matt Black - 2700K - DALI
Matt Black - 3000K - DALI

1A2290300.27.01
1A2290300.30.01
1A2290400.27.01
1A2290400.30.01



DOT BINARIO 51
Max 10W
100-240V
Bulb not included
ON/OFF
CE IP20

Matt White - ON/OFF
Matt Black - ON/OFF

1A3710300.00.00
1A3710400.00.00




Optional accessories / Accessori opzionali

Installation kit / Kit installazione

	Linear connector / Connettore lineare		Not included
	Matt Black	1A2800400.11.00	
	Matt White	1A2800300.11.00	
	Internal L connector / Connettore L interno		Not included
	Matt White	1A2800300.09.00	
	Matt Black	1A2800400.09.00	
	External L connector / Connettore L esterno		Not included
	Matt White	1A2800300.08.00	
	Matt Black	1A2800400.08.00	
	Right T connector / Connettore T destro		Not included
	Matt Black	1A2800400.14.00	
	Matt White	1A2800300.14.00	
	Left T connector / Connettore T sinistro		Not included
	Matt White	1A2800300.10.00	
	Matt Black	1A2800400.10.00	
	X connector / Connettore X		Not included
	Matt White	1A2800300.15.00	
	Matt Black	1A2800400.15.00	
	Adjustable suspension cable / Cavo di sospensione regolabile		Not included
	Lenght 1500mm	1A2800000.04.00	
	Adjustable suspension cable / Cavo di sospensione regolabile		Not included
	Lenght 3000mm	1A2800000.05.00	
	Adjustable suspension cable / Cavo di sospensione regolabile		Not included
	Lenght 5000mm	1A2800000.06.00	
	Clamp for track / Pinza per binario		Not included
		1A2800300.17.00	


Optional accessories / Accessori opzionali

Bulbs / Lampadine


	LED SORAA - GU10 - MR16		Not included
	230V - 7,5W - 10° - 2700K - 390lm - CRI 95 - Energy Efficiency G - Dimmable	DOT BINARIO 51	1Y1580210
	LED SORAA - GU10 - MR16		Not included
	230V - 7,5W - 10° - 3000K - 410lm - CRI 95 - Energy Efficiency G - Dimmable	DOT BINARIO 51	1Y1580010
	LED - GU10 - PAR16		Not included
	220-240V - 5,5W - 25° - 3000K - 375lm - CRI 97 - Energy Efficiency G - Dimmable	DOT BINARIO 51	1Y0330500
	Darklight		Not included
	MR16	LED SORAA - GU10	51580040
	25° beam filter / Filtro fascio 25°		Not included
	MR16	LED SORAA - GU10	51580020
	36° beam filter / Filtro fascio 36°		Not included
	MR16	LED SORAA - GU10	51580030

Optional accessories / Accessori opzionali


Other accessories / Altri accessori



Horizontal directional fins / Alette direzionali			Not included
Matt Black	SPOT BINARIO	1X0070400.01.00	



Cylindrical screen / Schermo cilindrico			Not included
Matt Black	SPOT BINARIO	1X0070400.02.00	



Cone 45° / Cono 45°			Not included
Matt Black	SPOT BINARIO	1X0070400.03.00	



Accessory holder + Soft filter + Honeycomb louvre / Porta accessori + Filtro soft + Frangiluce nido d'ape			Not included
Matt Black	SPOT BINARIO	1X0070400.04.00	



Accessory holder + Elliptical filter / Porta accessori + Filtro ellittico			Not included
Matt Black	SPOT BINARIO	1X0070400.05.00	



Blue filter / Filtro blu			Not included
Standard	SPOT BINARIO	1X0070000.06.00	





Red filter / Filtro rosso			Not included
Standard	SPOT BINARIO	1X0070000.07.00	



Yellow filter / Filtro giallo			Not included
Standard	SPOT BINARIO	1X0070000.08.00	








A minimal track system with tiny lights,
small hummingbirds that perch where needed.


Un sistema a binario ridotto al minimo, con minuscoli corpi luminosi,
piccoli Colibri che si posano dove necessario.



Layout example of wall and ceiling version



Layout example of recessed version



Tracks / Direct / Indoor


Material

Finish .04 Matt Black

Note

Wall or ceiling system for direct light - Superficial or recessed installation - Luminaire designed to be powered by ENDLESS system.

Sistema a parete o soffitto a luce diretta - Installazione a superficie o da incasso - Apparecchio predisposto per essere alimentato dal sistema ENDLESS.




COLIBRÌ 18 - BEAM 15°

2W
48V DC
2700K - 81lm / 3000K - 84lm
Beam 15°
CRI >90
Driver not included
DALI
CE IP20

Matt Black - 2700K - DALI
Matt Black - 3000K - DALI

1A4260400.27.01
1A4260400.30.01




COLIBRÌ 18 - BEAM 25°

2W
48V DC
2700K - 79lm / 3000K - 81lm
Beam 25°
CRI >90
Driver not included
DALI
CE IP20

Matt Black - 2700K - DALI
Matt Black - 3000K - DALI

1A4270400.27.01
1A4270400.30.01




COLIBRÌ 28 - BEAM 15°

4W
48V DC
2700K - 147lm / 3000K - 151lm
Beam 15°
CRI >90
Driver not included
DALI
CE IP20

Matt Black - 2700K - DALI
Matt Black - 3000K - DALI

1A4280400.27.01
1A4280400.30.01




COLIBRÌ 28 - BEAM 25°
5W
48V DC
2700K - 250lm / 3000K - 258lm
Beam 25°
CRI >90
Driver not included
DALI
CE IP20

Matt Black - 2700K - DALI	1A4290400.27.01
Matt Black - 3000K - DALI	1A4290400.30.01

Compulsory accessories / Accessori obbligatori


Installation kit / Kit installazione



Wall and ceiling track - 1m / Binario da parete e soffitto - 1m	Not included
Matt White	1A4170300.01.00
Matt Black	1A4170400.01.00

Wall and ceiling track - 2m / Binario da parete e soffitto - 2m	Not included
Matt White	1A4170300.02.00
Matt Black	1A4170400.02.00

Wall and ceiling track - 3m / Binario da parete e soffitto - 3m	Not included
Matt White	1A4170300.03.00
Matt Black	1A4170400.03.00




Power connector / Elemento di alimentazione	Not included
Matt White	1A4170300.04.00
Matt Black	1A4170400.04.00



End cap / Tappo di chiusura	Not included
Matt White	1A4170300.07.00
Matt Black	1A4170400.07.00

Compulsory accessories / Accessori obbligatori

Installation kit / Kit installazione



Recessed wall and ceiling track - 1m / Binario da parete e soffitto da incasso - 1m	Not included
Matt Black	1A4180400.01.00

Recessed wall and ceiling track - 2m / Binario da parete e soffitto da incasso - 2m	Not included
Matt Black	1A4180400.02.00

Recessed wall and ceiling track - 3m / Binario da parete e soffitto da incasso - 3m	Not included
Matt Black	1A4180400.03.00




Power connector / Elemento di alimentazione		Not included
Matt Black	For recessed track	1A4180400.04.00




End cap / Tappo di chiusura		Not included
Matt Black	For recessed track	1A4180400.05.00

Electrical power supply / Alimentazione elettrica





Remote power supply kit / Kit alimentazione remoto	Not included
Input 100-240V - 50/60Hz - Output 48V - 60W - IP20 - DALI	1A4170000.19.00




Remote power supply kit / Kit alimentazione remoto	Not included
Input 100-240V - 50/60Hz - Output 48V - 150W - IP20 - DALI	1A2810000.11.00

Optional accessories / Accessori opzionali

Installation kit for wall and ceiling track / Kit installazione per binario da parete e soffitto





	Corner joint cover H / Coprigiunto angolare H		Not included
	Matt White	For wall and ceiling track	1A4170300.05.00
	Matt Black	For wall and ceiling track	1A4170400.05.00
	Corner joint cover V / Coprigiunto angolare V		Not included
	Matt White	For wall and ceiling track	1A4170300.06.00
	Matt Black	For wall and ceiling track	1A4170400.06.00
	Cover - 3m / Copertura - 3m		Not included
	Matt White	For wall and ceiling track	1A4170300.08.00
	Matt Black	For wall and ceiling track	1A4170400.08.00
	Endless adapter / Adattatore Endless		Not included
	Standard	For wall and ceiling track	1A4170000.20.00

Installation kit for recessed track / Kit installazione per binario da incasso

	Cover - 1m / Copertura - 1m		Not included
	Matt White	For recessed track	1A4180300.06.00
	Matt Black	For recessed track	1A4180400.06.00
	Cover - 2m / Copertura - 2m		Not included
	Matt White	For recessed track	1A4180300.07.00
	Matt Black	For recessed track	1A4180400.07.00
	Cover - 3m / Copertura - 3m		Not included
	Matt White	For recessed track	1A4180300.08.00
	Matt Black	For recessed track	1A4180400.08.00
	Template / Modello		Not included
	Standard	For recessed track	1A4180000.09.00

Optional accessories / Accessori opzionali

Installation kit / Kit installazione

	L joint / Giunto a L		Not included
	Matt Black		1A4170400.13.00
	L-feed ceiling wall / Alimentazione a L soffitto-parete		Not included
	Matt Black		1A4170400.14.00
	Flexible joint / Giunto flessibile		Not included
	Matt Black		1A4170400.15.00
	Jointing connector / Connettore di giunzione		Not included
	Matt Black		1A4170400.16.00
	Locking tool for PVC / Strumento di bloccaggio per PVC		Not included
	Standard		1A4170000.17.00






Plasterboard track for recessed installation. It is designed for use with state-of-the-art LED modules to create a wide range of light beams.

Binario per installazione da incasso per cartongesso. Ideato per utilizzare moduli a LED di ultima generazione ed avere un'ampia disponibilità di fasci luminosi.


Layout example



Tracks / Direct / Indoor

Material

Finish .03 Matt White .04 Matt Black



DOT FRAMELESS

13W
48V DC
2700K / 3000K
CRI 97
Driver not included
DALI




Matt White - 2700K - DALI
Matt White - 3000K - DALI
Matt Black - 2700K - DALI
Matt Black - 3000K - DALI

1A0090300.27.01
1A0090300.30.01
1A0090400.27.01
1A0090400.30.01

Compulsory accessories / Accessori obbligatori

Installation kit / Kit installazione



Plasterboard track 12,5mm / Binario per cartongesso 12,5mm		Not included
Matt Black	48V DC - Max 15A - Lenght 2000mm - Cut-out 2000 x 26mm	1A2810400.01.00



Power connector / Elemento di alimentazione		Not included
Matt Black	Output 48V - Max 15A	1A2810400.02.00



End cap for power connector / Tappo di chiusura per alimentazione		Not included
Matt Black		1A2810400.03.00



End cap / Tappo di chiusura		Not included
Matt Black		1A2810400.04.00

Compulsory accessories / Accessori obbligatori

Installation kit / Kit installazione




Linear connector / Connettore lineare		Not included
Matt Black	Output 48V - Max 15A	1A2810400.05.00



Reinforcing bracket / Staffa di rinforzo		Not included
Matt Black		1A2810400.06.00



Clamp with M6 grippe / Morsetto con pinza M6		Not included
		1A2810000.07.00



Suspension set / Set sospensione		Not included
		1A2810000.08.00



Plaster installation guard / Protezione per installazione cartongesso		Not included
Lenght 2000mm		1A2810000.09.00



Cutting tool / Strumento taglio		Not included
		1A2810000.10.00


Other accessories / Altri accessori




Lens / Lente		Not included	
Beam - 14°	2700K - CRI 97 - 983lm	DOT FRAMELESS	1A3090000.00.00
	3000K - CRI 97 - 1038lm		
Beam - 24°	2700K - CRI 97 - 943lm	DOT FRAMELESS	1A3100000.00.00
	3000K - CRI 97 - 996lm		
Beam - 36°	2700K - CRI 97 - 955lm	DOT FRAMELESS	1A3110000.00.00
	3000K - CRI 97 - 1005lm		
Beam - 50°	2700K - CRI 97 - 965lm	DOT FRAMELESS	1A3120000.00.00
	3000K - CRI 97 - 1016lm		

Compulsory accessories / Accessori obbligatori


Electrical power supply / Alimentazione elettrica




Remote power supply kit / Kit alimentazione remoto		Not included
Input 100-240V - 50/60Hz - Output 48V - 150W - IP20 - DALI		1A2810000.11.00




Remote power supply kit / Kit alimentazione remoto		Not included
Input 100-240V - 50/60Hz - Output 48V - 320W - IP20 - DALI		1A2810000.12.00



Driver LED		Not included
100-240V	48V/150W/IP67/1-10V	1Z1120250



Driver LED		Not included
100-240V	48V/320W/IP67/1-10V	1Z1120380



Profiles designed to create projects with continuous light.


Profili pensati per realizzare progetti di luce continua.

Tracks / Direct / Indoor

Material	Metal
Finish	.00 Standard

Compulsory accessories / Accessori obbligatori

Installation kit / Kit installazione



Aluminium profile 2m / Profilo in alluminio 2m		Not included
Standard	With opal cover	1A4970000.01.00



Cap / Tappo		Not included
Standard		1A4970000.02.00




Fixing spring / Molla di fissaggio		Not included
Standard		1A4970000.03.00

Lighting modules / Corpi illuminanti




Strip LED - 5 m		Not included
	Input 24V DC - 63W - IP20 - 2700K - 6200lm - CRI >94	1A5010000.27.20
	Input 24V DC - 63W - IP20 - 3000K - 6900lm - CRI >94	1A5010000.30.20

Electrical power supply / Alimentazione elettrica




Driver LED		Not included
100-240V	24V/60W/IP67/1-10V	1Z1120260




Driver LED		Not included
100-240V	24V/80W/IP20/ON/OFF	1Z1120440

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica



Driver LED		Not included
100-240V	24V/96W/IP67/1-10V	1Z1120540




Driver LED		Not included
100-240V	24V/150W/IP67/1-10V	1Z1120500

Tracks / Direct / Indoor

Material	Metal
Finish	.00 Standard

Compulsory accessories / Accessori obbligatori

Installation kit / Kit installazione



Aluminium profile 2m / Profilo in alluminio 2m		Not included
Standard	With opal cover	1A4970000.04.00



Cap / Tappo		Not included
Standard		1A4970000.05.00




Fixing spring / Molla di fissaggio		Not included
Standard		1A4970000.06.00

Lighting modules / Corpi illuminanti




Strip LED - 5 m		Not included
	Input 24V DC - 63W - IP20 - 2700K - 6200lm - CRI >94	1A5010000.27.20
	Input 24V DC - 63W - IP20 - 3000K - 6900lm - CRI >94	1A5010000.30.20

Electrical power supply / Alimentazione elettrica




Driver LED		Not included
100-240V	24V/60W/IP67/1-10V	1Z1120260




Driver LED		Not included
100-240V	24V/80W/IP20/ON/OFF	1Z1120440

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica



Driver LED		Not included
100-240V	24V/96W/IP67/1-10V	1Z1120540




Driver LED		Not included
100-240V	24V/150W/IP67/1-10V	1Z1120500

Tracks / Direct / Indoor


Material	Metal
Finish	.00 Standard

Compulsory accessories / Accessori obbligatori

Installation kit / Kit installazione




Aluminium profile 2m / Profilo in alluminio 2m	Not included
Standard	1A4970000.07.00



Opal cover 2m / Diffusore opale 2m	Not included
Standard	1A4970000.08.00



Transparent cover 2m / Diffusore trasparente 2m	Not included
Standard	1A4970000.09.00



Satin cover 2m / Diffusore satinato 2m	Not included
Standard	1A4970000.10.00



Cap / Tappo	Not included
Standard	1A4970000.11.00



Adhesive 1m / Adesivo 1m	Not included
Standard	1A4970000.12.00



Adhesive magnet 1m / Calamita adesiva 1m	Not included
Standard	1A4970000.13.00

Compulsory accessories / Accessori obbligatori

Lighting modules / Corpi illuminanti



Strip LED - 5 m	Not included
Input 24V DC - 72W - IP20 - 2700K - 7100lm - CRI >80	1A4980000.27.20
Input 24V DC - 72W - IP20 - 3000K - 7875lm - CRI >80	1A4980000.30.20



Strip LED - 5 m	Not included
Input 24V DC - 96W - IP20 - 2700K - 10500lm - CRI >80	1A4990000.27.20
Input 24V DC - 96W - IP20 - 3000K - 11700lm - CRI >80	1A4990000.30.20




Strip LED - 5 m	Not included
Input 24V DC - 72W - IP65 - 2700K - 7100lm - CRI 82	1A5000000.27.20
Input 24V DC - 72W - IP65 - 3000K - 7875lm - CRI 82	1A5000000.30.20




Strip LED - 5 m	Not included
Input 24V DC - 63W - IP20 - 2700K - 6200lm - CRI >94	1A5010000.27.20
Input 24V DC - 63W - IP20 - 3000K - 6900lm - CRI >94	1A5010000.30.20


Electrical power supply / Alimentazione elettrica




Driver LED			Not included
100-240V	24V/60W/IP67/1-10V	1Z1120260	



Driver LED			Not included
100-240V	24V/80W/IP20/ON/OFF	1Z1120440	



Driver LED			Not included
100-240V	24V/96W/IP67/1-10V	1Z1120540	




Driver LED			Not included
100-240V	24V/150W/IP67/1-10V	1Z1120500	

Tracks / Direct / Indoor


Material	Metal
Finish	.00 Standard

Compulsory accessories / Accessori obbligatori


Installation kit / Kit installazione




Aluminium profile 2m / Profilo in alluminio 2m	Not included
Standard	1A4970000.14.00




Opal cover 2m / Diffusore opale 2m	Not included
Standard	1A4970000.08.00



Transparent cover 2m / Diffusore trasparente 2m	Not included
Standard	1A4970000.09.00




Satin cover 2m / Diffusore satinato 2m	Not included
Standard	1A4970000.10.00



Cap / Tappo	Not included
Standard	1A4970000.15.00



Fixing spring / Molla di fissaggio	Not included
Standard	1A4970000.16.00



Formwork kit 2m / Kit cassaforma 2m	Not included
Standard	1A4970000.17.00

Compulsory accessories / Accessori obbligatori

Lighting modules / Corpi illuminanti



Strip LED - 5 m	Not included
Input 24V DC - 72W - IP20 - 2700K - 7100lm - CRI >80	1A4980000.27.20
Input 24V DC - 72W - IP20 - 3000K - 7875lm - CRI >80	1A4980000.30.20



Strip LED - 5 m	Not included
Input 24V DC - 96W - IP20 - 2700K - 10500lm - CRI >80	1A4990000.27.20
Input 24V DC - 96W - IP20 - 3000K - 11700lm - CRI >80	1A4990000.30.20




Strip LED - 5 m	Not included
Input 24V DC - 72W - IP65 - 2700K - 7100lm - CRI 82	1A5000000.27.20
Input 24V DC - 72W - IP65 - 3000K - 7875lm - CRI 82	1A5000000.30.20




Strip LED - 5 m	Not included
Input 24V DC - 63W - IP20 - 2700K - 6200lm - CRI >94	1A5010000.27.20
Input 24V DC - 63W - IP20 - 3000K - 6900lm - CRI >94	1A5010000.30.20


Electrical power supply / Alimentazione elettrica




Driver LED			Not included
100-240V	24V/60W/IP67/1-10V	1Z1120260	



Driver LED			Not included
100-240V	24V/80W/IP20/ON/OFF	1Z1120440	



Driver LED			Not included
100-240V	24V/96W/IP67/1-10V	1Z1120540	




Driver LED			Not included
100-240V	24V/150W/IP67/1-10V	1Z1120500	

Tracks / Direct / Indoor

Material	Metal
Finish	.00 Standard

Compulsory accessories / Accessori obbligatori

Installation kit / Kit installazione



Aluminium profile 2m / Profilo in alluminio 2m	Not included
Standard	1A4970000.18.00
Opal cover 2m / Diffusore opale 2m	Not included
Standard	1A4970000.19.00

Lighting modules / Corpi illuminanti



Strip LED - 5 m	Not included
Input 24V DC - 72W - IP20 - 2700K - 7100lm - CRI >80	1A4980000.27.20
Input 24V DC - 72W - IP20 - 3000K - 7875lm - CRI >80	1A4980000.30.20



Strip LED - 5 m	Not included
Input 24V DC - 96W - IP20 - 2700K - 10500lm - CRI >80	1A4990000.27.20
Input 24V DC - 96W - IP20 - 3000K - 11700lm - CRI >80	1A4990000.30.20




Strip LED - 5 m	Not included
Input 24V DC - 72W - IP65 - 2700K - 7100lm - CRI 82	1A5000000.27.20
Input 24V DC - 72W - IP65 - 3000K - 7875lm - CRI 82	1A5000000.30.20




Strip LED - 5 m	Not included
Input 24V DC - 63W - IP20 - 2700K - 6200lm - CRI >94	1A5010000.27.20
Input 24V DC - 63W - IP20 - 3000K - 6900lm - CRI >94	1A5010000.30.20

Compulsory accessories / Accessori obbligatori


Electrical power supply / Alimentazione elettrica




Driver LED	Not included
100-240V24V/60W/IP67/1-10V	1Z1120260



Driver LED	Not included
100-240V24V/80W/IP20/ON/OFF	1Z1120440



Driver LED	Not included
100-240V24V/96W/IP67/1-10V	1Z1120540



Driver LED	Not included
100-240V24V/150W/IP67/1-10V	1Z1120500

OUTDOOR / ESTERNO



BELLADINOTTE

Maurizio Mancini / 2012

The magic of the mirror brought into the garden.
A study of camouflage. The reflective surface is used as a tool
to camouflage and hide the machine to create light.
The reflection of the environment makes the luminaire invisible.

La magia dello specchio portata in giardino.
Un lavoro sulla mimetica. La superficie riflettente utilizzata come strumento
per mimetizzare e nascondere la macchina per fare luce.
La riflessione del contesto ambientale rende invisibile il corpo illuminante.

BELLADINOTTE

Floor-Outdoor / Indirect / Outdoor

Material

Metal


Finish

.00 Standard

Note

Adjustable luminaire with mirror top - Green back side - Black cable (5 m).

Apparecchio orientabile con piano a specchio - Retro colore verde - Cavo nero (5 m).



BELLADINOTTE

2x4,2W
24V DC
2700K - 262lm / 3000K - 282lm
CRI >90
Driver not included


CE IP67

Standard - 2700K
Standard - 3000K

1A3560000.27.20
1A3560000.30.20

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica



Driver LED		Not included
110-240V	24V/25W/IP67/ON/OFF	1Z1120620

Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Driver connector IP68 / Connettore driver IP68		Included
1 Piece		1A1660000.00.00





BUBKA

Daniele Sprega / 2014

A perfect tool to make outdoor light.
The light as a tool for guiding people along a path or emphasising
the hierarchies of spaces and functions.

Un perfetto utensile per fare la luce fuori.
La luce come strumento per condurre le persone lungo i percorsi
oppure scandire le gerarchie degli spazi e delle funzioni.

BUBKA

Daniele Sprega / 2014

Outdoor-Floor / Direct / Outdoor

Material

AISI 316L Stainless Steel - Metal


Finish

.00 Standard

Note

Adjustable luminaire with AISI 316L Stainless steel stem - Black cable (7 m).

Apparecchio orientabile con stelo in acciaio INOX AISI 316L - Cavo nero (7 m).



BUBKA

8,4W

Max 700mA DC

2700K - 639lm / 3000K - 639lm

CRI >90

Driver not included

CE IP65

Standard - 2700K


Standard - 3000K

1A3600000.27.20

1A3600000.30.20

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica



Driver LED


220-240V(100-127V) 700mA/30W(15W)/IP68/ON/OFF

Not included

1Z0241110

Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Anchoring bolt / Tirafondo

Cut-out Ø 250 mm -
Minimum space for mounting 350 mm

Not included

1A3620000.00.00

Driver connector IP68 / Connettore driver IP68

1 Piece

Included


1A1660000.00.00

Daniele Sprega / 2014

BUBKA

Optional accessories / Accessori opzionali

Lighting modules / Corpi illuminanti



Additional LED head / Testa LED supplementare

Matt Black

Max 700mA DC - 8,4W -
2700K - 639lm - CRI>90

Max 700mA DC - 8,4W -
3000K - 639lm - CRI>90

Not included

1A3610400.27.20

1A3610400.30.20






BUBKA BOLLARD

Daniele Sprega / 2021

A perfect tool to make outdoor light.
The light as a tool for guiding people along a path or emphasising
the hierarchies of spaces and functions.


Un perfetto utensile per fare la luce fuori.
La luce come strumento per condurre le persone lungo i percorsi
oppure scandire le gerarchie degli spazi e delle funzioni.

Outdoor-Floor / Direct / Outdoor	
Material	AISI 316L Stainless Steel - Metal
Finish	.00 Standard
Note	Adjustable luminaire with AISI 316L Stainless steel stem - Black cable (9 m).
	Apparecchio orientabile con stelo in acciaio INOX AISI 316L - Cavo nero (9 m).

	BUBKA BOLLARD	
	8,4W	
	Max 700mA DC	
	2700K - 350lm / 3000K - 350lm	
	CRI >90	
	Driver not included	
	CE IP65	
	Standard - 2700K	1A1440000.27.20
	Standard - 3000K	1A1440000.30.20


Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica

	Driver LED		Not included
	220-240V(100-127V)	350mA/17W(15W)/IP68/ON/OFF	1Z0240880


Optional accessories / Accessori opzionali

Installation kit / Kit installazione

	Anchoring bolt / Tirafondo		Not included
	Cut-out Ø 250 mm - Minimum space for mounting 350 mm	1A3620000.00.00	
	Driver connector IP68 / Connettore driver IP68		Included
	1 Piece	1A1660000.00.00	

Optional accessories / Accessori opzionali

Lighting modules / Corpi illuminanti

	Additional LED head / Testa LED supplementare		Not included
	Matt Black	Max 700mA DC - 8,4W - 2700K - 639lm - CRI>90	1A3610400.27.20
		Max 700mA DC - 8,4W - 3000K - 639lm - CRI>90	1A3610400.30.20





A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.


Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

Outdoor-Wall / Direct / Outdoor

Material Glass - Metal

Finish .03 Matt White



CHILLOUT
Max 12W - E27
100-240V - 50/60Hz
Bulb not included
ON/OFF
CE IP65

Matt White - ON/OFF

1A3660300.00.00

Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Driver connector IP68 / Connettore driver IP68		Included
1 Piece	1A1660000.00.00	

Bulbs / Lampadine



LED - E27 - PAR30s		Not included
220-240V - 9,5W - 25° - 3000K - 760lm - CRI 80 - Energy Efficiency F - Dimmable	1Y0330730	





GRILLO

Daniele Sprega / 2012

A small luminous elf that you can install in your garden or inside a vase.

A thin stem stuck into the ground and a little adjustable LED projector.

For illuminating a flower, a plant or simply to accompany us along a path.

Lamp with spike.

Un piccolo elfo luminoso da installare in giardino o all'interno di un vaso.

Uno stelo sottile incastrato nel terreno e un piccolo proiettore a LED orientabile.

Per illuminare un fiore, una pianta o semplicemente per accompagnare un percorso.

Lampada con picchetto.

GRILLO

Daniele Sprega / 2012

Floor-Outdoor / Direct / Outdoor

Material

AISI 316L Stainless Steel - Metal

Finish

.04 Matt Black

Note

Adjustable luminaire with AISI 316L Stainless steel stem.

Apparecchio orientabile con stelo in acciaio INOX AISI 316L.



GRILLO

4,2W

24V DC

2700K - 262lm / 3000K - 282lm

CRI >90

Driver not included

CE IP67

Matt Black - 2700K


Matt Black - 3000K

1A3570400.27.20

1A3570400.30.20

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica



Driver LED

110-240V

24V/25W/IP67/ON/OFF

Not included

1Z1120620

Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Additional stem 1m / Stelo supplementare 1m

Standard

AISI 316L stainless steel

Not included

1A3590000.00.00



Driver connector IP68 / Connettore driver IP68

1 Piece

Included


1A1660000.00.00

Daniele Sprega / 2012

GRILLO

Optional accessories / Accessori opzionali

Lighting modules / Corpi illuminanti



Additional LED head / Testa LED supplementare

Matt Black

24V DC - 4,2W - 2700K - 262lm - CRI>90

24V DC - 4,2W - 3000K - 282lm - CRI>90

Not included

1A3580400.27.20

1A3580400.30.20





HAZARD

Davide Groppi / 2023

We have always been thrilled by bare, abandoned lamps.
On the walls of mountain huts, in the countryside of our plain.

Unfinished works, lamps still to be decided,
ephemeral thoughts that become poetry.

Wall-mounted lamp with direct light for outdoor environments
with steel nail subject to natural oxidation over time.

Ci hanno sempre emozionato le lampadine abbandonate, nude.
Sui muri delle case di montagna, nelle campagne della nostra pianura.

Lavori non ancora finiti, lampade ancora da decidere,
pensieri effimeri che diventano poesia.

Lampada da parete a luce diretta per ambienti esterni
con chiodo in acciaio soggetto ad ossidazione naturale nel tempo.

HAZARD


Davide Groppi / 2023

Wall-Outdoor / Direct / Outdoor

Material Metal - Thermoplastic resin
Finish .00 Standard

Note Luminaire with red and black cables (1,5 m).

Apparecchio con cavi rosso e nero (1,5 m).




HAZARD
0,6W - E27
36V DC
2200K - 50lm
CRI 80
Bulb included
Driver not included
CE IP65

Standard - 2200K

1A4210000.22.20

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica



Driver LED		Not included
110-240V	36V/36W/IP67/ON/OFF	1Z1120590







IMU

Omar Carraglia / 2013

Light has found a home.
A lamp designed to welcome, illuminating the entrance.

La luce ha trovato casa.
Una lampada pensata per dare il benvenuto, per illuminare la soglia.

IMU

Omar Carraglia / 2013

Wall-Outdoor / Direct / Outdoor

Material

Metal


Finish

.00 Standard

Note


Matt black luminaire with matt red top.

Apparecchio nero opaco con tetto rosso opaco.

	IMU 5,5W Max 350mA DC 3000K - 306lm CRI >80 Driver not included CE IP65	Standard - 3000K 1A3550000.30.20
---	--	--

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica



Driver LED	Not included
220-240V(100-127V) 350mA/17W(15W)/IP68/ON/OFF	1Z0240880

Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Driver connector IP68 / Connettore driver IP68	Included
1 Piece	1A1660000.00.00





Light, waiting for Romeo.


An outdoor light, for walls or to illuminate the entrance.

La luce, aspettando Romeo.

Una luce per esterno, sulle pareti o per illuminare le soglie.

Wall-Outdoor / Diffuse / Outdoor

MaterialGlass - Metal
Finish.03 Matt White



JULIET
18W
220-240V - 50/60Hz
2700K - 827lm / 3000K - 865lm
CRI >80
TRIAC/IGBT
CE IP65

Matt White - 2700K - TRIAC/IGBT	1A3670300.27.02
Matt White - 3000K - TRIAC/IGBT	1A3670300.30.02

Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Driver connector IP68 / Connettore driver IP68	Included
1 Piece	1A1660000.00.00





A lantern. Soft and diffuse light.
A Slow-Light project for outdoors.

Una lanterna, luce morbida e diffusa.
Un progetto di slow-light per l'outdoor.

LENTA

Bestetti Associati - Davide Groppi / 2011

Floor-Outdoor / Diffuse / Outdoor

Material

Metal - Methacrylate - Polycarbonate


Finish

.03 Matt White

Note

Luminaire with black cable (5 m).

Apparecchio con cavo nero (5 m).



LENTA

Max 18W - E27

100-240V - 50/60Hz

Bulb not included

ON/OFF

CE IP65

Matt White - ON/OFF

1A3630300.00.00

Optional accessories / Accessori opzionali


Installation kit / Kit installazione

	Driver connector IP68 / Connettore driver IP68	Included
	1 Piece	1A1660000.00.00

Bulbs / Lampadine

	LED - E27	Not included
	220-240V - 13W - 200° - 2700K - 1521lm - CRI 80 - Energy Efficiency E	1Y0330650

Other accessories / Altri accessori

	Power shell	Not included
	IP65	1A2950000.00.00





NEURO OUTDOOR

Davide Groppi - Beppe Merlano / 2022

The idea is to bring light wherever you like.
A simple project: a cable and a LED.
Indoor version available.

È l'idea di portare la luce dove si desidera.
Un progetto semplice: un cavo e un modulo LED.
Disponibile nella versione indoor.

NEURO OUTDOOR


Davide Groppi - Beppe Merlano / 2022

Suspension-Outdoor / Direct / Outdoor

Material	AISI 316L Stainless Steel - Metal		
Finish	.04 Matt Black	.32	Copper Oxide

Note Luminaire with black cable (10 m).

Apparecchio con cavo nero (10 m).



NEURO OUTDOOR

4,2W
24V DC
2700K - 262lm / 3000K - 282lm
CRI >90
Driver not included

CE IP67

Matt Black - 2700K

Matt Black - 3000K

Copper Oxide - 2700K

Copper Oxide - 3000K

1A4030400.27.20


1A4030400.30.20

1A4033200.27.20

1A4033200.30.20

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica



Driver LED		Not included
110-240V	24V/25W/IP67/ON/OFF	1Z1120620

Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Driver connector IP68 / Connettore driver IP68		Included
1 Piece		1A1660000.00.00




NUIT

Maurici Ginés / 2023

Night has always been a source of inspiration.
We walk, and we are not alone.
Nuit is a small travel companion that draws our night-time journeys.

La notte è sempre fonte di ispirazione.
Camminiamo e non siamo soli.
Nuit è una piccola compagna di viaggio che disegna i nostri transiti notturni.

Outdoor-Wall / Diffuse / Indoor-Outdoor			
Material	Metal		
Finish	.03 Matt White	.27 Gravity Black	.38 Blasted Inox
Note	Semi-recessed luminaire - For installation: minimum space for mounting 55 mm.		
	Apparecchio da semincasso - Per installazione: spazio minimo per incasso 55 mm.		



NUIT

1W
24V DC
2700K - 45lm / 3000K - 50lm
CRI 90
Driver not included




Matt White - 2700K
Matt White - 3000K
Gravity Black - 2700K
Gravity Black - 3000K
Blasted Inox - 2700K
Blasted Inox - 3000K

1A1320300.27.20
1A1320300.30.20
1A1322700.27.20
1A1322700.30.20
1A1323800.27.20
1A1323800.30.20

Compulsory accessories / Accessori obbligatori

Installation kit / Kit installazione




Concrete box / Cassaforma per cemento armato		Not included
		1A4460000.00.00



Plasterboard frame 12,5 mm / Cornice per cartongesso 12,5 mm		Not included
Matt White	Cut-out 100 x 100 mm - Minimum space for mounting 120 mm	1A4470000.00.00

Electrical power supply / Alimentazione elettrica



Driver LED		Not included
110-240V	24V/25W/IP67/ON/OFF	1Z1120620

Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Adapter plasterboard frame 25 mm / Adattatore cornice per cartongesso 25 mm		Not included
Standard		1A5030000.00.00





ORIGINE OUTDOOR

Davide Groppi - Giorgio Rava / 2020

From the Latin "origo", start, birth, source.

It appears like a bud emerging from the ground and soaring upwards towards the sky, a stem that becomes increasingly thinner. Mysterious, enigmatic but comfortable, it combines the fascination of the unknown with the pleasure of a sophisticated and elegant ambient light.

Origine sculpts and enhances every environment with its indirect light, which is intentionally non-invasive, graphic and fascinating.

Indoor version available.

**AZ Award 2021 and People's Choice
Archiproducts Design Award 2020**

Dal latino "origo", inizio, nascita, fonte.

Evoca un germoglio che emerge dalla terra e si slancia verso il cielo, lo stelo che diventa sempre più sottile. Misteriosa, enigmatica ma confortevole, unisce il fascino dell'incognito al piacere di una luce d'ambiente sofisticata ed elegante.

Origine scolpisce e valorizza ogni ambiente con la sua luce indiretta, volutamente non invasiva, grafica e affascinante.

Disponibile nella versione indoor.

**AZ Award 2021 e People's Choice
Archiproducts Design Award 2020**

ORIGINE OUTDOOR

Davide Groppi - Giorgio Rava / 2020

Outdoor-Floor / Indirect / Outdoor

Material Fiberglass - Metal
Finish .04 Matt Black

Note Luminaire with black cable (5 m).

Apparecchio con cavo nero (5 m).



ORIGINE OUTDOOR

35W
24V DC
2700K - 2872lm / 3000K - 2930lm
CRI >80
Driver not included

CE IP65

Matt Black - 2700K


Matt Black - 3000K

1A2480400.27.20

1A2480400.30.20

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica



Driver LED		Not included
100-240V	24V/60W/IP67/1-10V	1Z1120260

Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Driver connector IP68 / Connettore driver IP68		Included
1 Piece	1A1660000.00.00	






A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.



A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

Recessed-Outdoor / Direct / Outdoor

Material	Glass - Metal
Finish	.10 Stainless Steel


	OUT 58 - 39° 7W 24V DC 3000K - 546lm Beam 39° CRI >90 Driver not included CE IP67	Stainless Steel - 3000K	1A1551000.30.20
---	---	-------------------------	-----------------

Compulsory accessories / Accessori obbligatori

Installation kit / Kit installazione

	Installation box / Cassaforma installazione Cut-out 55 mm - Minimum space for mounting 110 mm	Not included
		1A1560000.00.00

Electrical power supply / Alimentazione elettrica


	Driver LED 110-240V	24V/25W/IP67/ON/OFF	Not included
			1Z1120620

Optional accessories / Accessori opzionali

Installation kit / Kit installazione

	Driver connector IP68 / Connettore driver IP68 1 Piece	Included
		1A1660000.00.00





A tool to light.

The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.

Elemento di luce.

Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.

Recessed-Outdoor / Direct / Outdoor

Material	Glass - Metal
Finish	.10 Stainless Steel

	OUT 100 - 15° 20W Max 500mA DC 3000K - 2058lm Beam 15° CRI >90 Driver not included CE IP67	Stainless Steel - 3000K	1A1571000.30.20
	OUT 100 - 23° 20W Max 500mA DC 3000K - 2058lm Beam 23° CRI >90 Driver not included CE IP67	Stainless Steel - 3000K	1A1581000.30.20

Compulsory accessories / Accessori obbligatori


Installation kit / Kit installazione



Installation box / Cassaforma installazione	Not included
Cut-out 94 mm - Minimum space for mounting 160 mm	1A1590000.00.00

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica



Driver LED	Not included
220-240V(110-127V) 500mA/24W(15W)/IP68/ON/OFF	1Z0241170

Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Driver connector IP68 / Connettore driver IP68	Not included
1 Piece	1A1660000.00.00



Q²

Alberto Zattin / 2006


A piece of architecture to be used in space.
A concrete cube that allows you to understand volumes and architecture in an
unusual and sometimes unprecedented way.
Indoor version available.

Un pezzo di architettura da utilizzare nello spazio.
Un cubo realizzato in cemento che permette di interpretare i volumi e le architetture in
modo inconsueto e talvolta inedito.
Disponibile nella versione indoor.

Q²

Alberto Zattin / 2006

Floor-Outdoor / Direct / Outdoor	
Material	Cement - Metal
Finish	.00 Standard
Note	Luminaire with black cable (2,5 m).
	Apparecchio con cavo nero (2,5 m).




Q²
20W
Max 500mA DC
3000K - 2058lm
CRI >90
Driver not included
CE IP67

Standard - 3000K

1A1150000.30.20

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica



Driver LED		Not included
220-240V(110-127V)	500mA/24W(15W)/IP68/ON/OFF	1Z0241170

Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Driver connector IP68 / Connettore driver IP68		Included
1 Piece		1A1660000.00.00





SAMPEI 440 OUTDOOR

Enzo Calabrese - Davide Groppi / 2011


A special project, an authentic ready-made.
Obtained from a fishing flexible rod, it is a delicate and elegant sign, which brings to
mind the subtle branches of a willow tree
or bamboo canes floating on a light breeze.
Sampei is an unexpected gift, it is the magic of looking up, using light as a hook,
and being amazed by so much weightlessness.
Indoor version available.

Un progetto speciale, un autentico ready-made.
Ricavata da una canna da pesca flessibile, è un segno delicato ed elegante, che fa
pensare a effimeri rami di salice, a canne di bambù mosse da un debole vento.
Sampei è un regalo inaspettato, è la magia di guardare in alto, usando la luce come amo,
e stupirsi di tanta leggerezza.
Disponibile nella versione indoor.

SAMPEI 440 OUTDOOR

Enzo Calabrese - Davide Groppi / 2011

Floor-Outdoor / Direct / Outdoor		
Material	Fiberglass - Metal	
Finish	.03 Matt White	.04 Matt Black
Note	Adjustable luminaire with black cable (5,5 m).	
	Apparecchio orientabile con cavo nero (5,5 m).	



SAMPEI 440 OUTDOOR


8,4W
Max 700mA DC
2700K - 639lm / 3000K - 639lm
CRI >90
Driver not included

CE IP65

Matt White - 2700K	1A3770300.27.20
Matt White - 3000K	1A3770300.30.20
Matt Black - 2700K	1A3770400.27.20
Matt Black - 3000K	1A3770400.30.20

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica



Driver LED		Not included
220-240V(100-127V)	700mA/30W(15W)/IP68/ON/OFF	1Z0241110

Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Driver connector IP68 / Connettore driver IP68		Included
1 Piece		1A1660000.00.00





SHOJI OUTDOOR

Davide Groppi - Paola Lenti / 2013

Exploiting the technique used by Paola Lenti for her beautiful works, we designed a nylon lampshade, strictly hand-stitched and hand-made. Indoor version available.

Sfruttando la tecnica utilizzata da Paola Lenti per la realizzazione dei suoi meravigliosi oggetti, abbiamo pensato ad un paralume in nylon rigorosamente cucito e confezionato a mano. Disponibile nella versione indoor.

SHOJI OUTDOOR

Davide Groppi - Paola Lenti / 2013

Floor-Outdoor / Diffuse / Outdoor

Material

Metal - PBT - Polycarbonate


Finish

.00 Standard

Note

Luminaire with black cable (5 m).

Apparecchio con cavo nero (5 m).



SHOJI

Max 18W - E27

100-240V - 50/60Hz

Bulb not included

ON/OFF

CE IP65

Standard - ON/OFF

1A3640000.00.00

Optional accessories / Accessori opzionali

Installation kit / Kit installazione




Driver connector IP68 / Connettore driver IP68	Included
1 Piece	1A1660000.00.00

Bulbs / Lampadine




LED - E27	Not included
220-240V - 13W - 200° - 2700K - 1521lm - CRI 80 - Energy Efficiency E	1Y0330650

Other accessories / Altri accessori



Power shell / Power shell	Not included
IP65	1A2950000.00.00





A tool to light.

**The luminaire is pure form, a simple container for the light source.
Light is incorporated into the space, becoming an architectural element.**

Elemento di luce.

**Il corpo illuminante è forma pura, semplice contenitore della fonte luminosa.
La luce si integra con lo spazio diventando elemento architettonico.**

SPOT IP65


/ 2018

Wall-Outdoor / Direct / Outdoor

Material	Metal	
Finish	.03 Matt White	.04 Matt Black

Note Adjustable luminaire.

Apparecchio orientabile.



SPOT IP65

8,4W

Max 700mA DC

2700K - 639lm / 3000K - 639lm

CRI >90



Matt White - 2700K

Matt White - 3000K

Matt Black - 2700K

Matt Black - 3000K

1A3650300.27.20


1A3650300.30.20

1A3650400.27.20

1A3650400.30.20

Compulsory accessories / Accessori obbligatori

Electrical power supply / Alimentazione elettrica



Driver LED	Not included
220-240V(100-127V) 700mA/30W(15W)/IP68/ON/OFF	1Z0241110

Optional accessories / Accessori opzionali

Installation kit / Kit installazione



Driver connector IP68 / Connettore driver IP68	Included
1 Piece	1A1660000.00.00








BULBS / LAMPADINE

	Socket	Voltage	Power	Beam Angle	CCT	Lumens	CRI	Energy Efficiency	Dimmable	Code
	E14	220-240V	4,5W		2700K	470lm	>80	F	X	1Y0041410
	E27	220-240V	7W	360°	2700K	806lm	80	E	X	1Y2080010
	E27	220-240V	11,2W	360°	2700K	1521lm	90	D	X	1Y0330790
	E27	220-240V	9,5W	25°	3000K	760lm	80	F	X	1Y0330730
	E27	220-240V	21W	200°	2700K	2452lm	>80	E	X	1Y0041470
	E27	220-240V	13W	200°	2700K	1521lm	80	E	-	1Y0330650
	GU4	12V	20W	24°	2700K	200lm	80	G	-	1Y0330450
	GU5,3	12V	6,7W	36°	3000K	440lm	97	G	X	1Y0330530
	GU10	230V	7,5W	10°	2700K	390lm	95	G	X	1Y1580210
	GU10	230V	7,5W	10°	3000K	410lm	95	G	X	1Y1580010
	GU10	220-240V	5,5W	25°	3000K	375lm	97	G	X	1Y0330500
	GU10	220-240V	4,9W	120°	3000K	550lm	80	E	-	1Y0330740








DG111 LED MODULES / MODULI LED DG111












	Current	Power	Beam Angle	CCT	Lumens	CRI	Energy Efficiency	Dimmable	Code
	350mA DC	11,7W	15°	2700K	1336lm	90	F	X	1A4700000.27.20
	350mA DC	11,7W	15°	3000K	1364lm	90	F	X	1A4700000.30.20
	350mA DC	11,7W	22°	2700K	1266lm	90	F	X	1A3900000.27.20
	350mA DC	11,7W	22°	3000K	1323lm	90	F	X	1A3900000.30.20
	350mA DC	11,7W	36°	2700K	1508lm	90	F	X	1A3890000.27.20
	350mA DC	11,7W	36°	3000K	1578lm	90	F	X	1A3890000.30.20
	500mA DC	16,7W	15°	2700K	1648lm	90	F	X	1A4700000.27.20
	500mA DC	16,7W	15°	3000K	1682lm	90	F	X	1A4700000.30.20
	500mA DC	16,7W	22°	2700K	1859lm	90	F	X	1A3890000.27.20
	500mA DC	16,7W	22°	3000K	1945lm	90	F	X	1A3890000.30.20
	500mA DC	16,7W	36°	2700K	1808lm	90	F	X	1A3900000.27.20
	500mA DC	16,7W	36°	3000K	1890lm	90	F	X	1A3900000.30.20

DRIVERS


	Power	Input	Output	Dimming	Protection	Code
	60W(40W)	220-240V(100-127V)	1000mA	DALI	IP20	1Z0241140.1000
	50W	230-240V	12V	TRIAC/IGBT	IP20	1Z0240440
	50W	100-240V	24V	ON/OFF	IP20	1Z1120490
	80W	100-240V	24V	ON/OFF	IP20	1Z1120440
	20W	220-240V	24V	TRIAC/IGBT	IP20	1Z0240850.24
	16W(15W)	220-240V(100-127V)	24V	DALI	IP20	1Z0241180.24
	20W(15W)	220-240V(100-127V)	24V	PUSH	IP20	1Z0240870.24
	17W	220-240V	350mA	TRIAC/IGBT	IP20	1Z0240850.350
	17W(15W)	220-240V(100-127V)	350mA	DALI	IP20	1Z0241180.350
	18W(15W)	220-240V(100-127V)	350mA	PUSH - 1-10V	IP20	1Z0240870.350
	18W(18W)	220-240V(100-127V)	350mA	DALI - PUSH - 1-10V	IP20	1Z0240530.350

DRIVERS

	Power	Input	Output	Dimming	Protection	Code
	60W	100-240V	48V	1-10V	IP20	1Z1120600
	60W	220-240V	48V	DALI	IP20	1Z0830820
	20W	220-240V	500mA	TRIAC/IGBT	IP20	1Z0240850.500
	36,4W	220-240V	500mA	TRIAC/IGBT	IP20	1Z2270010.500
	20W(15W)	220-240V(100-127V)	500mA	DALI	IP20	1Z0241180.500
	20W(15W)	220-240V(100-127V)	500mA	PUSH	IP20	1Z0240840.500
	20W(15W)	220-240V(100-127V)	500mA	PUSH - 1-10V	IP20	1Z0240870.500
	25W(13,5W)	220-240V(110-127V)	500mA	DALI - PUSH - 1-10V	IP20	1Z0241270.500
	15W	100-240V	5V	ON/OFF	IP20	1Z1470180
	150W	100-240V	24V	1-10V	IP67	1Z1120500
	60W	100-240V	24V	1-10V	IP67	1Z1120260

	Power	Input	Output	Dimming	Protection	Code
	96W	100-240V	24V	1-10V	IP67	1Z1120540
	25W	110-240V	24V	ON/OFF	IP67	1Z1120620
	36W	110-240V	36V	ON/OFF	IP67	1Z1120590
	150W	100-240V	48V	1-10V	IP67	1Z1120250
	240W	100-240V	48V	1-10V	IP67	1Z1120390
	320W	100-240V	48V	1-10V	IP67	1Z1120380
	60W	100-240V	48V	ON/OFF	IP67	1Z1120640
	80W	100-240V	48V	1-10V	IP67	1Z1120400
	17W(15W)	220-240V(100-127V)	350mA	ON/OFF	IP68	1Z0240880
	24W(15W)	220-240V(110-127V)	500mA	ON/OFF	IP68	1Z0241170
	30W(15W)	220-240V(100-127V)	700mA	ON/OFF	IP68	1Z0241110

COMMON ACCESSORIES / ACCESSORI COMUNI



	Power	Input	Output	Dimming	Protection	Code
Controller Casambi - Radio signal 2.4 - 2.486 GHz						
				DALI	IP20	1Z0400740
		220-240V - 50Hz		1-10 V	IP20	1Z0400660
	(75W) 150W	(110V) 240V - 50/60Hz		TRIAC	IP20	1Z0400670

COMMON ACCESSORIES / ACCESSORI COMUNI

	Size	Cut-out	Finish	Code
Plasterboard trapdoors / Botole in cartongesso				
	200 x 200 mm	205 x 205 mm	Standard	1A3780000.00.00
	400 x 400 mm	415 x 415 mm	Standard	1A3790000.00.00
Clamp / Bloccacavo				
	Ø 50 x 20 mm		Matt White	1A3270300.00.00
			Matt Black	1A3270400.00.00
Driver connector IP68 / Connettore driver IP68				
			Standard	1A1660000.00.00

SUSPENSION FIXING KIT / KIT DI FISSAGGIO PER SOSPENSIONE

Recessed fixing kit / Kit fissaggio ad incasso



Fixing kit for 12.5 mm plasterboard
Kit fissaggio per cartongesso 12,5 mm

Magnetic fixing
Fissaggio magnetico




62

Model	Use	Product reference	Finish	Code
Recessed fixing kit.01	For suspension cables	REFLEX S 1	Matt White	1X0000300.01.00
		SHANGHAI 2 SIMBIOSI SOTTILE 2 SOTTILE 2 DE	Matt Black	1X0000400.01.00
Recessed fixing kit.02	For electrical cables	MAGIA	Matt White	1X0000300.02.00
			Matt Black	1X0000400.02.00
Recessed fixing kit.03	For suspension cables	FOSBURY MASAI 1 MASAI 2 SPY SPY DE	Matt White	1X0000300.03.00
			Matt Black	1X0000400.03.00
Recessed fixing kit.04	For electrical cables	ASINTOTO REFLEX S 2 SOTTILE 2 SOTTILE 2 DE	Matt White	1X0000300.04.00
			Matt Black	1X0000400.04.00
Recessed fixing kit.05	For electrical cables	LOUIS XIV 2 SOTTOSOPRA 2	Matt White	1X0000300.05.00
			Matt Black	1X0000400.05.00

SUSPENSION FIXING KIT / KIT DI FISSAGGIO PER SOSPENSIONE

Ceiling fixing kit / Kit fissaggio a soffitto




Back plate for masonry ceilings
Back plate per soffitti in muratura

Magnetic fixing
Fissaggio magnetico



77

Model	Use	Product reference	Finish	Code
Ceiling fixing kit.01	For suspension cables	REFLEX S 1 SHANGHAI 1 SHANGHAI 2 SIMBIOSI SOTTILE 2 SOTTILE 2 DE	Matt White	1X0010300.01.00
			Matt Black	1X0010400.01.00
Ceiling fixing kit.02	For electrical cables	MAGIA	Matt White	1X0010300.02.00
			Matt Black	1X0010400.02.00
Ceiling fixing kit.03	For suspension cables	FOSBURY MASAI 1 MASAI 2 SPY SPY DE	Matt White	1X0010300.03.00
			Matt Black	1X0010400.03.00
Ceiling fixing kit.04	For electrical cables	ASINTOTO REFLEX S 2 SOTTILE 2 SOTTILE 2 DE	Matt White	1X0010300.04.00
			Matt Black	1X0010400.04.00
Back plate	For masonry ceilings		Matt White	1X0050300.01.00



120

General terms.

This price list replaces any other previous one.

Davide Groppi srl reserves the right to change its products without notice. In this case, the descriptions printed here are not binding.

The sizes are expressed in millimeters.

Prices are in Euro, excluding VAT.

Shipment.

Returned merchandise must be authorized in writing by Davide Groppi srl.

Any claim must be made in writing to Davide Groppi srl within 7 days of the delivery date. If not, will not be accepted.

Warranty.

All products are guaranteed for 24 months from the date of delivery.

The warranty is not valid for damage caused by third parties.

Any damage resulting from improper installation or changes to products cannot be considered the responsibility of Davide Groppi srl.

Rights.

No part of this price list may be reproduced or transmitted in any form or by any means: electronic, mechanical or otherwise, without the written permission of Davide Groppi srl.

Jurisdiction.

For any dispute, Piacenza, Italy, will be the court of jurisdiction.

Privacy.

Davide Groppi srl protects the confidentiality of personal data as provided to articles 12, 13 and 14 of the European Regulation n. 679/2016 (GDPR).

Condizioni generali.

Il presente listino prezzi annulla e sostituisce ogni edizione precedente.

Davide Groppi srl si riserva la facoltà di modificare i propri prodotti senza preavviso pertanto le descrizioni riportate in questo documento non sono vincolanti.

Le dimensioni sono espresse in millimetri.

I prezzi sono espressi in Euro IVA esclusa.

Spedizioni.

Resi di materiale sono accettati previa autorizzazione scritta dell'azienda.

Eventuali reclami sono considerati solo se comunicati per iscritto entro 7 giorni dalla data di consegna della merce.

Garanzia.

I prodotti di Davide Groppi srl sono garantiti per 24 mesi dalla data di consegna.

La garanzia non ha valore per danni causati da terzi.

Eventuali danni derivanti da errata installazione o da modifiche apportate ai prodotti non possono essere considerati responsabilità di Davide Groppi srl.

Diritti.

Nessuna parte di questo listino prezzi può essere riprodotta o trasmessa in qualsiasi forma o con qualsiasi mezzo elettronico, meccanico o altro senza l'autorizzazione scritta di Davide Groppi srl.

Foro Competente.

Per eventuali controversie è competente il Foro di Piacenza.

Privacy.

La Davide Groppi srl tutela la riservatezza dei dati personali come previsto degli art. 12, 13 e 14 del Regolamento Europeo n. 679/2016 (GDPR).

Davide Groppi srl is constantly revising its products in order to offer the best and latest technology available.

This is why its catalogues and technical notes are in constant evolution.

You can find the latest information and technical updates on our website www.davidegroppi.com

La Davide Groppi srl revisiona costantemente i propri prodotti per poter offrire sempre il meglio della tecnologia disponibile.

Per questo motivo i cataloghi e le schede prodotto sono in continua evoluzione.

Le informazioni e i dettagli tecnici più aggiornati sono pubblicati sul nostro sito www.davidegroppi.com

davidegroppi.com

Davide Groppi srl
Via Belizzi 20 / 22
29122 Piacenza - Italia
Ph. +39.0523.571590
info@davidegroppi.com

Davide Groppi srl © 2024
Company with sole shareholder under the direction and coordination of IDB spa